Isabelle/FOL — First-Order Logic

Larry Paulson and Markus Wenzel

October 24, 2026

Contents

1 Intuitionistic first-order logic **1**
1.1 Syntax and axiomatic basis . . . 1
1.1.1 Equality . . . 1
1.1.2 Propositional logic . . . 1
1.1.3 Quantifiers . . . 2
1.1.4 Definitions . . . 2
1.1.5 Old-style ASCII syntax . . . 3
1.2 Lemmas and proof tools . . . 3
1.2.1 Sequent-style elimination rules for $\wedge$ $\longrightarrow$ and $\forall$ . . . 3
1.2.2 Negation rules, which translate between $\neg$ P and P $\longrightarrow$ *False* . . . 4
1.2.3 Modus Ponens Tactics . . . 4
1.3 If-and-only-if . . . 4
1.3.1 Destruct rules for $\longleftrightarrow$ similar to Modus Ponens . . . 5
1.4 Unique existence . . . 5
1.4.1 $\longleftrightarrow$ congruence rules for simplification . . . 5
1.5 Equality rules . . . 6
1.6 Simplifications of assumed implications . . . 7
1.7 Intuitionistic Reasoning . . . 8
1.8 Polymorphic congruence rules . . . 9
1.8.1 Congruence rules for predicate letters . . . 10
1.9 Atomizing meta-level rules . . . 10
1.10 Atomizing elimination rules . . . 10
1.11 Calculational rules . . . 11
1.12 "Let" declarations . . . 11
1.13 Intuitionistic simplification rules . . . 12
1.13.1 Conversion into rewrite rules . . . 13
1.13.2 More rewrite rules . . . 13

2 Classical first-order logic **14**
2.1 The classical axiom 14
2.2 Lemmas and proof tools 14
2.2.1 Classical introduction rules for $\vee$ and $\exists$ 14
2.3 Special elimination rules 15
2.3.1 Tactics for implication and contradiction 15

3 Classical Reasoner **16**
3.1 Classical simplification rules 17
3.1.1 Miniscoping: pushing quantifiers in 17
3.1.2 Named rewrite rules proved for IFOL 18
3.2 Other simple lemmas 18
3.2.1 Monotonicity of implications 19
3.3 Proof by cases and induction 19

1 Intuitionistic first-order logic

theory *IFOL*
imports *Pure*
abbrevs *?<* = $\exists_{\leq 1}$
begin

⟨*ML*⟩

1.1 Syntax and axiomatic basis

⟨*ML*⟩

class *term*
default-sort ‹*term*›

typedecl *o*

judgment
Trueprop :: ‹*o* ⇒ *prop*› (‹(‹*notation=judgment*›-)› *5*)

1.1.1 Equality

axiomatization
eq :: ‹['*a*, '*a*] ⇒ *o*› (**infixl** ‹=› *50*)
where
refl: ‹*a* = *a*› **and**
subst: ‹*a* = *b* ⟹ *P*(*a*) ⟹ *P*(*b*)›

1.1.2 Propositional logic

axiomatization
False :: ‹*o*› **and**

conj :: ‹[*o*, *o*] => *o*› (**infixr** ‹∧› *35*) **and**
disj :: ‹[*o*, *o*] => *o*› (**infixr** ‹∨› *30*) **and**
imp :: ‹[*o*, *o*] => *o*› (**infixr** ‹⟶› *25*)
where
conjI: ‹⟦*P*; *Q*⟧ ⟹ *P* ∧ *Q*› **and**
conjunct1: ‹*P* ∧ *Q* ⟹ *P*› **and**
conjunct2: ‹*P* ∧ *Q* ⟹ *Q*› **and**

disjI1: ‹*P* ⟹ *P* ∨ *Q*› **and**
disjI2: ‹*Q* ⟹ *P* ∨ *Q*› **and**
disjE: ‹⟦*P* ∨ *Q*; *P* ⟹ *R*; *Q* ⟹ *R*⟧ ⟹ *R*› **and**

impI: ‹(*P* ⟹ *Q*) ⟹ *P* ⟶ *Q*› **and**
mp: ‹⟦*P* ⟶ *Q*; *P*⟧ ⟹ *Q*› **and**

FalseE: ‹*False* ⟹ *P*›

1.1.3 Quantifiers

axiomatization
All :: ‹('*a* ⇒ *o*) ⇒ *o*› (**binder** ‹∀› *10*) **and**
Ex :: ‹('*a* ⇒ *o*) ⇒ *o*› (**binder** ‹∃› *10*)
where
allI: ‹(⋀*x*. *P*(*x*)) ⟹ (∀ *x*. *P*(*x*))› **and**
spec: ‹(∀ *x*. *P*(*x*)) ⟹ *P*(*x*)› **and**
exI: ‹*P*(*x*) ⟹ (∃ *x*. *P*(*x*))› **and**
exE: ‹⟦∃ *x*. *P*(*x*); ⋀*x*. *P*(*x*) ⟹ *R*⟧ ⟹ *R*›

1.1.4 Definitions

definition ‹*True* ≡ *False* ⟶ *False*›

definition *Not* (‹(‹*open-block notation*=‹*prefix* ¬››¬ -)› [*40*] *40*)
where *not-def*: ‹¬ *P* ≡ *P* ⟶ *False*›

definition *iff* (**infixr** ‹⟷› *25*)
where ‹*P* ⟷ *Q* ≡ (*P* ⟶ *Q*) ∧ (*Q* ⟶ *P*)›

definition *Uniq* :: ('*a* ⇒ *o*) ⇒ *o*
where ‹*Uniq*(*P*) ≡ (∀ *x y*. *P*(*x*) ⟶ *P*(*y*) ⟶ *y* = *x*)›

definition *Ex1* :: ‹('*a* ⇒ *o*) ⇒ *o*› (**binder** ‹∃!› *10*)
where *ex1-def*: ‹∃!*x*. *P*(*x*) ≡ ∃ *x*. *P*(*x*) ∧ (∀ *y*. *P*(*y*) ⟶ *y* = *x*)›

axiomatization where — Reflection, admissible
eq-reflection: ‹(*x* = *y*) ⟹ (*x* ≡ *y*)› **and**
iff-reflection: ‹(*P* ⟷ *Q*) ⟹ (*P* ≡ *Q*)›

abbreviation *not-equal* :: ‹['*a*, '*a*] ⇒ *o*› (**infixl** ‹≠› *50*)
where ‹*x* ≠ *y* ≡ ¬ (*x* = *y*)›

syntax -*Uniq* :: *pttrn* ⇒ *o* ⇒ *o* (‹(‹*indent=2 notation=‹binder* ∃≤1››∃≤1 -./ -)› [*0*, *10*] *10*)
syntax-consts -*Uniq* ⇌ *Uniq*
translations ∃≤1*x*. *P* ⇌ *CONST Uniq* (λ*x*. *P*)
⟨*ML*⟩

1.1.5 Old-style ASCII syntax

notation (*ASCII*)
not-equal (**infixl** ‹~=› *50*) **and**
Not (‹(‹*open-block notation=‹prefix* ~››~ -)› [*40*] *40*) **and**
conj (**infixr** ‹&› *35*) **and**
disj (**infixr** ‹|› *30*) **and**
All (**binder** ‹*ALL* › *10*) **and**
Ex (**binder** ‹*EX* › *10*) **and**
Ex1 (**binder** ‹*EX*! › *10*) **and**
imp (**infixr** ‹–>› *25*) **and**
iff (**infixr** ‹<–>› *25*)

1.2 Lemmas and proof tools

lemmas *strip* = *impI allI*

lemma *TrueI*: ‹*True*›
⟨*proof*⟩

1.2.1 Sequent-style elimination rules for ∧ ⟶ and ∀

lemma *conjE*:
assumes *major*: ‹*P* ∧ *Q*›
and *r*: ‹⟦*P*; *Q*⟧ ⟹ *R*›
shows ‹*R*›
⟨*proof*⟩

lemma *impE*:
assumes *major*: ‹*P* ⟶ *Q*›
and ‹*P*›
and *r*: ‹*Q* ⟹ *R*›
shows ‹*R*›
⟨*proof*⟩

lemma *allE*:
assumes *major*: ‹∀ *x*. *P*(*x*)›
and *r*: ‹*P*(*x*) ⟹ *R*›
shows ‹*R*›
⟨*proof*⟩

Duplicates the quantifier; for use with `eresolve_tac`.

lemma *all-dupE*:

assumes *major*: ‹$\forall x.\ P(x)$›
and *r*: ‹$[\![P(x); \forall x.\ P(x)]\!] \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

1.2.2 Negation rules, which translate between $\neg P$ and $P \longrightarrow False$

lemma *notI*: ‹$(P \Longrightarrow False) \Longrightarrow \neg P$›
⟨*proof*⟩

lemma *notE*: ‹$[\![\neg P; P]\!] \Longrightarrow R$›
⟨*proof*⟩

lemma *rev-notE*: ‹$[\![P; \neg P]\!] \Longrightarrow R$›
⟨*proof*⟩

This is useful with the special implication rules for each kind of P.

lemma *not-to-imp*:
assumes ‹$\neg P$›
and *r*: ‹$P \longrightarrow False \Longrightarrow Q$›
shows ‹Q›
⟨*proof*⟩

For substitution into an assumption P, reduce Q to $P \longrightarrow Q$, substitute into this implication, then apply *impI* to move P back into the assumptions.

lemma *rev-mp*: ‹$[\![P; P \longrightarrow Q]\!] \Longrightarrow Q$›
⟨*proof*⟩

Contrapositive of an inference rule.

lemma *contrapos*:
assumes *major*: ‹$\neg Q$›
and *minor*: ‹$P \Longrightarrow Q$›
shows ‹$\neg P$›
⟨*proof*⟩

1.2.3 Modus Ponens Tactics

Finds $P \longrightarrow Q$ and P in the assumptions, replaces implication by Q.

⟨*ML*⟩

1.3 If-and-only-if

lemma *iffI*: ‹$[\![P \Longrightarrow Q; Q \Longrightarrow P]\!] \Longrightarrow P \longleftrightarrow Q$›
⟨*proof*⟩

lemma *iffE*:
assumes *major*: ‹$P \longleftrightarrow Q$›
and *r*: ‹$[\![P \longrightarrow Q; Q \longrightarrow P]\!] \Longrightarrow R$›

shows ‹*R*›
⟨*proof*⟩

1.3.1 Destruct rules for ⟷ similar to Modus Ponens

lemma *iffD1*: ‹⟦*P* ⟷ *Q*; *P*⟧ ⟹ *Q*›
⟨*proof*⟩

lemma *iffD2*: ‹⟦*P* ⟷ *Q*; *Q*⟧ ⟹ *P*›
⟨*proof*⟩

lemma *rev-iffD1*: ‹⟦*P*; *P* ⟷ *Q*⟧ ⟹ *Q*›
⟨*proof*⟩

lemma *rev-iffD2*: ‹⟦*Q*; *P* ⟷ *Q*⟧ ⟹ *P*›
⟨*proof*⟩

lemma *iff-refl*: ‹*P* ⟷ *P*›
⟨*proof*⟩

lemma *iff-sym*: ‹*Q* ⟷ *P* ⟹ *P* ⟷ *Q*›
⟨*proof*⟩

lemma *iff-trans*: ‹⟦*P* ⟷ *Q*; *Q* ⟷ *R*⟧ ⟹ *P* ⟷ *R*›
⟨*proof*⟩

1.4 Unique existence

NOTE THAT the following 2 quantifications:

- ∃!*x* such that [∃!*y* such that P(x,y)] (sequential)
- ∃!*x*,*y* such that P(x,y) (simultaneous)

do NOT mean the same thing. The parser treats ∃!*x y*.*P*(*x*,*y*) as sequential.

lemma *ex1I*: ‹*P*(*a*) ⟹ (⋀*x*. *P*(*x*) ⟹ *x* = *a*) ⟹ ∃!*x*. *P*(*x*)›
⟨*proof*⟩

Sometimes easier to use: the premises have no shared variables. Safe!

lemma *ex-ex1I*: ‹∃ *x*. *P*(*x*) ⟹ (⋀*x y*. ⟦*P*(*x*); *P*(*y*)⟧ ⟹ *x* = *y*) ⟹ ∃!*x*. *P*(*x*)›
⟨*proof*⟩

lemma *ex1E*: ‹∃! *x*. *P*(*x*) ⟹ (⋀*x*. ⟦*P*(*x*); ∀ *y*. *P*(*y*) ⟶ *y* = *x*⟧ ⟹ *R*) ⟹ *R*›
⟨*proof*⟩

1.4.1 ⟷ congruence rules for simplification

Use *iffE* on a premise. For *conj-cong*, *imp-cong*, *all-cong*, *ex-cong*.

⟨*ML*⟩

lemma *conj-cong*:
assumes ‹$P \longleftrightarrow P'$›
and ‹$P' \Longrightarrow Q \longleftrightarrow Q'$›
shows ‹$(P \wedge Q) \longleftrightarrow (P' \wedge Q')$›
⟨*proof*⟩

Reversed congruence rule! Used in ZF/Order.

lemma *conj-cong2*:
assumes ‹$P \longleftrightarrow P'$›
and ‹$P' \Longrightarrow Q \longleftrightarrow Q'$›
shows ‹$(Q \wedge P) \longleftrightarrow (Q' \wedge P')$›
⟨*proof*⟩

lemma *disj-cong*:
assumes ‹$P \longleftrightarrow P'$› **and** ‹$Q \longleftrightarrow Q'$›
shows ‹$(P \vee Q) \longleftrightarrow (P' \vee Q')$›
⟨*proof*⟩

lemma *imp-cong*:
assumes ‹$P \longleftrightarrow P'$›
and ‹$P' \Longrightarrow Q \longleftrightarrow Q'$›
shows ‹$(P \longrightarrow Q) \longleftrightarrow (P' \longrightarrow Q')$›
⟨*proof*⟩

lemma *iff-cong*: ‹$[\![P \longleftrightarrow P';\ Q \longleftrightarrow Q']\!] \Longrightarrow (P \longleftrightarrow Q) \longleftrightarrow (P' \longleftrightarrow Q')$›
⟨*proof*⟩

lemma *not-cong*: ‹$P \longleftrightarrow P' \Longrightarrow \neg P \longleftrightarrow \neg P'$›
⟨*proof*⟩

lemma *all-cong*:
assumes ‹$\bigwedge x.\ P(x) \longleftrightarrow Q(x)$›
shows ‹$(\forall x.\ P(x)) \longleftrightarrow (\forall x.\ Q(x))$›
⟨*proof*⟩

lemma *ex-cong*:
assumes ‹$\bigwedge x.\ P(x) \longleftrightarrow Q(x)$›
shows ‹$(\exists x.\ P(x)) \longleftrightarrow (\exists x.\ Q(x))$›
⟨*proof*⟩

lemma *ex1-cong*:
assumes ‹$\bigwedge x.\ P(x) \longleftrightarrow Q(x)$›
shows ‹$(\exists!x.\ P(x)) \longleftrightarrow (\exists!x.\ Q(x))$›
⟨*proof*⟩

1.5 Equality rules

lemma *sym*: ‹$a = b \Longrightarrow b = a$›
⟨*proof*⟩

lemma *trans*: ‹$[\![a = b; b = c]\!] \Longrightarrow a = c$›
⟨*proof*⟩

lemma *not-sym*: ‹$b \neq a \Longrightarrow a \neq b$›
⟨*proof*⟩

Two theorems for rewriting only one instance of a definition: the first for definitions of formulae and the second for terms.

lemma *def-imp-iff*: ‹$(A \equiv B) \Longrightarrow A \longleftrightarrow B$›
⟨*proof*⟩

lemma *meta-eq-to-obj-eq*: ‹$(A \equiv B) \Longrightarrow A = B$›
⟨*proof*⟩

lemma *meta-eq-to-iff*: ‹$x \equiv y \Longrightarrow x \longleftrightarrow y$›
⟨*proof*⟩

Substitution.

lemma *ssubst*: ‹$[\![b = a; P(a)]\!] \Longrightarrow P(b)$›
⟨*proof*⟩

A special case of *ex1E* that would otherwise need quantifier expansion.

lemma *ex1-equalsE*: ‹$[\![\exists!x.\ P(x); P(a); P(b)]\!] \Longrightarrow a = b$›
⟨*proof*⟩

1.6 Simplifications of assumed implications

Roy Dyckhoff has proved that *conj-impE*, *disj-impE*, and *imp-impE* used with `mp_tac` (restricted to atomic formulae) is COMPLETE for intuitionistic propositional logic.

See R. Dyckhoff, Contraction-free sequent calculi for intuitionistic logic (preprint, University of St Andrews, 1991).

lemma *conj-impE*:
assumes *major*: ‹$(P \wedge Q) \longrightarrow S$›
and *r*: ‹$P \longrightarrow (Q \longrightarrow S) \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

lemma *disj-impE*:
assumes *major*: ‹$(P \vee Q) \longrightarrow S$›
and *r*: ‹$[\![P \longrightarrow S; Q \longrightarrow S]\!] \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

Simplifies the implication. Classical version is stronger. Still UNSAFE since Q must be provable – backtracking needed.

lemma *imp-impE*:
assumes *major*: ‹$(P \longrightarrow Q) \longrightarrow S$›
and *r1*: ‹$[\![P;\ Q \longrightarrow S]\!] \Longrightarrow Q$›
and *r2*: ‹$S \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

Simplifies the implication. Classical version is stronger. Still UNSAFE since P must be provable – backtracking needed.

lemma *not-impE*: ‹$\neg\ P \longrightarrow S \Longrightarrow (P \Longrightarrow \mathit{False}) \Longrightarrow (S \Longrightarrow R) \Longrightarrow R$›
⟨*proof*⟩

Simplifies the implication. UNSAFE.

lemma *iff-impE*:
assumes *major*: ‹$(P \longleftrightarrow Q) \longrightarrow S$›
and *r1*: ‹$[\![P;\ Q \longrightarrow S]\!] \Longrightarrow Q$›
and *r2*: ‹$[\![Q;\ P \longrightarrow S]\!] \Longrightarrow P$›
and *r3*: ‹$S \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

What if $(\forall x.\ \neg\ \neg\ P(x)) \longrightarrow \neg\ \neg\ (\forall x.\ P(x))$ is an assumption? UNSAFE.

lemma *all-impE*:
assumes *major*: ‹$(\forall x.\ P(x)) \longrightarrow S$›
and *r1*: ‹$\bigwedge x.\ P(x)$›
and *r2*: ‹$S \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

Unsafe: $\exists x.\ P(x)) \longrightarrow S$ is equivalent to $\forall x.\ P(x) \longrightarrow S$.

lemma *ex-impE*:
assumes *major*: ‹$(\exists x.\ P(x)) \longrightarrow S$›
and *r*: ‹$P(x) \longrightarrow S \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

Courtesy of Krzysztof Grabczewski.

lemma *disj-imp-disj*: ‹$P \vee Q \Longrightarrow (P \Longrightarrow R) \Longrightarrow (Q \Longrightarrow S) \Longrightarrow R \vee S$›
⟨*proof*⟩

⟨*ML*⟩

lemma *thin-refl*: ‹$[\![x = x;\ \mathit{PROP}\ W]\!] \Longrightarrow \mathit{PROP}\ W$› ⟨*proof*⟩

⟨*ML*⟩

1.7 Intuitionistic Reasoning

⟨*ML*⟩

lemma *impE′*:
  assumes *1*: ‹$P \longrightarrow Q$›
    and *2*: ‹$Q \Longrightarrow R$›
    and *3*: ‹$P \longrightarrow Q \Longrightarrow P$›
  shows ‹R›
⟨*proof*⟩

lemma *allE′*:
  assumes *1*: ‹$\forall x.\ P(x)$›
    and *2*: ‹$P(x) \Longrightarrow \forall x.\ P(x) \Longrightarrow Q$›
  shows ‹Q›
⟨*proof*⟩

lemma *notE′*:
  assumes *1*: ‹$\neg\ P$›
    and *2*: ‹$\neg\ P \Longrightarrow P$›
  shows ‹R›
⟨*proof*⟩

lemmas [*Pure.elim*!] = *disjE iffE FalseE conjE exE*
  and [*Pure.intro*!] = *iffI conjI impI TrueI notI allI refl*
  and [*Pure.elim 2*] = *allE notE′ impE′*
  and [*Pure.intro*] = *exI disjI2 disjI1*

⟨*ML*⟩

lemma *iff-not-sym*: ‹$\neg\ (Q \longleftrightarrow P) \Longrightarrow \neg\ (P \longleftrightarrow Q)$›
  ⟨*proof*⟩

lemmas [*sym*] = *sym iff-sym not-sym iff-not-sym*
  and [*Pure.elim?*] = *iffD1 iffD2 impE*

lemma *eq-commute*: ‹$a = b \longleftrightarrow b = a$›
  ⟨*proof*⟩

1.8 Polymorphic congruence rules

lemma *subst-context*: ‹$a = b \Longrightarrow t(a) = t(b)$›
  ⟨*proof*⟩

lemma *subst-context2*: ‹$⟦a = b;\ c = d⟧ \Longrightarrow t(a,c) = t(b,d)$›
  ⟨*proof*⟩

lemma *subst-context3*: ‹$⟦a = b;\ c = d;\ e = f⟧ \Longrightarrow t(a,c,e) = t(b,d,f)$›

⟨*proof*⟩

Useful with `eresolve_tac` for proving equalities from known equalities.

a = b | | c = d

lemma *box-equals*: ‹⟦*a* = *b*; *a* = *c*; *b* = *d*⟧ ⟹ *c* = *d*›
⟨*proof*⟩

Dual of *box-equals*: for proving equalities backwards.

lemma *simp-equals*: ‹⟦*a* = *c*; *b* = *d*; *c* = *d*⟧ ⟹ *a* = *b*›
⟨*proof*⟩

1.8.1 Congruence rules for predicate letters

lemma *pred1-cong*: ‹*a* = *a'* ⟹ *P*(*a*) ⟷ *P*(*a'*)›
⟨*proof*⟩

lemma *pred2-cong*: ‹⟦*a* = *a'*; *b* = *b'*⟧ ⟹ *P*(*a*,*b*) ⟷ *P*(*a'*,*b'*)›
⟨*proof*⟩

lemma *pred3-cong*: ‹⟦*a* = *a'*; *b* = *b'*; *c* = *c'*⟧ ⟹ *P*(*a*,*b*,*c*) ⟷ *P*(*a'*,*b'*,*c'*)›
⟨*proof*⟩

Special case for the equality predicate!

lemma *eq-cong*: ‹⟦*a* = *a'*; *b* = *b'*⟧ ⟹ *a* = *b* ⟷ *a'* = *b'*›
⟨*proof*⟩

1.9 Atomizing meta-level rules

lemma *atomize-all* [*atomize*]: ‹(⋀*x*. *P*(*x*)) ≡ *Trueprop* (∀ *x*. *P*(*x*))›
⟨*proof*⟩

lemma *atomize-imp* [*atomize*]: ‹(*A* ⟹ *B*) ≡ *Trueprop* (*A* ⟶ *B*)›
⟨*proof*⟩

lemma *atomize-eq* [*atomize*]: ‹(*x* ≡ *y*) ≡ *Trueprop* (*x* = *y*)›
⟨*proof*⟩

lemma *atomize-iff* [*atomize*]: ‹(*A* ≡ *B*) ≡ *Trueprop* (*A* ⟷ *B*)›
⟨*proof*⟩

lemma *atomize-conj* [*atomize*]: ‹(*A* &&& *B*) ≡ *Trueprop* (*A* ∧ *B*)›
⟨*proof*⟩

lemmas [*symmetric*, *rulify*] = *atomize-all atomize-imp*
and [*symmetric*, *defn*] = *atomize-all atomize-imp atomize-eq atomize-iff*

1.10 Atomizing elimination rules

lemma *atomize-exL*[*atomize-elim*]: ‹(⋀*x*. *P*(*x*) ⟹ *Q*) ≡ ((∃ *x*. *P*(*x*)) ⟹ *Q*)›

⟨*proof*⟩

lemma *atomize-conjL*[*atomize-elim*]: ‹(*A* ⟹ *B* ⟹ *C*) ≡ (*A* ∧ *B* ⟹ *C*)›
⟨*proof*⟩

lemma *atomize-disjL*[*atomize-elim*]: ‹((*A* ⟹ *C*) ⟹ (*B* ⟹ *C*) ⟹ *C*) ≡ ((*A* ∨ *B* ⟹ *C*) ⟹ *C*)›
⟨*proof*⟩

lemma *atomize-elimL*[*atomize-elim*]: ‹(⋀*B*. (*A* ⟹ *B*) ⟹ *B*) ≡ *Trueprop*(*A*)›
⟨*proof*⟩

1.11 Calculational rules

lemma *forw-subst*: ‹*a* = *b* ⟹ *P*(*b*) ⟹ *P*(*a*)›
⟨*proof*⟩

lemma *back-subst*: ‹*P*(*a*) ⟹ *a* = *b* ⟹ *P*(*b*)›
⟨*proof*⟩

Note that this list of rules is in reverse order of priorities.

lemmas *basic-trans-rules* [*trans*] =
forw-subst
back-subst
rev-mp
mp
trans

1.12 "Let" declarations

nonterminal *letbinds* **and** *letbind*

definition *Let* :: ‹['*a*::{}, '*a* => '*b*] ⇒ ('*b*::{})›
where ‹*Let*(*s*, *f*) ≡ *f*(*s*)›

syntax
-bind :: ‹[*pttrn*, '*a*] => *letbind*› (‹(‹*indent=2 notation=‹infix let binding›*›-=/ -)› *10*)
:: ‹*letbind* => *letbinds*› (‹-›)
-binds :: ‹[*letbind*, *letbinds*] => *letbinds*› (‹-;/ -›)
-Let :: ‹[*letbinds*, '*a*] => '*a*› (‹(‹*notation=‹mixfix let expression›*›*let* (-)/ *in* (-))› *10*)
syntax-consts
-Let ⇌ *Let*
translations
-Let(*-binds*(*b*, *bs*), *e*) == *-Let*(*b*, *-Let*(*bs*, *e*))
let x = a in e == *CONST Let*(*a*, λ*x*. *e*)

lemma *LetI*:

assumes ‹$\bigwedge x.\ x = t \Longrightarrow P(u(x))$›
shows ‹$P(\mathit{let}\ x = t\ \mathit{in}\ u(x))$›
⟨*proof*⟩

1.13 Intuitionistic simplification rules

lemma *conj-simps*:
‹$P \wedge \mathit{True} \longleftrightarrow P$›
‹$\mathit{True} \wedge P \longleftrightarrow P$›
‹$P \wedge \mathit{False} \longleftrightarrow \mathit{False}$›
‹$\mathit{False} \wedge P \longleftrightarrow \mathit{False}$›
‹$P \wedge P \longleftrightarrow P$›
‹$P \wedge P \wedge Q \longleftrightarrow P \wedge Q$›
‹$P \wedge \neg P \longleftrightarrow \mathit{False}$›
‹$\neg P \wedge P \longleftrightarrow \mathit{False}$›
‹$(P \wedge Q) \wedge R \longleftrightarrow P \wedge (Q \wedge R)$›
⟨*proof*⟩

lemma *disj-simps*:
‹$P \vee \mathit{True} \longleftrightarrow \mathit{True}$›
‹$\mathit{True} \vee P \longleftrightarrow \mathit{True}$›
‹$P \vee \mathit{False} \longleftrightarrow P$›
‹$\mathit{False} \vee P \longleftrightarrow P$›
‹$P \vee P \longleftrightarrow P$›
‹$P \vee P \vee Q \longleftrightarrow P \vee Q$›
‹$(P \vee Q) \vee R \longleftrightarrow P \vee (Q \vee R)$›
⟨*proof*⟩

lemma *not-simps*:
‹$\neg (P \vee Q) \longleftrightarrow \neg P \wedge \neg Q$›
‹$\neg \mathit{False} \longleftrightarrow \mathit{True}$›
‹$\neg \mathit{True} \longleftrightarrow \mathit{False}$›
⟨*proof*⟩

lemma *imp-simps*:
‹$(P \longrightarrow \mathit{False}) \longleftrightarrow \neg P$›
‹$(P \longrightarrow \mathit{True}) \longleftrightarrow \mathit{True}$›
‹$(\mathit{False} \longrightarrow P) \longleftrightarrow \mathit{True}$›
‹$(\mathit{True} \longrightarrow P) \longleftrightarrow P$›
‹$(P \longrightarrow P) \longleftrightarrow \mathit{True}$›
‹$(P \longrightarrow \neg P) \longleftrightarrow \neg P$›
⟨*proof*⟩

lemma *iff-simps*:
‹$(\mathit{True} \longleftrightarrow P) \longleftrightarrow P$›
‹$(P \longleftrightarrow \mathit{True}) \longleftrightarrow P$›
‹$(P \longleftrightarrow P) \longleftrightarrow \mathit{True}$›
‹$(\mathit{False} \longleftrightarrow P) \longleftrightarrow \neg P$›
‹$(P \longleftrightarrow \mathit{False}) \longleftrightarrow \neg P$›

⟨*proof*⟩

The $x = t$ versions are needed for the simplification procedures.

lemma *quant-simps*:
‹$\bigwedge P.\ (\forall x.\ P) \longleftrightarrow P$›
‹$(\forall x.\ x = t \longrightarrow P(x)) \longleftrightarrow P(t)$›
‹$(\forall x.\ t = x \longrightarrow P(x)) \longleftrightarrow P(t)$›
‹$\bigwedge P.\ (\exists x.\ P) \longleftrightarrow P$›
‹$\exists x.\ x = t$›
‹$\exists x.\ t = x$›
‹$(\exists x.\ x = t \wedge P(x)) \longleftrightarrow P(t)$›
‹$(\exists x.\ t = x \wedge P(x)) \longleftrightarrow P(t)$›
⟨*proof*⟩

These are NOT supplied by default!

lemma *distrib-simps*:
‹$P \wedge (Q \vee R) \longleftrightarrow P \wedge Q \vee P \wedge R$›
‹$(Q \vee R) \wedge P \longleftrightarrow Q \wedge P \vee R \wedge P$›
‹$(P \vee Q \longrightarrow R) \longleftrightarrow (P \longrightarrow R) \wedge (Q \longrightarrow R)$›
⟨*proof*⟩

lemma *subst-all*:
‹$(\bigwedge x.\ x = a \Longrightarrow PROP\ P(x)) \equiv PROP\ P(a)$›
‹$(\bigwedge x.\ a = x \Longrightarrow PROP\ P(x)) \equiv PROP\ P(a)$›
⟨*proof*⟩

1.13.1 Conversion into rewrite rules

lemma *P-iff-F*: ‹$\neg P \Longrightarrow (P \longleftrightarrow False)$›
⟨*proof*⟩
lemma *iff-reflection-F*: ‹$\neg P \Longrightarrow (P \equiv False)$›
⟨*proof*⟩

lemma *P-iff-T*: ‹$P \Longrightarrow (P \longleftrightarrow True)$›
⟨*proof*⟩
lemma *iff-reflection-T*: ‹$P \Longrightarrow (P \equiv True)$›
⟨*proof*⟩

1.13.2 More rewrite rules

lemma *conj-commute*: ‹$P \wedge Q \longleftrightarrow Q \wedge P$› ⟨*proof*⟩
lemma *conj-left-commute*: ‹$P \wedge (Q \wedge R) \longleftrightarrow Q \wedge (P \wedge R)$› ⟨*proof*⟩
lemmas *conj-comms = conj-commute conj-left-commute*

lemma *disj-commute*: ‹$P \vee Q \longleftrightarrow Q \vee P$› ⟨*proof*⟩
lemma *disj-left-commute*: ‹$P \vee (Q \vee R) \longleftrightarrow Q \vee (P \vee R)$› ⟨*proof*⟩
lemmas *disj-comms = disj-commute disj-left-commute*

lemma *conj-disj-distribL*: ‹$P \wedge (Q \vee R) \longleftrightarrow (P \wedge Q \vee P \wedge R)$› ⟨*proof*⟩

lemma *conj-disj-distribR*: ‹$(P \vee Q) \wedge R \longleftrightarrow (P \wedge R \vee Q \wedge R)$› ⟨*proof*⟩

lemma *disj-conj-distribL*: ‹$P \vee (Q \wedge R) \longleftrightarrow (P \vee Q) \wedge (P \vee R)$› ⟨*proof*⟩
lemma *disj-conj-distribR*: ‹$(P \wedge Q) \vee R \longleftrightarrow (P \vee R) \wedge (Q \vee R)$› ⟨*proof*⟩

lemma *imp-conj-distrib*: ‹$(P \longrightarrow (Q \wedge R)) \longleftrightarrow (P \longrightarrow Q) \wedge (P \longrightarrow R)$› ⟨*proof*⟩
lemma *imp-conj*: ‹$((P \wedge Q) \longrightarrow R) \longleftrightarrow (P \longrightarrow (Q \longrightarrow R))$› ⟨*proof*⟩
lemma *imp-disj*: ‹$(P \vee Q \longrightarrow R) \longleftrightarrow (P \longrightarrow R) \wedge (Q \longrightarrow R)$› ⟨*proof*⟩

lemma *de-Morgan-disj*: ‹$(\neg (P \vee Q)) \longleftrightarrow (\neg P \wedge \neg Q)$› ⟨*proof*⟩

lemma *not-ex*: ‹$(\neg (\exists x.\ P(x))) \longleftrightarrow (\forall x.\ \neg P(x))$› ⟨*proof*⟩
lemma *imp-ex*: ‹$((\exists x.\ P(x)) \longrightarrow Q) \longleftrightarrow (\forall x.\ P(x) \longrightarrow Q)$› ⟨*proof*⟩

lemma *ex-disj-distrib*: ‹$(\exists x.\ P(x) \vee Q(x)) \longleftrightarrow ((\exists x.\ P(x)) \vee (\exists x.\ Q(x)))$›
⟨*proof*⟩

lemma *all-conj-distrib*: ‹$(\forall x.\ P(x) \wedge Q(x)) \longleftrightarrow ((\forall x.\ P(x)) \wedge (\forall x.\ Q(x)))$›
⟨*proof*⟩

end

2 Classical first-order logic

theory *FOL*
imports *IFOL*
keywords *print-claset print-induct-rules* :: *diag*
begin

⟨*ML*⟩

2.1 The classical axiom

axiomatization where
classical: ‹$(\neg P \Longrightarrow P) \Longrightarrow P$›

2.2 Lemmas and proof tools

lemma *ccontr*: ‹$(\neg P \Longrightarrow \mathit{False}) \Longrightarrow P$›
⟨*proof*⟩

2.2.1 Classical introduction rules for $\vee$ and $\exists$

lemma *disjCI*: ‹$(\neg Q \Longrightarrow P) \Longrightarrow P \vee Q$›
⟨*proof*⟩

Introduction rule involving only $\exists$

lemma *ex-classical*:
assumes *r*: ‹$\neg (\exists x.\ P(x)) \Longrightarrow P(a)$›

shows ‹$\exists\, x.\ P(x)$›
⟨*proof*⟩

Version of above, simplifying $\neg\exists$ to $\forall\neg$.

lemma *exCI*:
assumes *r*: ‹$\forall\, x.\ \neg\ P(x) \Longrightarrow P(a)$›
shows ‹$\exists\, x.\ P(x)$›
⟨*proof*⟩

lemma *excluded-middle*: ‹$\neg\ P \vee P$›
⟨*proof*⟩

lemma *case-split* [*case-names True False*]:
assumes *r1*: ‹$P \Longrightarrow Q$›
and *r2*: ‹$\neg\ P \Longrightarrow Q$›
shows ‹Q›
⟨*proof*⟩

⟨*ML*⟩

2.3 Special elimination rules

Classical implies ($\longrightarrow$) elimination.

lemma *impCE*:
assumes *major*: ‹$P \longrightarrow Q$›
and *r1*: ‹$\neg\ P \Longrightarrow R$›
and *r2*: ‹$Q \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

This version of $\longrightarrow$ elimination works on Q before P. It works best for those cases in which P holds "almost everywhere". Can't install as default: would break old proofs.

lemma *impCE'*:
assumes *major*: ‹$P \longrightarrow Q$›
and *r1*: ‹$Q \Longrightarrow R$›
and *r2*: ‹$\neg\ P \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

Double negation law.

lemma *notnotD*: ‹$\neg\ \neg\ P \Longrightarrow P$›
⟨*proof*⟩

lemma *contrapos2*: ‹$[\![Q;\ \neg\ P \Longrightarrow \neg\ Q]\!] \Longrightarrow P$›
⟨*proof*⟩

2.3.1 Tactics for implication and contradiction

Classical $\longleftrightarrow$ elimination. Proof substitutes $P = Q$ in $\neg\ P \Longrightarrow \neg\ Q$ and $P \Longrightarrow Q$.

lemma *iffCE*:
assumes *major*: ‹$P \longleftrightarrow Q$›
and *r1*: ‹$[\![P;\ Q]\!] \Longrightarrow R$›
and *r2*: ‹$[\![\neg\ P;\ \neg\ Q]\!] \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

lemma *alt-ex1E*:
assumes *major*: ‹$\exists!\ x.\ P(x)$›
and *r*: ‹$\bigwedge x.\ [\![P(x);\ \forall\ y\ y'.\ P(y) \wedge P(y') \longrightarrow y = y']\!] \Longrightarrow R$›
shows ‹R›
⟨*proof*⟩

lemma *imp-elim*: ‹$P \longrightarrow Q \Longrightarrow (\neg\ R \Longrightarrow P) \Longrightarrow (Q \Longrightarrow R) \Longrightarrow R$›
⟨*proof*⟩

lemma *swap*: ‹$\neg\ P \Longrightarrow (\neg\ R \Longrightarrow P) \Longrightarrow R$›
⟨*proof*⟩

3 Classical Reasoner

⟨*ML*⟩

lemmas [*intro*!] = *refl TrueI conjI disjCI impI notI iffI*
and [*elim*!] = *conjE disjE impCE FalseE iffCE*
⟨*ML*⟩

lemmas [*intro*!] = *allI ex-ex1I*
and [*intro*] = *exI*
and [*elim*!] = *exE alt-ex1E*
and [*elim*] = *allE*
⟨*ML*⟩

lemma *ex1-functional*: ‹$[\![\exists!\ z.\ P(a,z);\ P(a,b);\ P(a,c)]\!] \Longrightarrow b = c$›
⟨*proof*⟩

Elimination of *True* from assumptions:

lemma *True-implies-equals*: ‹$(True \Longrightarrow PROP\ P) \equiv PROP\ P$›
⟨*proof*⟩

lemma *uncurry*: ‹$P \longrightarrow Q \longrightarrow R \Longrightarrow P \wedge Q \longrightarrow R$›
⟨*proof*⟩

lemma *iff-allI*: ‹$(\bigwedge x.\ P(x) \longleftrightarrow Q(x)) \Longrightarrow (\forall x.\ P(x)) \longleftrightarrow (\forall x.\ Q(x))$›
⟨*proof*⟩

lemma *iff-exI*: ‹$(\bigwedge x.\ P(x) \longleftrightarrow Q(x)) \Longrightarrow (\exists x.\ P(x)) \longleftrightarrow (\exists x.\ Q(x))$›
⟨*proof*⟩

lemma *all-comm*: ‹$(\forall x\ y.\ P(x,y)) \longleftrightarrow (\forall y\ x.\ P(x,y))$›
⟨*proof*⟩

lemma *ex-comm*: ‹$(\exists x\ y.\ P(x,y)) \longleftrightarrow (\exists y\ x.\ P(x,y))$›
⟨*proof*⟩

3.1 Classical simplification rules

Avoids duplication of subgoals after *expand-if*, when the true and false cases boil down to the same thing.

lemma *cases-simp*: ‹$(P \longrightarrow Q) \wedge (\neg P \longrightarrow Q) \longleftrightarrow Q$›
⟨*proof*⟩

3.1.1 Miniscoping: pushing quantifiers in

We do NOT distribute of $\forall$ over $\wedge$, or dually that of $\exists$ over $\vee$.
Baaz and Leitsch, On Skolemization and Proof Complexity (1994) show that this step can increase proof length!

Existential miniscoping.

lemma *int-ex-simps*:
‹$\bigwedge P\ Q.\ (\exists x.\ P(x) \wedge Q) \longleftrightarrow (\exists x.\ P(x)) \wedge Q$›
‹$\bigwedge P\ Q.\ (\exists x.\ P \wedge Q(x)) \longleftrightarrow P \wedge (\exists x.\ Q(x))$›
‹$\bigwedge P\ Q.\ (\exists x.\ P(x) \vee Q) \longleftrightarrow (\exists x.\ P(x)) \vee Q$›
‹$\bigwedge P\ Q.\ (\exists x.\ P \vee Q(x)) \longleftrightarrow P \vee (\exists x.\ Q(x))$›
⟨*proof*⟩

Classical rules.

lemma *cla-ex-simps*:
‹$\bigwedge P\ Q.\ (\exists x.\ P(x) \longrightarrow Q) \longleftrightarrow (\forall x.\ P(x)) \longrightarrow Q$›
‹$\bigwedge P\ Q.\ (\exists x.\ P \longrightarrow Q(x)) \longleftrightarrow P \longrightarrow (\exists x.\ Q(x))$›
⟨*proof*⟩

lemmas *ex-simps* = *int-ex-simps cla-ex-simps*

Universal miniscoping.

lemma *int-all-simps*:

‹$\bigwedge P\ Q.\ (\forall x.\ P(x) \wedge Q) \longleftrightarrow (\forall x.\ P(x)) \wedge Q$›
‹$\bigwedge P\ Q.\ (\forall x.\ P \wedge Q(x)) \longleftrightarrow P \wedge (\forall x.\ Q(x))$›
‹$\bigwedge P\ Q.\ (\forall x.\ P(x) \longrightarrow Q) \longleftrightarrow (\exists\ x.\ P(x)) \longrightarrow Q$›
‹$\bigwedge P\ Q.\ (\forall x.\ P \longrightarrow Q(x)) \longleftrightarrow P \longrightarrow (\forall x.\ Q(x))$›
⟨*proof*⟩

Classical rules.

lemma *cla-all-simps*:
‹$\bigwedge P\ Q.\ (\forall x.\ P(x) \vee Q) \longleftrightarrow (\forall x.\ P(x)) \vee Q$›
‹$\bigwedge P\ Q.\ (\forall x.\ P \vee Q(x)) \longleftrightarrow P \vee (\forall x.\ Q(x))$›
⟨*proof*⟩

lemmas *all-simps* = *int-all-simps cla-all-simps*

3.1.2 Named rewrite rules proved for IFOL

lemma *imp-disj1*: ‹$(P \longrightarrow Q) \vee R \longleftrightarrow (P \longrightarrow Q \vee R)$› ⟨*proof*⟩
lemma *imp-disj2*: ‹$Q \vee (P \longrightarrow R) \longleftrightarrow (P \longrightarrow Q \vee R)$› ⟨*proof*⟩

lemma *de-Morgan-conj*: ‹$(\neg\ (P \wedge Q)) \longleftrightarrow (\neg\ P \vee \neg\ Q)$› ⟨*proof*⟩

lemma *not-imp*: ‹$\neg\ (P \longrightarrow Q) \longleftrightarrow (P \wedge \neg\ Q)$› ⟨*proof*⟩
lemma *not-iff*: ‹$\neg\ (P \longleftrightarrow Q) \longleftrightarrow (P \longleftrightarrow \neg\ Q)$› ⟨*proof*⟩

lemma *not-all*: ‹$(\neg\ (\forall x.\ P(x))) \longleftrightarrow (\exists x.\ \neg\ P(x))$› ⟨*proof*⟩
lemma *imp-all*: ‹$((\forall x.\ P(x)) \longrightarrow Q) \longleftrightarrow (\exists x.\ P(x) \longrightarrow Q)$› ⟨*proof*⟩

lemmas *meta-simps* =
triv-forall-equality — prunes params
True-implies-equals — prune asms *True*

lemmas *IFOL-simps* =
refl [*THEN P-iff-T*] *conj-simps disj-simps not-simps*
imp-simps iff-simps quant-simps

lemma *notFalseI*: ‹$\neg$ *False*› ⟨*proof*⟩

lemma *cla-simps-misc*:
‹$\neg\ (P \wedge Q) \longleftrightarrow \neg\ P \vee \neg\ Q$›
‹$P \vee \neg\ P$›
‹$\neg\ P \vee P$›
‹$\neg\ \neg\ P \longleftrightarrow P$›
‹$(\neg\ P \longrightarrow P) \longleftrightarrow P$›
‹$(\neg\ P \longleftrightarrow \neg\ Q) \longleftrightarrow (P \longleftrightarrow Q)$› ⟨*proof*⟩

lemmas *cla-simps* =
de-Morgan-conj de-Morgan-disj imp-disj1 imp-disj2
not-imp not-all not-ex cases-simp cla-simps-misc

⟨*ML*⟩

3.2 Other simple lemmas

lemma [*simp*]: ‹((*P* ⟶ *R*) ⟷ (*Q* ⟶ *R*)) ⟷ ((*P* ⟷ *Q*) ∨ *R*)›
⟨*proof*⟩

lemma [*simp*]: ‹((*P* ⟶ *Q*) ⟷ (*P* ⟶ *R*)) ⟷ (*P* ⟶ (*Q* ⟷ *R*))›
⟨*proof*⟩

lemma *not-disj-iff-imp*: ‹¬ *P* ∨ *Q* ⟷ (*P* ⟶ *Q*)›
⟨*proof*⟩

3.2.1 Monotonicity of implications

lemma *conj-mono*: ‹⟦*P1* ⟶ *Q1*; *P2* ⟶ *Q2*⟧ ⟹ (*P1* ∧ *P2*) ⟶ (*Q1* ∧ *Q2*)›
⟨*proof*⟩

lemma *disj-mono*: ‹⟦*P1* ⟶ *Q1*; *P2* ⟶ *Q2*⟧ ⟹ (*P1* ∨ *P2*) ⟶ (*Q1* ∨ *Q2*)›
⟨*proof*⟩

lemma *imp-mono*: ‹⟦*Q1* ⟶ *P1*; *P2* ⟶ *Q2*⟧ ⟹ (*P1* ⟶ *P2*) ⟶ (*Q1* ⟶ *Q2*)›
⟨*proof*⟩

lemma *imp-refl*: ‹*P* ⟶ *P*›
⟨*proof*⟩

The quantifier monotonicity rules are also intuitionistically valid.

lemma *ex-mono*: ‹(⋀*x*. *P*(*x*) ⟶ *Q*(*x*)) ⟹ (∃ *x*. *P*(*x*)) ⟶ (∃ *x*. *Q*(*x*))›
⟨*proof*⟩

lemma *all-mono*: ‹(⋀*x*. *P*(*x*) ⟶ *Q*(*x*)) ⟹ (∀ *x*. *P*(*x*)) ⟶ (∀ *x*. *Q*(*x*))›
⟨*proof*⟩

3.3 Proof by cases and induction

Proper handling of non-atomic rule statements.

context
begin

qualified definition ‹*induct-forall*(*P*) ≡ ∀ *x*. *P*(*x*)›
qualified definition ‹*induct-implies*(*A*, *B*) ≡ *A* ⟶ *B*›
qualified definition ‹*induct-equal*(*x*, *y*) ≡ *x* = *y*›
qualified definition ‹*induct-conj*(*A*, *B*) ≡ *A* ∧ *B*›

lemma *induct-forall-eq*: ‹(⋀*x*. *P*(*x*)) ≡ *Trueprop*(*induct-forall*(λ*x*. *P*(*x*)))›

⟨*proof*⟩

lemma *induct-implies-eq*: ‹(*A* ⟹ *B*) ≡ *Trueprop*(*induct-implies*(*A*, *B*))›
⟨*proof*⟩

lemma *induct-equal-eq*: ‹(*x* ≡ *y*) ≡ *Trueprop*(*induct-equal*(*x*, *y*))›
⟨*proof*⟩

lemma *induct-conj-eq*: ‹(*A* &&& *B*) ≡ *Trueprop*(*induct-conj*(*A*, *B*))›
⟨*proof*⟩

lemmas *induct-atomize* = *induct-forall-eq induct-implies-eq induct-equal-eq induct-conj-eq*
lemmas *induct-rulify* [*symmetric*] = *induct-atomize*
lemmas *induct-rulify-fallback* =
induct-forall-def induct-implies-def induct-equal-def induct-conj-def

Method setup.

⟨*ML*⟩

declare *case-split* [*cases type*: *o*]

end

⟨*ML*⟩

hide-const (**open**) *eq*

end