Matrix

Steven Obua

October 24, 2026

theory *Matrix*
imports *Main HOL−Library.Lattice-Algebras*
begin

type-synonym *'a infmatrix = nat ⇒ nat ⇒ 'a*

definition *nonzero-positions* :: *(nat ⇒ nat ⇒ 'a::zero) ⇒ (nat × nat) set* **where**
nonzero-positions A = {pos. A (fst pos) (snd pos) ~= 0}

definition *matrix = {(f::(nat ⇒ nat ⇒ 'a::zero)). finite (nonzero-positions f)}*

typedef (**overloaded**) *'a matrix = matrix :: (nat ⇒ nat ⇒ 'a::zero) set*
unfolding *matrix-def*
proof
show *(λj i. 0) ∈ {(f::(nat ⇒ nat ⇒ 'a::zero)). finite (nonzero-positions f)}*
by *(simp add: nonzero-positions-def)*
qed

declare *Rep-matrix-inverse*[*simp*]

lemma *matrix-eqI*:
fixes *A B :: 'a::zero matrix*
assumes *⋀m n. Rep-matrix A m n = Rep-matrix B m n*
shows *A=B*
using *Rep-matrix-inject assms* **by** *blast*

lemma *finite-nonzero-positions* : *finite (nonzero-positions (Rep-matrix A))*
by *(induct A) (simp add: Abs-matrix-inverse matrix-def)*

definition *nrows* :: *('a::zero) matrix ⇒ nat* **where**
nrows A == if nonzero-positions(Rep-matrix A) = {} then 0 else Suc(Max ((image fst) (nonzero-positions (Rep-matrix A))))

definition *ncols* :: *('a::zero) matrix ⇒ nat* **where**
ncols A == if nonzero-positions(Rep-matrix A) = {} then 0 else Suc(Max ((image snd) (nonzero-positions (Rep-matrix A))))

lemma *nrows*:
assumes *hyp*: *nrows A* ≤ *m*
shows (*Rep-matrix A m n*) = *0*
proof *cases*
assume *nonzero-positions*(*Rep-matrix A*) = {}
then show (*Rep-matrix A m n*) = *0* **by** (*simp add*: *nonzero-positions-def*)
next
assume *a*: *nonzero-positions*(*Rep-matrix A*) ≠ {}
let *?S* = *fst*‘(*nonzero-positions*(*Rep-matrix A*))
have *c*: *finite* (*?S*) **by** (*simp add*: *finite-nonzero-positions*)
from *hyp* **have** *d*: *Max* (*?S*) < *m* **by** (*simp add*: *a nrows-def*)
have *m* ∉ *?S*
proof −
have *m* ∈ *?S* ⟹ *m* ≤ *Max*(*?S*) **by** (*simp add*: *Max-ge* [*OF c*])
moreover from *d* **have** ~(*m* ≤ *Max ?S*) **by** (*simp*)
ultimately show *m* ∉ *?S* **by** (*auto*)
qed
thus *Rep-matrix A m n* = *0* **by** (*simp add*: *nonzero-positions-def image-Collect*)
qed

definition *transpose-infmatrix* :: *'a infmatrix* ⇒ *'a infmatrix* **where**
transpose-infmatrix A j i == *A i j*

definition *transpose-matrix* :: (*'a*::*zero*) *matrix* ⇒ *'a matrix* **where**
transpose-matrix == *Abs-matrix o transpose-infmatrix o Rep-matrix*

declare *transpose-infmatrix-def*[*simp*]

lemma *transpose-infmatrix-twice*[*simp*]: *transpose-infmatrix* (*transpose-infmatrix A*) = *A*
by ((*rule ext*)+, *simp*)

lemma *transpose-infmatrix*: *transpose-infmatrix* (λ*j i*. *P j i*) = (λ*j i*. *P i j*)
by *force*

lemma *transpose-infmatrix-closed*[*simp*]: *Rep-matrix* (*Abs-matrix* (*transpose-infmatrix* (*Rep-matrix x*))) = *transpose-infmatrix* (*Rep-matrix x*)
proof −
let *?A* = {*pos*. *Rep-matrix x* (*snd pos*) (*fst pos*) ≠ *0*}
let *?B* = {*pos*. *Rep-matrix x* (*fst pos*) (*snd pos*) ≠ *0*}
let *?swap* = λ*pos*. (*snd pos*, *fst pos*)
have *finite ?A*
proof −
have *swap-image*: *?swap*‘*?A* = *?B*
by (*force simp add*: *image-def*)
then have *finite* (*?swap*‘*?A*)
by (*metis* (*full-types*) *finite-nonzero-positions nonzero-positions-def*)
moreover

have *inj-on ?swap ?A* **by** (*simp add*: *inj-on-def*)
ultimately show *finite ?A*
using *finite-imageD* **by** *blast*
qed
then show *?thesis*
by (*simp add*: *Abs-matrix-inverse matrix-def nonzero-positions-def*)
qed

lemma *infmatrixforward*: $(x::'a\ infmatrix) = y \Longrightarrow \forall\ a\ b.\ x\ a\ b = y\ a\ b$
by *auto*

lemma *transpose-infmatrix-inject*: (*transpose-infmatrix A* = *transpose-infmatrix B*) = (*A* = *B*)
by (*metis transpose-infmatrix-twice*)

lemma *transpose-matrix-inject*: (*transpose-matrix A* = *transpose-matrix B*) = (*A* = *B*)
unfolding *transpose-matrix-def o-def*
by (*metis Rep-matrix-inject transpose-infmatrix-closed transpose-infmatrix-inject*)

lemma *transpose-matrix*[*simp*]: *Rep-matrix*(*transpose-matrix A*) *j i* = *Rep-matrix A i j*
by (*simp add*: *transpose-matrix-def*)

lemma *transpose-transpose-id*[*simp*]: *transpose-matrix* (*transpose-matrix A*) = *A*
by (*simp add*: *transpose-matrix-def*)

lemma *nrows-transpose*[*simp*]: *nrows* (*transpose-matrix A*) = *ncols A*
by (*simp add*: *nrows-def ncols-def nonzero-positions-def transpose-matrix-def image-def*)

lemma *ncols-transpose*[*simp*]: *ncols* (*transpose-matrix A*) = *nrows A*
by (*metis nrows-transpose transpose-transpose-id*)

lemma *ncols*: *ncols A* $\leq$ *n* $\Longrightarrow$ *Rep-matrix A m n* = *0*
by (*metis nrows nrows-transpose transpose-matrix*)

lemma *ncols-le*: (*ncols A* $\leq$ *n*) $\longleftrightarrow$ ($\forall j\ i.\ n \leq i \longrightarrow$ (*Rep-matrix A j i*) = *0*) (**is** *- = ?st*)
proof −
have *Rep-matrix A j i* = *0*
if *ncols A* $\leq$ *n n* $\leq$ *i* **for** *j i*
by (*meson that le-trans ncols*)
moreover have *ncols A* $\leq$ *n*
if $\forall j\ i.\ n \leq i \longrightarrow$ *Rep-matrix A j i* = *0*
unfolding *ncols-def*
proof (*clarsimp split*: *if-split-asm*)
assume §: *nonzero-positions* (*Rep-matrix A*) $\neq$ {}
let *?P* = *nonzero-positions* (*Rep-matrix A*)

let *?p = snd'?P*
have *a:finite ?p* **by** (*simp add*: *finite-nonzero-positions*)
let *?m = Max ?p*
show *Suc* (*Max* (*snd ' nonzero-positions* (*Rep-matrix A*))) ≤ *n*
using § *that obtains-MAX* [*OF finite-nonzero-positions*]
by (*metis* (*mono-tags*, *lifting*) *mem-Collect-eq nonzero-positions-def not-less-eq-eq*)
qed
ultimately show *?thesis*
by *auto*
qed

lemma *less-ncols*: (*n* < *ncols A*) = (∃*j i*. *n* ≤ *i* ∧ (*Rep-matrix A j i*) ≠ *0*)
by (*meson linorder-not-le ncols-le*)

lemma *le-ncols*: (*n* ≤ *ncols A*) = (∀ *m*. (∀ *j i*. *m* ≤ *i* ⟶ (*Rep-matrix A j i*) = *0*) ⟶ *n* ≤ *m*)
by (*meson le-trans ncols ncols-le*)

lemma *nrows-le*: (*nrows A* ≤ *n*) = (∀*j i*. *n* ≤ *j* ⟶ (*Rep-matrix A j i*) = *0*) (**is** *?s*)
by (*metis ncols-le ncols-transpose transpose-matrix*)

lemma *less-nrows*: (*m* < *nrows A*) = (∃*j i*. *m* ≤ *j* ∧ (*Rep-matrix A j i*) ≠ *0*)
by (*meson linorder-not-le nrows-le*)

lemma *le-nrows*: (*n* ≤ *nrows A*) = (∀ *m*. (∀ *j i*. *m* ≤ *j* ⟶ (*Rep-matrix A j i*) = *0*) ⟶ *n* ≤ *m*)
by (*meson order.trans nrows nrows-le*)

lemma *nrows-notzero*: *Rep-matrix A m n* ≠ *0* ⟹ *m* < *nrows A*
by (*meson leI nrows*)

lemma *ncols-notzero*: *Rep-matrix A m n* ≠ *0* ⟹ *n* < *ncols A*
by (*meson leI ncols*)

lemma *finite-natarray1*: *finite* {*x*. *x* < (*n*::*nat*)}
by *simp*

lemma *finite-natarray2*: *finite* {(*x*, *y*). *x* < (*m*::*nat*) ∧ *y* < (*n*::*nat*)}
by *simp*

lemma *RepAbs-matrix*:
assumes ∃ *m*. ∀*j i*. *m* ≤ *j* ⟶ *x j i* = *0*
and ∃ *n*. ∀*j i*. (*n* ≤ *i* ⟶ *x j i* = *0*)
shows (*Rep-matrix* (*Abs-matrix x*)) = *x*
proof −
have *finite* {*pos*. *x* (*fst pos*) (*snd pos*) ≠ *0*}
proof −
from *assms* **obtain** *m n* **where** *a*: ∀*j i*. *m* ≤ *j* ⟶ *x j i* = *0*

```
    and b: ∀ j i. n ≤ i ⟶ x j i = 0 by (blast)
  let ?u = {(i, j). x i j ≠ 0}
  let ?v = {(i, j). i < m ∧ j < n}
  have c: ⋀(m::nat) a. ~(m ≤ a) ⟹ a < m by (arith)
  with a b have d: ?u ⊆ ?v by blast
  moreover have finite ?v by (simp add: finite-natarray2)
  moreover have {pos. x (fst pos) (snd pos) ≠ 0} = ?u by auto
  ultimately show finite {pos. x (fst pos) (snd pos) ≠ 0}
    by (metis (lifting) finite-subset)
qed
then show ?thesis
  by (simp add: Abs-matrix-inverse matrix-def nonzero-positions-def)
qed

definition apply-infmatrix :: ('a ⇒ 'b) ⇒ 'a infmatrix ⇒ 'b infmatrix where
  apply-infmatrix f == λA. (λj i. f (A j i))

definition apply-matrix :: ('a ⇒ 'b) ⇒ ('a::zero) matrix ⇒ ('b::zero) matrix where
  apply-matrix f == λA. Abs-matrix (apply-infmatrix f (Rep-matrix A))

definition combine-infmatrix :: ('a ⇒ 'b ⇒ 'c) ⇒ 'a infmatrix ⇒ 'b infmatrix ⇒
'c infmatrix where
  combine-infmatrix f == λA B. (λj i. f (A j i) (B j i))

definition combine-matrix :: ('a ⇒ 'b ⇒ 'c) ⇒ ('a::zero) matrix ⇒ ('b::zero)
matrix ⇒ ('c::zero) matrix where
  combine-matrix f == λA B. Abs-matrix (combine-infmatrix f (Rep-matrix A)
(Rep-matrix B))

lemma expand-apply-infmatrix[simp]: apply-infmatrix f A j i = f (A j i)
  by (simp add: apply-infmatrix-def)

lemma expand-combine-infmatrix[simp]: combine-infmatrix f A B j i = f (A j i)
(B j i)
  by (simp add: combine-infmatrix-def)

definition commutative :: ('a ⇒ 'a ⇒ 'b) ⇒ bool where
  commutative f == ∀ x y. f x y = f y x

definition associative :: ('a ⇒ 'a ⇒ 'a) ⇒ bool where
  associative f == ∀ x y z. f (f x y) z = f x (f y z)
```

To reason about associativity and commutativity of operations on matrices, let's take a step back and look at the general situtation: Assume that we have sets A and B with $B \subset A$ and an abstraction $u : A \to B$. This abstraction has to fulfill $u(b) = b$ for all $b \in B$, but is arbitrary otherwise. Each function $f : A \times A \to A$ now induces a function $f' : B \times B \to B$ by $f' = u \circ f$. It is obvious that commutativity of f implies commutativity of f': $f'xy = u(fxy) = u(fyx) = f'yx$.

lemma *combine-infmatrix-commute*:
commutative f $\Longrightarrow$ *commutative* (*combine-infmatrix f*)
by (*simp add*: *commutative-def combine-infmatrix-def*)

lemma *combine-matrix-commute*:
commutative f $\Longrightarrow$ *commutative* (*combine-matrix f*)
by (*simp add*: *combine-matrix-def commutative-def combine-infmatrix-def*)

On the contrary, given an associative function f we cannot expect f' to be associative. A counterexample is given by $A = \mathbb{Z}$, $B = \{-1, 0, 1\}$, as f we take addition on $\mathbb{Z}$, which is clearly associative. The abstraction is given by $u(a) = 0$ for $a \notin B$. Then we have

$$f'(f'11) - 1 = u(f(u(f11)) - 1) = u(f(u2) - 1) = u(f0 - 1) = -1,$$

but on the other hand we have

$$f'1(f'1 - 1) = u(f1(u(f1 - 1))) = u(f10) = 1.$$

A way out of this problem is to assume that $f(A \times A) \subset A$ holds, and this is what we are going to do:

lemma *nonzero-positions-combine-infmatrix*[*simp*]: *f 0 0 = 0* $\Longrightarrow$ *nonzero-positions* (*combine-infmatrix f A B*) $\subseteq$ (*nonzero-positions A*) $\cup$ (*nonzero-positions B*)
by (*smt* (*verit*) *UnCI expand-combine-infmatrix mem-Collect-eq nonzero-positions-def subsetI*)

lemma *finite-nonzero-positions-Rep*[*simp*]: *finite* (*nonzero-positions* (*Rep-matrix A*))
by (*simp add*: *finite-nonzero-positions*)

lemma *combine-infmatrix-closed* [*simp*]:
f 0 0 = 0 $\Longrightarrow$ *Rep-matrix* (*Abs-matrix* (*combine-infmatrix f* (*Rep-matrix A*) (*Rep-matrix B*))) = *combine-infmatrix f* (*Rep-matrix A*) (*Rep-matrix B*)
apply (*rule Abs-matrix-inverse*)
apply (*simp add*: *matrix-def*)
by (*meson finite-Un finite-nonzero-positions-Rep finite-subset nonzero-positions-combine-infmatrix*)

We need the next two lemmas only later, but it is analog to the above one, so we prove them now:

lemma *nonzero-positions-apply-infmatrix*[*simp*]: *f 0 = 0* $\Longrightarrow$ *nonzero-positions* (*apply-infmatrix f A*) $\subseteq$ *nonzero-positions A*
by (*rule subsetI*, *simp add*: *nonzero-positions-def apply-infmatrix-def*, *auto*)

lemma *apply-infmatrix-closed* [*simp*]:
f 0 = 0 $\Longrightarrow$ *Rep-matrix* (*Abs-matrix* (*apply-infmatrix f* (*Rep-matrix A*))) = *apply-infmatrix f* (*Rep-matrix A*)
apply (*rule Abs-matrix-inverse*)
apply (*simp add*: *matrix-def*)

by (*meson finite-nonzero-positions-Rep finite-subset nonzero-positions-apply-infmatrix*)

lemma *combine-infmatrix-assoc*[*simp*]: $f\ 0\ 0 = 0 \Longrightarrow$ *associative* $f \Longrightarrow$ *associative* (*combine-infmatrix* f)
by (*simp add*: *associative-def combine-infmatrix-def*)

lemma *combine-matrix-assoc*: $f\ 0\ 0 = 0 \Longrightarrow$ *associative* $f \Longrightarrow$ *associative* (*combine-matrix* f)
by (*smt* (*verit*) *associative-def combine-infmatrix-assoc combine-infmatrix-closed combine-matrix-def*)

lemma *Rep-apply-matrix*[*simp*]: $f\ 0 = 0 \Longrightarrow$ *Rep-matrix* (*apply-matrix* $f\ A$) $j\ i =$ f (*Rep-matrix* $A\ j\ i$)
by (*simp add*: *apply-matrix-def*)

lemma *Rep-combine-matrix*[*simp*]: $f\ 0\ 0 = 0 \Longrightarrow$ *Rep-matrix* (*combine-matrix* f $A\ B$) $j\ i = f$ (*Rep-matrix* $A\ j\ i$) (*Rep-matrix* $B\ j\ i$)
by(*simp add*: *combine-matrix-def*)

lemma *combine-nrows-max*: $f\ 0\ 0 = 0 \Longrightarrow$ *nrows* (*combine-matrix* $f\ A\ B$) $\leq$ *max* (*nrows* A) (*nrows* B)
by (*simp add*: *nrows-le*)

lemma *combine-ncols-max*: $f\ 0\ 0 = 0 \Longrightarrow$ *ncols* (*combine-matrix* $f\ A\ B$) $\leq$ *max* (*ncols* A) (*ncols* B)
by (*simp add*: *ncols-le*)

lemma *combine-nrows*: $f\ 0\ 0 = 0 \Longrightarrow$ *nrows* $A \leq q \Longrightarrow$ *nrows* $B \leq q \Longrightarrow$ *nrows*(*combine-matrix* $f\ A\ B$) $\leq q$
by (*simp add*: *nrows-le*)

lemma *combine-ncols*: $f\ 0\ 0 = 0 \Longrightarrow$ *ncols* $A \leq q \Longrightarrow$ *ncols* $B \leq q \Longrightarrow$ *ncols*(*combine-matrix* $f\ A\ B$) $\leq q$
by (*simp add*: *ncols-le*)

definition *zero-r-neutral* :: $('a \Rightarrow 'b{::}zero \Rightarrow 'a) \Rightarrow$ *bool* **where**
zero-r-neutral $f == \forall\, a.\ f\ a\ 0 = a$

definition *zero-l-neutral* :: $('a{::}zero \Rightarrow 'b \Rightarrow 'b) \Rightarrow$ *bool* **where**
zero-l-neutral $f == \forall\, a.\ f\ 0\ a = a$

definition *zero-closed* :: $(('a{::}zero) \Rightarrow ('b{::}zero) \Rightarrow ('c{::}zero)) \Rightarrow$ *bool* **where**
zero-closed $f == (\forall\, x.\ f\ x\ 0 = 0) \wedge (\forall\, y.\ f\ 0\ y = 0)$

primrec *foldseq* :: $('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow (nat \Rightarrow 'a) \Rightarrow nat \Rightarrow 'a$
where
foldseq $f\ s\ 0 = s\ 0$
| *foldseq* $f\ s\ (Suc\ n) = f\ (s\ 0)$ (*foldseq* $f\ (\lambda k.\ s(Suc\ k))\ n$)

```
primrec foldseq-transposed :: ('a ⇒ 'a ⇒ 'a) ⇒ (nat ⇒ 'a) ⇒ nat ⇒ 'a
where
  foldseq-transposed f s 0 = s 0
| foldseq-transposed f s (Suc n) = f (foldseq-transposed f s n) (s (Suc n))

lemma foldseq-assoc:
  assumes a:associative f
  shows associative f ⟹ foldseq f = foldseq-transposed f
proof −
  have N ≤ n ⟹ foldseq f s N = foldseq-transposed f s N for N s n
  proof (induct n arbitrary: N s)
    case 0
    then show ?case
      by auto
  next
    case (Suc n)
    show ?case
    proof cases
      assume N ≤ n
      then show ?thesis
        by (simp add: Suc.hyps)
    next
      assume ~(N ≤ n)
      then have Nsuceq: N = Suc n
        using Suc.prems by linarith
      have neqz: n ≠ 0 ⟹ ∃ m. n = Suc m ∧ Suc m ≤ n
        by arith
      have assocf: !! x y z. f x (f y z) = f (f x y) z
        by (metis a associative-def)
     have f (f (s 0) (foldseq-transposed f (λk. s (Suc k)) m)) (s (Suc (Suc m))) =
              f (f (foldseq-transposed f s m) (s (Suc m))) (s (Suc (Suc m)))
        if n = Suc m for m
      proof −
        have §: foldseq-transposed f (λk. s (Suc k)) m = foldseq f (λk. s (Suc k))
m (is ?T1 = ?T2)
          by (simp add: Suc.hyps that)
        have f (s 0) ?T2 = foldseq f s (Suc m) by simp
        also have ... = foldseq-transposed f s (Suc m)
          using Suc.hyps that by blast
        also have ... = f (foldseq-transposed f s m) (s (Suc m))
          by simp
        finally show ?thesis
          by (simp add: §)
      qed
      then show foldseq f s N = foldseq-transposed f s N
        unfolding Nsuceq using assocf Suc.hyps neqz by force
    qed
  qed
  then show ?thesis
```

by *blast*
qed

lemma *foldseq-distr*:
assumes *assoc*: *associative f* **and** *comm*: *commutative f*
shows *foldseq f* (λ*k*. *f* (*u k*) (*v k*)) *n* = *f* (*foldseq f u n*) (*foldseq f v n*)
proof −
from *assoc* **have** *a*:!! *x y z*. *f* (*f x y*) *z* = *f x* (*f y z*) **by** (*simp add*: *associative-def*)
from *comm* **have** *b*: !! *x y*. *f x y* = *f y x* **by** (*simp add*: *commutative-def*)
from *assoc comm* **have** *c*: !! *x y z*. *f x* (*f y z*) = *f y* (*f x z*) **by** (*simp add*: *commutative-def associative-def*)
have (∀ *u v*. *foldseq f* (λ*k*. *f* (*u k*) (*v k*)) *n* = *f* (*foldseq f u n*) (*foldseq f v n*)) **for** *n*
by (*induct n*) (*simp-all add*: *assoc b c foldseq-assoc*)
then show *foldseq f* (λ*k*. *f* (*u k*) (*v k*)) *n* = *f* (*foldseq f u n*) (*foldseq f v n*) **by** *simp*
qed

theorem ⟦*associative f*; *associative g*; ∀ *a b c d*. *g* (*f a b*) (*f c d*) = *f* (*g a c*) (*g b d*); ∃ *x y*. (*f x*) ≠ (*f y*); ∃ *x y*. (*g x*) ≠ (*g y*); *f x x* = *x*; *g x x* = *x*⟧ ⟹ *f*=*g* | (∀ *y*. *f y x* = *y*) | (∀ *y*. *g y x* = *y*)
oops

lemma *foldseq-zero*:
assumes *fz*: *f 0 0* = *0* **and** *sz*: ∀ *i*. *i* ≤ *n* ⟶ *s i* = *0*
shows *foldseq f s n* = *0*
proof −
have ∀ *s*. (∀ *i*. *i* ≤ *n* ⟶ *s i* = *0*) ⟶ *foldseq f s n* = *0* **for** *n*
by (*induct n*) (*simp-all add*: *fz*)
then show *?thesis*
by (*simp add*: *sz*)
qed

lemma *foldseq-significant-positions*:
assumes *p*: ∀ *i*. *i* ≤ *N* ⟶ *S i* = *T i*
shows *foldseq f S N* = *foldseq f T N*
using *assms*
proof (*induction N arbitrary*: *S T*)
case *0*
then show *?case* **by** *simp*
next
case (*Suc N*)
then show *?case*
unfolding *foldseq.simps* **by** (*metis not-less-eq-eq le0*)
qed

lemma *foldseq-tail*:
assumes *M* ≤ *N*

```
  shows foldseq f S N = foldseq f (λk. (if k < M then (S k) else (foldseq f (λk.
S(k+M)) (N−M)))) M
  using assms
proof (induction N arbitrary: M S)
  case 0
  then show ?case by auto
next
  case (Suc N)
  show ?case
  proof (cases M = Suc N)
    case True
    then show ?thesis
      by (auto intro!: arg-cong [of concl: f (S 0)] foldseq-significant-positions)
  next
    case False
    then have M≤N
      using Suc.prems by force
    show ?thesis
    proof (cases M = 0)
      case True
      then show ?thesis
        by auto
    next
      case False
      then obtain M' where M': M = Suc M' M' ≤ N
        by (metis Suc-leD ‹M ≤ N› nat.nchotomy)
      then show ?thesis
        apply (simp add: Suc.IH [OF ‹M'≤N›])
        using add-Suc-right diff-Suc-Suc by presburger
    qed
  qed
qed

lemma foldseq-zerotail:
  assumes fz: f 0 0 = 0 and sz: ∀ i.  n ≤ i ⟶ s i = 0 and nm: n ≤ m
  shows foldseq f s n = foldseq f s m
  unfolding foldseq-tail[OF nm]
  by (metis (no-types, lifting) foldseq-zero fz le-add2 linorder-not-le sz)

lemma foldseq-zerotail2:
  assumes ∀ x. f x 0 = x
  and ∀ i. n < i ⟶ s i = 0
  and nm: n ≤ m
shows foldseq f s n = foldseq f s m
proof −
  have s i = (if i < n then s i else foldseq f (λk. s (k + n)) (m − n))
    if i≤n for i
  proof (cases m=n)
    case True
```

```
    then show ?thesis
      using that by auto
  next
    case False
    then obtain k where m−n = Suc k
      by (metis Suc-diff-Suc le-neq-implies-less nm)
    then show ?thesis
      apply simp
      by (simp add: assms(1,2) foldseq-zero nat-less-le that)
  qed
  then show ?thesis
    unfolding foldseq-tail[OF nm]
    by (auto intro: foldseq-significant-positions)
qed

lemma foldseq-zerostart:
  assumes f00x: ∀ x. f 0 (f 0 x) = f 0 x and 0: ∀ i. i ≤ n ⟶ s i = 0
  shows foldseq f s (Suc n) = f 0 (s (Suc n))
  using 0
proof (induction n arbitrary: s)
  case 0
  then show ?case by auto
next
  case (Suc n s)
  then show ?case
    apply (simp add: le-Suc-eq)
   by (smt (verit, ccfv-threshold) Suc.prems Suc-le-mono f00x foldseq-significant-positions
le0)
qed

lemma foldseq-zerostart2:
  assumes x: ∀ x. f 0 x = x and 0: ∀ i. i < n ⟶ s i = 0
  shows  foldseq f s n = s n
proof −
  show foldseq f s n = s n
  proof (cases n)
    case 0
    then show ?thesis
      by auto
  next
    case (Suc n')
    then show ?thesis
      by (metis 0 foldseq-zerostart le-imp-less-Suc x)
  qed
qed

lemma foldseq-almostzero:
  assumes f0x: ∀ x. f 0 x = x and fx0: ∀ x. f x 0 = x and s0: ∀ i. i ≠ j ⟶ s i
= 0
```

shows *foldseq f s n = (if (j ≤ n) then (s j) else 0)*
by (*smt* (*verit*, *ccfv-SIG*) *f0x foldseq-zerostart2 foldseq-zerotail2 fx0 le-refl nat-less-le s0*)

lemma *foldseq-distr-unary*:
assumes ⋀*a b*. *g* (*f a b*) = *f* (*g a*) (*g b*)
shows *g*(*foldseq f s n*) = *foldseq f* (λ*x*. *g*(*s x*)) *n*
proof (*induction n arbitrary*: *s*)
case *0*
then show *?case*
by *auto*
next
case (*Suc n*)
then show *?case*
using *assms* **by** *fastforce*
qed

definition *mult-matrix-n* :: *nat* ⇒ (('*a*::*zero*) ⇒ ('*b*::*zero*) ⇒ ('*c*::*zero*)) ⇒ ('*c* ⇒ '*c* ⇒ '*c*) ⇒ '*a matrix* ⇒ '*b matrix* ⇒ '*c matrix* **where**
mult-matrix-n n fmul fadd A B == *Abs-matrix*(λ*j i*. *foldseq fadd* (λ*k*. *fmul* (*Rep-matrix A j k*) (*Rep-matrix B k i*)) *n*)

definition *mult-matrix* :: (('*a*::*zero*) ⇒ ('*b*::*zero*) ⇒ ('*c*::*zero*)) ⇒ ('*c* ⇒ '*c* ⇒ '*c*) ⇒ '*a matrix* ⇒ '*b matrix* ⇒ '*c matrix* **where**
mult-matrix fmul fadd A B == *mult-matrix-n* (*max* (*ncols A*) (*nrows B*)) *fmul fadd A B*

lemma *mult-matrix-n*:
assumes *ncols A* ≤ *n nrows B* ≤ *n fadd 0 0* = *0 fmul 0 0* = *0*
shows *mult-matrix fmul fadd A B* = *mult-matrix-n n fmul fadd A B*
proof −
have *foldseq fadd* (λ*k*. *fmul* (*Rep-matrix A j k*) (*Rep-matrix B k i*))
(*max* (*ncols A*) (*nrows B*)) =
foldseq fadd (λ*k*. *fmul* (*Rep-matrix A j k*) (*Rep-matrix B k i*)) *n* **for** *i j*
using *assms* **by** (*simp add*: *foldseq-zerotail nrows-le ncols-le*)
then show *?thesis*
by (*simp add*: *mult-matrix-def mult-matrix-n-def*)
qed

lemma *mult-matrix-nm*:
assumes *ncols A* ≤ *n nrows B* ≤ *n ncols A* ≤ *m nrows B* ≤ *m fadd 0 0* = *0 fmul 0 0* = *0*
shows *mult-matrix-n n fmul fadd A B* = *mult-matrix-n m fmul fadd A B*
proof −
from *assms* **have** *mult-matrix-n n fmul fadd A B* = *mult-matrix fmul fadd A B*
by (*simp add*: *mult-matrix-n*)
also from *assms* **have** ... = *mult-matrix-n m fmul fadd A B*
by (*simp add*: *mult-matrix-n*[*THEN sym*])
finally show *mult-matrix-n n fmul fadd A B* = *mult-matrix-n m fmul fadd A B*

by *simp*
qed

definition *r-distributive* :: $('a \Rightarrow 'b \Rightarrow 'b) \Rightarrow ('b \Rightarrow 'b \Rightarrow 'b) \Rightarrow bool$ **where**
r-distributive fmul fadd == $\forall a\ u\ v.$ *fmul a* (*fadd u v*) = *fadd* (*fmul a u*) (*fmul a v*)

definition *l-distributive* :: $('a \Rightarrow 'b \Rightarrow 'a) \Rightarrow ('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow bool$ **where**
l-distributive fmul fadd == $\forall a\ u\ v.$ *fmul* (*fadd u v*) *a* = *fadd* (*fmul u a*) (*fmul v a*)

definition *distributive* :: $('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow ('a \Rightarrow 'a \Rightarrow 'a) \Rightarrow bool$ **where**
distributive fmul fadd == *l-distributive fmul fadd* $\wedge$ *r-distributive fmul fadd*

lemma *max1*: !! *a x y.* (*a*::*nat*) $\leq$ *x* $\Longrightarrow$ *a* $\leq$ *max x y* **by** (*arith*)
lemma *max2*: !! *b x y.* (*b*::*nat*) $\leq$ *y* $\Longrightarrow$ *b* $\leq$ *max x y* **by** (*arith*)

lemma *r-distributive-matrix*:
assumes
r-distributive fmul fadd
associative fadd
commutative fadd
fadd 0 0 = 0
$\forall$ *a. fmul a 0 = 0*
$\forall$ *a. fmul 0 a = 0*
shows *r-distributive* (*mult-matrix fmul fadd*) (*combine-matrix fadd*)
proof −
from *assms* **show** *?thesis*
apply (*simp add*: *r-distributive-def mult-matrix-def*, *auto*)
proof −
fix *a*::'*a matrix*
fix *u*::'*b matrix*
fix *v*::'*b matrix*
let *?mx* = *max* (*ncols a*) (*max* (*nrows u*) (*nrows v*))
from *assms* **show** *mult-matrix-n* (*max* (*ncols a*) (*nrows* (*combine-matrix fadd u v*))) *fmul fadd a* (*combine-matrix fadd u v*) =
combine-matrix fadd (*mult-matrix-n* (*max* (*ncols a*) (*nrows u*)) *fmul fadd a u*) (*mult-matrix-n* (*max* (*ncols a*) (*nrows v*)) *fmul fadd a v*)
apply (*subst mult-matrix-nm*[*of - - - ?mx fadd fmul*])
apply (*simp add*: *max1 max2 combine-nrows combine-ncols*)+
apply (*subst mult-matrix-nm*[*of - - v ?mx fadd fmul*])
apply (*simp add*: *max1 max2 combine-nrows combine-ncols*)+
apply (*subst mult-matrix-nm*[*of - - u ?mx fadd fmul*])
apply (*simp add*: *max1 max2 combine-nrows combine-ncols*)+
apply (*simp add*: *mult-matrix-n-def r-distributive-def foldseq-distr*[*of fadd*])
apply (*simp add*: *combine-matrix-def combine-infmatrix-def*)
apply (*intro ext arg-cong*[*of concl*: *Abs-matrix*])
apply (*simplesubst RepAbs-matrix*)
apply (*simp*, *auto*)

```
      apply (rule exI[of - nrows a], simp add: nrows-le foldseq-zero)
      apply (rule exI[of - ncols v], simp add: ncols-le foldseq-zero)
      apply (subst RepAbs-matrix)
      apply (simp, auto)
      apply (rule exI[of - nrows a], simp add: nrows-le foldseq-zero)
      apply (rule exI[of - ncols u], simp add: ncols-le foldseq-zero)
      done
  qed
qed

lemma l-distributive-matrix:
 assumes
  l-distributive fmul fadd
  associative fadd
  commutative fadd
  fadd 0 0 = 0
  ∀ a. fmul a 0 = 0
  ∀ a. fmul 0 a = 0
 shows l-distributive (mult-matrix fmul fadd) (combine-matrix fadd)
proof −
  from assms show ?thesis
    apply (simp add: l-distributive-def mult-matrix-def, auto)
    proof −
      fix a::'b matrix
      fix u::'a matrix
      fix v::'a matrix
      let ?mx = max (nrows a) (max (ncols u) (ncols v))
        from assms show mult-matrix-n (max (ncols (combine-matrix fadd u v))
(nrows a)) fmul fadd (combine-matrix fadd u v) a =
              combine-matrix fadd (mult-matrix-n (max (ncols u) (nrows a)) fmul
fadd u a) (mult-matrix-n (max (ncols v) (nrows a)) fmul fadd v a)
        apply (subst mult-matrix-nm[of v - - ?mx fadd fmul])
        apply (simp add: max1 max2 combine-nrows combine-ncols)+
        apply (subst mult-matrix-nm[of u - - ?mx fadd fmul])
        apply (simp add: max1 max2 combine-nrows combine-ncols)+
        apply (subst mult-matrix-nm[of - - - ?mx fadd fmul])
        apply (simp add: max1 max2 combine-nrows combine-ncols)+
        apply (simp add: mult-matrix-n-def l-distributive-def foldseq-distr[of fadd])
        apply (simp add: combine-matrix-def combine-infmatrix-def)
        apply (intro ext arg-cong[of concl: Abs-matrix])
        apply (simplesubst RepAbs-matrix)
        apply (simp, auto)
        apply (rule exI[of - nrows v], simp add: nrows-le foldseq-zero)
        apply (rule exI[of - ncols a], simp add: ncols-le foldseq-zero)
        apply (subst RepAbs-matrix)
        apply (simp, auto)
        apply (rule exI[of - nrows u], simp add: nrows-le foldseq-zero)
        apply (rule exI[of - ncols a], simp add: ncols-le foldseq-zero)
        done
```

qed
qed

instantiation *matrix* :: (*zero*) *zero*
begin

definition *zero-matrix-def*: *0* = *Abs-matrix* (λ*j i*. *0*)

instance ..

end

lemma *Rep-zero-matrix-def*[*simp*]: *Rep-matrix 0 j i* = *0*
by (*simp add*: *RepAbs-matrix zero-matrix-def*)

lemma *zero-matrix-def-nrows*[*simp*]: *nrows 0* = *0*
using *nrows-le* **by** *force*

lemma *zero-matrix-def-ncols*[*simp*]: *ncols 0* = *0*
using *ncols-le* **by** *fastforce*

lemma *combine-matrix-zero-l-neutral*: *zero-l-neutral f* ⟹ *zero-l-neutral* (*combine-matrix f*)
by (*simp add*: *zero-l-neutral-def combine-matrix-def combine-infmatrix-def*)

lemma *combine-matrix-zero-r-neutral*: *zero-r-neutral f* ⟹ *zero-r-neutral* (*combine-matrix f*)
by (*simp add*: *zero-r-neutral-def combine-matrix-def combine-infmatrix-def*)

lemma *mult-matrix-zero-closed*: ⟦*fadd 0 0* = *0*; *zero-closed fmul*⟧ ⟹ *zero-closed* (*mult-matrix fmul fadd*)
apply (*simp add*: *zero-closed-def mult-matrix-def mult-matrix-n-def*)
by (*simp add*: *foldseq-zero zero-matrix-def*)

lemma *mult-matrix-n-zero-right*[*simp*]: ⟦*fadd 0 0* = *0*; ∀ *a*. *fmul a 0* = *0*⟧ ⟹ *mult-matrix-n n fmul fadd A 0* = *0*
by (*simp add*: *RepAbs-matrix foldseq-zero matrix-eqI mult-matrix-n-def*)

lemma *mult-matrix-n-zero-left*[*simp*]: ⟦*fadd 0 0* = *0*; ∀ *a*. *fmul 0 a* = *0*⟧ ⟹ *mult-matrix-n n fmul fadd 0 A* = *0*
by (*simp add*: *RepAbs-matrix foldseq-zero matrix-eqI mult-matrix-n-def*)

lemma *mult-matrix-zero-left*[*simp*]: ⟦*fadd 0 0* = *0*; ∀ *a*. *fmul 0 a* = *0*⟧ ⟹ *mult-matrix fmul fadd 0 A* = *0*
by (*simp add*: *mult-matrix-def*)

lemma *mult-matrix-zero-right*[*simp*]: ⟦*fadd 0 0* = *0*; ∀ *a*. *fmul a 0* = *0*⟧ ⟹ *mult-matrix fmul fadd A 0* = *0*
by (*simp add*: *mult-matrix-def*)

lemma *apply-matrix-zero*[*simp*]: $f\ 0 = 0 \Longrightarrow$ *apply-matrix* $f\ 0 = 0$
by (*simp add*: *matrix-eqI*)

lemma *combine-matrix-zero*: $f\ 0\ 0 = 0 \Longrightarrow$ *combine-matrix* $f\ 0\ 0 = 0$
by (*simp add*: *matrix-eqI*)

lemma *transpose-matrix-zero*[*simp*]: *transpose-matrix* $0 = 0$
by (*simp add*: *matrix-eqI*)

lemma *apply-zero-matrix-def*[*simp*]: *apply-matrix* $(\lambda x.\ 0)\ A = 0$
by (*simp add*: *matrix-eqI*)

definition *singleton-matrix* :: *nat* ⇒ *nat* ⇒ ('*a*::*zero*) ⇒ '*a matrix* **where**
singleton-matrix j i a == *Abs-matrix*($\lambda m\ n.$ *if* $j = m \wedge i = n$ *then a else* 0)

definition *move-matrix* :: ('*a*::*zero*) *matrix* ⇒ *int* ⇒ *int* ⇒ '*a matrix* **where**
move-matrix A y x == *Abs-matrix*($\lambda j\ i.$ *if* $(((int\ j)-y) < 0) \mid (((int\ i)-x) < 0)$
then 0 else Rep-matrix A (*nat* ((*int j*)−*y*)) (*nat* ((*int i*)−*x*)))

definition *take-rows* :: ('*a*::*zero*) *matrix* ⇒ *nat* ⇒ '*a matrix* **where**
take-rows A r == *Abs-matrix*($\lambda j\ i.$ *if* $(j < r)$ *then* (*Rep-matrix A j i*) *else* 0)

definition *take-columns* :: ('*a*::*zero*) *matrix* ⇒ *nat* ⇒ '*a matrix* **where**
take-columns A c == *Abs-matrix*($\lambda j\ i.$ *if* $(i < c)$ *then* (*Rep-matrix A j i*) *else* 0)

definition *column-of-matrix* :: ('*a*::*zero*) *matrix* ⇒ *nat* ⇒ '*a matrix* **where**
column-of-matrix A n == *take-columns* (*move-matrix A 0* (− *int n*)) *1*

definition *row-of-matrix* :: ('*a*::*zero*) *matrix* ⇒ *nat* ⇒ '*a matrix* **where**
row-of-matrix A m == *take-rows* (*move-matrix A* (− *int m*) *0*) *1*

lemma *Rep-singleton-matrix*[*simp*]: *Rep-matrix* (*singleton-matrix j i e*) *m n* = (*if*
$j = m \wedge i = n$ *then e else* 0)
unfolding *singleton-matrix-def*
by (*smt* (*verit*, *del-insts*) *RepAbs-matrix Suc-n-not-le-n*)

lemma *apply-singleton-matrix*[*simp*]: $f\ 0 = 0 \Longrightarrow$ *apply-matrix f* (*singleton-matrix*
j i x) = (*singleton-matrix j i* (*f x*))
by (*simp add*: *matrix-eqI*)

lemma *singleton-matrix-zero*[*simp*]: *singleton-matrix j i* $0 = 0$
by (*simp add*: *singleton-matrix-def zero-matrix-def*)

lemma *nrows-singleton*[*simp*]: *nrows*(*singleton-matrix j i e*) = (*if e* = *0 then 0 else*
Suc j)
proof −
have $e \neq 0 \Longrightarrow$ *Suc j* ≤ *nrows* (*singleton-matrix j i e*)
by (*metis Rep-singleton-matrix not-less-eq-eq nrows*)

then show *?thesis*
by (*simp add*: *le-antisym nrows-le*)
qed

lemma *ncols-singleton*[*simp*]: *ncols*(*singleton-matrix j i e*) = (*if e* = *0 then 0 else Suc i*)
by (*simp add*: *Suc-leI le-antisym ncols-le ncols-notzero*)

lemma *combine-singleton*: *f 0 0* = *0* ⟹ *combine-matrix f* (*singleton-matrix j i a*) (*singleton-matrix j i b*) = *singleton-matrix j i* (*f a b*)
apply (*simp add*: *singleton-matrix-def combine-matrix-def combine-infmatrix-def*)
apply (*intro ext arg-cong*[*of concl*: *Abs-matrix*])
by (*metis Rep-singleton-matrix singleton-matrix-def*)

lemma *transpose-singleton*[*simp*]: *transpose-matrix* (*singleton-matrix j i a*) = *singleton-matrix i j a*
by (*simp add*: *matrix-eqI*)

lemma *Rep-move-matrix*[*simp*]:
Rep-matrix (*move-matrix A y x*) *j i* =
(*if* (((*int j*)−*y*) < *0*) | (((*int i*)−*x*) < *0*) *then 0 else Rep-matrix A* (*nat*((*int j*)−*y*)) (*nat*((*int i*)−*x*)))
apply (*simp add*: *move-matrix-def*)
by (*subst RepAbs-matrix*,
rule exI[*of* - (*nrows A*)+(*nat* |*y*|)], *auto*, *rule nrows*, *arith*,
rule exI[*of* - (*ncols A*)+(*nat* |*x*|)], *auto*, *rule ncols*, *arith*)+

lemma *move-matrix-0-0*[*simp*]: *move-matrix A 0 0* = *A*
by (*simp add*: *move-matrix-def*)

lemma *move-matrix-ortho*: *move-matrix A j i* = *move-matrix* (*move-matrix A j 0*) *0 i*
by (*simp add*: *matrix-eqI*)

lemma *transpose-move-matrix*[*simp*]:
transpose-matrix (*move-matrix A x y*) = *move-matrix* (*transpose-matrix A*) *y x*
by (*simp add*: *matrix-eqI*)

lemma *move-matrix-singleton*[*simp*]: *move-matrix* (*singleton-matrix u v x*) *j i* =
(*if* (*j* + *int u* < *0*) | (*i* + *int v* < *0*) *then 0 else* (*singleton-matrix* (*nat* (*j* + *int u*)) (*nat* (*i* + *int v*)) *x*))
by (*auto intro*!: *matrix-eqI split*: *if-split-asm*)

lemma *Rep-take-columns*[*simp*]:
Rep-matrix (*take-columns A c*) *j i* = (*if i* < *c then* (*Rep-matrix A j i*) *else 0*)
unfolding *take-columns-def*
by (*smt* (*verit*, *best*) *RepAbs-matrix leD nrows*)

lemma *Rep-take-rows*[*simp*]:

Rep-matrix (*take-rows A r*) *j i* = (*if j* < *r then* (*Rep-matrix A j i*) *else 0*)
unfolding *take-rows-def*
by (*smt* (*verit*, *best*) *RepAbs-matrix leD ncols*)

lemma *Rep-column-of-matrix*[*simp*]:
Rep-matrix (*column-of-matrix A c*) *j i* = (*if i* = *0 then* (*Rep-matrix A j c*) *else 0*)
by (*simp add*: *column-of-matrix-def*)

lemma *Rep-row-of-matrix*[*simp*]:
Rep-matrix (*row-of-matrix A r*) *j i* = (*if j* = *0 then* (*Rep-matrix A r i*) *else 0*)
by (*simp add*: *row-of-matrix-def*)

lemma *column-of-matrix*: *ncols A* ≤ *n* ⟹ *column-of-matrix A n* = *0*
by (*simp add*: *matrix-eqI ncols*)

lemma *row-of-matrix*: *nrows A* ≤ *n* ⟹ *row-of-matrix A n* = *0*
by (*simp add*: *matrix-eqI nrows*)

lemma *mult-matrix-singleton-right*[*simp*]:
assumes ∀ *x*. *fmul x 0* = *0* ∀ *x*. *fmul 0 x* = *0* ∀ *x*. *fadd 0 x* = *x* ∀ *x*. *fadd x 0* = *x*
shows (*mult-matrix fmul fadd A* (*singleton-matrix j i e*)) = *apply-matrix* (λ*x*. *fmul x e*) (*move-matrix* (*column-of-matrix A j*) *0* (*int i*))
using *assms*
unfolding *mult-matrix-def*
apply (*subst mult-matrix-nm*[*of - - - max* (*ncols A*) (*Suc j*)];
simp add: *mult-matrix-n-def apply-matrix-def apply-infmatrix-def*)
apply (*intro ext arg-cong*[*of concl*: *Abs-matrix*])
by (*simp add*: *max-def assms foldseq-almostzero*[*of - j*])

lemma *mult-matrix-ext*:
assumes
eprem:
∃ *e*. (∀ *a b*. *a* ≠ *b* ⟶ *fmul a e* ≠ *fmul b e*)
and *fprems*:
∀ *a*. *fmul 0 a* = *0*
∀ *a*. *fmul a 0* = *0*
∀ *a*. *fadd a 0* = *a*
∀ *a*. *fadd 0 a* = *a*
and *contraprems*: *mult-matrix fmul fadd A* = *mult-matrix fmul fadd B*
shows *A* = *B*
proof(*rule ccontr*)
assume *A* ≠ *B*
then obtain *J I* **where** *ne*: (*Rep-matrix A J I*) ≠ (*Rep-matrix B J I*)
by (*meson matrix-eqI*)
from *eprem* **obtain** *e* **where** *eprops*:(∀ *a b*. *a* ≠ *b* ⟶ *fmul a e* ≠ *fmul b e*) **by** *blast*
let *?S* = *singleton-matrix I 0 e*
let *?comp* = *mult-matrix fmul fadd*

```
  have d: !!x f g. f = g ⟹ f x = g x by blast
  have e: (λx. fmul x e) 0 = 0 by (simp add: assms)
  have Rep-matrix (apply-matrix (λx. fmul x e) (column-of-matrix A I)) ≠
        Rep-matrix (apply-matrix (λx. fmul x e) (column-of-matrix B I))
    using fprems
    by (metis Rep-apply-matrix Rep-column-of-matrix eprops ne)
  then have ?comp A ?S ≠ ?comp B ?S
    by (simp add: fprems eprops Rep-matrix-inject)
  with contraprems show False by simp
qed

definition foldmatrix :: ('a ⇒ 'a ⇒ 'a) ⇒ ('a ⇒ 'a ⇒ 'a) ⇒ ('a infmatrix) ⇒
nat ⇒ nat ⇒ 'a where
  foldmatrix f g A m n == foldseq-transposed g (λj. foldseq f (A j) n) m

definition foldmatrix-transposed :: ('a ⇒ 'a ⇒ 'a) ⇒ ('a ⇒ 'a ⇒ 'a) ⇒ ('a
infmatrix) ⇒ nat ⇒ nat ⇒ 'a where
  foldmatrix-transposed f g A m n == foldseq g (λj. foldseq-transposed f (A j) n)
m

lemma foldmatrix-transpose:
  assumes ∀ a b c d. g(f a b) (f c d) = f (g a c) (g b d)
  shows foldmatrix f g A m n = foldmatrix-transposed g f (transpose-infmatrix A)
n m
proof −
  have forall:⋀P x. (∀ x. P x) ⟹ P x by auto
 have tworows:∀ A. foldmatrix f g A 1 n = foldmatrix-transposed g f (transpose-infmatrix
A) n 1
  proof (induct n)
    case 0
    then show ?case
      by (simp add: foldmatrix-def foldmatrix-transposed-def)
  next
    case (Suc n)
    then show ?case
      apply (clarsimp simp: foldmatrix-def foldmatrix-transposed-def assms)
      apply (rule arg-cong [of concl: f -])
      by meson
  qed
  have foldseq-transposed g (λj. foldseq f (A j) n) m =
    foldseq f (λj. foldseq-transposed g (transpose-infmatrix A j) m) n
  proof (induct m)
    case 0
    then show ?case by auto
  next
    case (Suc m)
    then show ?case
      using tworows
      apply (drule-tac x=λj i. (if j = 0 then (foldseq-transposed g (λu. A u i) m)
```

else (*A* (*Suc m*) *i*)) **in** *spec*)
by (*simp add*: *Suc foldmatrix-def foldmatrix-transposed-def*)
qed
then show *foldmatrix f g A m n* = *foldmatrix-transposed g f* (*transpose-infmatrix A*) *n m*
by (*simp add*: *foldmatrix-def foldmatrix-transposed-def*)
qed

lemma *foldseq-foldseq*:
assumes *associative f associative g* ∀ *a b c d*. *g*(*f a b*) (*f c d*) = *f* (*g a c*) (*g b d*)
shows
foldseq g (λ*j*. *foldseq f* (*A j*) *n*) *m* = *foldseq f* (λ*j*. *foldseq g* ((*transpose-infmatrix A*) *j*) *m*) *n*
using *foldmatrix-transpose*[*of g f A m n*]
by (*simp add*: *foldmatrix-def foldmatrix-transposed-def foldseq-assoc*[*THEN sym*] *assms*)

lemma *mult-n-nrows*:
assumes ∀ *a*. *fmul 0 a* = *0* ∀ *a*. *fmul a 0* = *0 fadd 0 0* = *0*
shows *nrows* (*mult-matrix-n n fmul fadd A B*) ≤ *nrows A*
unfolding *nrows-le mult-matrix-n-def*
apply (*subst RepAbs-matrix*)
apply (*rule-tac x*=*nrows A* **in** *exI*)
apply (*simp add*: *nrows assms foldseq-zero*)
apply (*rule-tac x*=*ncols B* **in** *exI*)
apply (*simp add*: *ncols assms foldseq-zero*)
apply (*simp add*: *nrows assms foldseq-zero*)
done

lemma *mult-n-ncols*:
assumes ∀ *a*. *fmul 0 a* = *0* ∀ *a*. *fmul a 0* = *0 fadd 0 0* = *0*
shows *ncols* (*mult-matrix-n n fmul fadd A B*) ≤ *ncols B*
unfolding *ncols-le mult-matrix-n-def*
apply (*subst RepAbs-matrix*)
apply (*rule-tac x*=*nrows A* **in** *exI*)
apply (*simp add*: *nrows assms foldseq-zero*)
apply (*rule-tac x*=*ncols B* **in** *exI*)
apply (*simp add*: *ncols assms foldseq-zero*)
apply (*simp add*: *ncols assms foldseq-zero*)
done

lemma *mult-nrows*:
assumes
∀ *a*. *fmul 0 a* = *0*
∀ *a*. *fmul a 0* = *0*
fadd 0 0 = *0*
shows *nrows* (*mult-matrix fmul fadd A B*) ≤ *nrows A*
by (*simp add*: *mult-matrix-def mult-n-nrows assms*)

lemma *mult-ncols*:
assumes
$\forall a.\ fmul\ 0\ a = 0$
$\forall a.\ fmul\ a\ 0 = 0$
$fadd\ 0\ 0 = 0$
shows $ncols\ (mult\text{-}matrix\ fmul\ fadd\ A\ B) \leq ncols\ B$
by (*simp add*: *mult-matrix-def mult-n-ncols assms*)

lemma *nrows-move-matrix-le*: $nrows\ (move\text{-}matrix\ A\ j\ i) \leq nat((int\ (nrows\ A)) + j)$
by (*smt* (*verit*) *Rep-move-matrix int-nat-eq nrows nrows-le of-nat-le-iff*)

lemma *ncols-move-matrix-le*: $ncols\ (move\text{-}matrix\ A\ j\ i) \leq nat((int\ (ncols\ A)) + i)$
by (*metis nrows-move-matrix-le nrows-transpose transpose-move-matrix*)

lemma *mult-matrix-assoc*:
assumes
$\forall a.\ fmul1\ 0\ a = 0$
$\forall a.\ fmul1\ a\ 0 = 0$
$\forall a.\ fmul2\ 0\ a = 0$
$\forall a.\ fmul2\ a\ 0 = 0$
$fadd1\ 0\ 0 = 0$
$fadd2\ 0\ 0 = 0$
$\forall a\ b\ c\ d.\ fadd2\ (fadd1\ a\ b)\ (fadd1\ c\ d) = fadd1\ (fadd2\ a\ c)\ (fadd2\ b\ d)$
$associative\ fadd1$
$associative\ fadd2$
$\forall a\ b\ c.\ fmul2\ (fmul1\ a\ b)\ c = fmul1\ a\ (fmul2\ b\ c)$
$\forall a\ b\ c.\ fmul2\ (fadd1\ a\ b)\ c = fadd1\ (fmul2\ a\ c)\ (fmul2\ b\ c)$
$\forall a\ b\ c.\ fmul1\ c\ (fadd2\ a\ b) = fadd2\ (fmul1\ c\ a)\ (fmul1\ c\ b)$
shows $mult\text{-}matrix\ fmul2\ fadd2\ (mult\text{-}matrix\ fmul1\ fadd1\ A\ B)\ C = mult\text{-}matrix\ fmul1\ fadd1\ A\ (mult\text{-}matrix\ fmul2\ fadd2\ B\ C)$
proof −
have *comb-left*: $!!\ A\ B\ x\ y.\ A = B \Longrightarrow (Rep\text{-}matrix\ (Abs\text{-}matrix\ A))\ x\ y = (Rep\text{-}matrix(Abs\text{-}matrix\ B))\ x\ y$ **by** *blast*
have *fmul2fadd1fold*: $!!\ x\ s\ n.\ fmul2\ (foldseq\ fadd1\ s\ n)\ \ x = foldseq\ fadd1\ (\lambda k.\ fmul2\ (s\ k)\ x)\ n$
by (*rule-tac g1* $= \lambda y.\ fmul2\ y\ x$ **in** *ssubst* [*OF foldseq-distr-unary*], *insert assms*, *simp-all*)
have *fmul1fadd2fold*: $!!\ x\ s\ n.\ fmul1\ x\ (foldseq\ fadd2\ s\ n) = foldseq\ fadd2\ (\lambda k.\ fmul1\ x\ (s\ k))\ n$
using *assms* **by** (*rule-tac g1* $= \lambda y.\ fmul1\ x\ y$ **in** *ssubst* [*OF foldseq-distr-unary*], *simp-all*)
let *?N* $= max\ (ncols\ A)\ (max\ (ncols\ B)\ (max\ (nrows\ B)\ (nrows\ C)))$
show *?thesis*
apply (*intro matrix-eqI*)
apply (*simp add*: *mult-matrix-def*)
apply (*simplesubst mult-matrix-nm*[*of - max* (*ncols* (*mult-matrix-n* (*max* (*ncols A*) (*nrows B*)) *fmul1 fadd1 A B*)) (*nrows C*) *- max* (*ncols B*) (*nrows C*)])

apply (*simp add*: *max1 max2 mult-n-ncols mult-n-nrows assms*)+
apply (*simplesubst mult-matrix-nm*[*of* - *max* (*ncols A*) (*nrows* (*mult-matrix-n* (*max* (*ncols B*) (*nrows C*)) *fmul2 fadd2 B C*)) - *max* (*ncols A*) (*nrows B*)])
apply (*simp add*: *max1 max2 mult-n-ncols mult-n-nrows assms*)+
apply (*simplesubst mult-matrix-nm*[*of* - - - *?N*])
apply (*simp add*: *max1 max2 mult-n-ncols mult-n-nrows assms*)+
apply (*simplesubst mult-matrix-nm*[*of* - - - *?N*])
apply (*simp add*: *max1 max2 mult-n-ncols mult-n-nrows assms*)+
apply (*simplesubst mult-matrix-nm*[*of* - - - *?N*])
apply (*simp add*: *max1 max2 mult-n-ncols mult-n-nrows assms*)+
apply (*simplesubst mult-matrix-nm*[*of* - - - *?N*])
apply (*simp add*: *max1 max2 mult-n-ncols mult-n-nrows assms*)+
apply (*simp add*: *mult-matrix-n-def*)
apply (*rule comb-left*)
apply ((*rule ext*)+, *simp*)
apply (*simplesubst RepAbs-matrix*)
apply (*rule exI*[*of* - *nrows B*])
apply (*simp add*: *nrows assms foldseq-zero*)
apply (*rule exI*[*of* - *ncols C*])
apply (*simp add*: *assms ncols foldseq-zero*)
apply (*subst RepAbs-matrix*)
apply (*rule exI*[*of* - *nrows A*])
apply (*simp add*: *nrows assms foldseq-zero*)
apply (*rule exI*[*of* - *ncols B*])
apply (*simp add*: *assms ncols foldseq-zero*)
apply (*simp add*: *fmul2fadd1fold fmul1fadd2fold assms*)
apply (*subst foldseq-foldseq*)
apply (*simp add*: *assms*)+
apply (*simp add*: *transpose-infmatrix*)
done
qed

lemma *mult-matrix-assoc-simple*:
assumes
$\forall$ *a*. *fmul 0 a* = *0*
$\forall$ *a*. *fmul a 0* = *0*
associative fadd
commutative fadd
associative fmul
distributive fmul fadd
shows *mult-matrix fmul fadd* (*mult-matrix fmul fadd A B*) *C* = *mult-matrix fmul fadd A* (*mult-matrix fmul fadd B C*)
by (*smt* (*verit*) *assms associative-def commutative-def distributive-def l-distributive-def mult-matrix-assoc r-distributive-def*)

lemma *transpose-apply-matrix*: *f 0* = *0* $\Longrightarrow$ *transpose-matrix* (*apply-matrix f A*) = *apply-matrix f* (*transpose-matrix A*)
by (*simp add*: *matrix-eqI*)

lemma *transpose-combine-matrix*: $f\ 0\ 0 = 0 \Longrightarrow$ *transpose-matrix* (*combine-matrix* $f\ A\ B$) = *combine-matrix* f (*transpose-matrix* A) (*transpose-matrix* B)
by (*simp add*: *matrix-eqI*)

lemma *Rep-mult-matrix*:
assumes $\forall\, a.$ *fmul* $0\ a = 0\ \forall\, a.$ *fmul* $a\ 0 = 0$ *fadd* $0\ 0 = 0$
shows
Rep-matrix(*mult-matrix fmul fadd* $A\ B$) $j\ i =$
foldseq fadd ($\lambda k.$ *fmul* (*Rep-matrix* $A\ j\ k$) (*Rep-matrix* $B\ k\ i$)) (*max* (*ncols* A) (*nrows* B))
using *assms*
apply (*simp add*: *mult-matrix-def mult-matrix-n-def*)
apply (*subst RepAbs-matrix*)
apply (*rule exI*[*of* - *nrows* A], *simp add*: *nrows foldseq-zero*)
apply (*rule exI*[*of* - *ncols* B], *simp add*: *ncols foldseq-zero*)
apply *simp*
done

lemma *transpose-mult-matrix*:
assumes
$\forall\, a.$ *fmul* $0\ a = 0$
$\forall\, a.$ *fmul* $a\ 0 = 0$
fadd $0\ 0 = 0$
$\forall\, x\ y.$ *fmul* $y\ x =$ *fmul* $x\ y$
shows
transpose-matrix (*mult-matrix fmul fadd* $A\ B$) = *mult-matrix fmul fadd* (*transpose-matrix* B) (*transpose-matrix* A)
using *assms*
by (*simp add*: *matrix-eqI Rep-mult-matrix ac-simps*)

lemma *column-transpose-matrix*: *column-of-matrix* (*transpose-matrix* A) n = *transpose-matrix* (*row-of-matrix* $A\ n$)
by (*simp add*: *matrix-eqI*)

lemma *take-columns-transpose-matrix*: *take-columns* (*transpose-matrix* A) n = *transpose-matrix* (*take-rows* $A\ n$)
by (*simp add*: *matrix-eqI*)

instantiation *matrix* :: ({*zero*, *ord*}) *ord*
begin

definition
le-matrix-def: $A \leq B \longleftrightarrow (\forall\, j\ i.$ *Rep-matrix* $A\ j\ i \leq$ *Rep-matrix* $B\ j\ i)$

definition
less-def: $A < (B::'a\ matrix) \longleftrightarrow A \leq B \wedge \neg\ B \leq A$

instance ..

end

instance *matrix* :: ({*zero*, *order*}) *order*
proof
  fix *x y z* :: *'a matrix*
  assume $x \leq y$ $y \leq z$
  show $x \leq z$
    by (*meson* ‹$x \leq y$› ‹$y \leq z$› *le-matrix-def order-trans*)
next
  fix *x y* :: *'a matrix*
  assume $x \leq y$ $y \leq x$
  show $x = y$
    by (*meson* ‹$x \leq y$› ‹$y \leq x$› *le-matrix-def matrix-eqI order-antisym*)
qed (*auto simp*: *less-def le-matrix-def*)

lemma *le-apply-matrix*:
  assumes
  $f\ 0 = 0$
  $\forall x\ y.\ x \leq y \longrightarrow f\ x \leq f\ y$
  (a::('a::{*ord*, *zero*}) *matrix*) $\leq b$
  shows *apply-matrix f a* $\leq$ *apply-matrix f b*
  using *assms* **by** (*simp add*: *le-matrix-def*)

lemma *le-combine-matrix*:
  assumes
  $f\ 0\ 0 = 0$
  $\forall a\ b\ c\ d.\ a \leq b \wedge c \leq d \longrightarrow f\ a\ c \leq f\ b\ d$
  $A \leq B$
  $C \leq D$
  shows *combine-matrix f A C* $\leq$ *combine-matrix f B D*
  using *assms* **by** (*simp add*: *le-matrix-def*)

lemma *le-left-combine-matrix*:
  assumes
  $f\ 0\ 0 = 0$
  $\forall a\ b\ c.\ a \leq b \longrightarrow f\ c\ a \leq f\ c\ b$
  $A \leq B$
  shows *combine-matrix f C A* $\leq$ *combine-matrix f C B*
  using *assms* **by** (*simp add*: *le-matrix-def*)

lemma *le-right-combine-matrix*:
  assumes
  $f\ 0\ 0 = 0$
  $\forall a\ b\ c.\ a \leq b \longrightarrow f\ a\ c \leq f\ b\ c$
  $A \leq B$
  shows *combine-matrix f A C* $\leq$ *combine-matrix f B C*
  using *assms* **by** (*simp add*: *le-matrix-def*)

lemma *le-transpose-matrix*: ($A \leq B$) = (*transpose-matrix A* $\leq$ *transpose-matrix*

B)
by (*simp add*: *le-matrix-def*, *auto*)

lemma *le-foldseq*:
assumes
$\forall\, a\ b\ c\ d\ .\ a \leq b \wedge c \leq d \longrightarrow f\ a\ c \leq f\ b\ d$
$\forall\, i.\ i \leq n \longrightarrow s\ i \leq t\ i$
shows *foldseq f s n* $\leq$ *foldseq f t n*
proof −
have $\forall\, s\ t.\ (\forall\, i.\ i<=n \longrightarrow s\ i \leq t\ i) \longrightarrow$ *foldseq f s n* $\leq$ *foldseq f t n*
by (*induct n*) (*simp-all add*: *assms*)
then show *foldseq f s n* $\leq$ *foldseq f t n* **using** *assms* **by** *simp*
qed

lemma *le-left-mult*:
assumes
$\forall\, a\ b\ c\ d.\ a \leq b \wedge c \leq d \longrightarrow$ *fadd a c* $\leq$ *fadd b d*
$\forall\, c\ a\ b.\quad 0 \leq c \wedge a \leq b \longrightarrow$ *fmul c a* $\leq$ *fmul c b*
$\forall\, a.$ *fmul 0 a* $= 0$
$\forall\, a.$ *fmul a 0* $= 0$
fadd 0 0 $= 0$
$0 \leq C$
$A \leq B$
shows *mult-matrix fmul fadd C A* $\leq$ *mult-matrix fmul fadd C B*
using *assms*
apply (*auto simp*: *le-matrix-def Rep-mult-matrix*)
apply (*simplesubst foldseq-zerotail*[*of - - - max* (*ncols C*) (*max* (*nrows A*) (*nrows B*))], *simp-all add*: *nrows ncols max1 max2*)+
apply (*rule le-foldseq*)
apply (*auto*)
done

lemma *le-right-mult*:
assumes
$\forall\, a\ b\ c\ d.\ a \leq b \wedge c \leq d \longrightarrow$ *fadd a c* $\leq$ *fadd b d*
$\forall\, c\ a\ b.\ 0 \leq c \wedge a \leq b \longrightarrow$ *fmul a c* $\leq$ *fmul b c*
$\forall\, a.$ *fmul 0 a* $= 0$
$\forall\, a.$ *fmul a 0* $= 0$
fadd 0 0 $= 0$
$0 \leq C$
$A \leq B$
shows *mult-matrix fmul fadd A C* $\leq$ *mult-matrix fmul fadd B C*
using *assms*
apply (*auto simp*: *le-matrix-def Rep-mult-matrix*)
apply (*simplesubst foldseq-zerotail*[*of - - - max* (*nrows C*) (*max* (*ncols A*) (*ncols B*))], *simp-all add*: *nrows ncols max1 max2*)+
apply (*rule le-foldseq*)
apply (*auto*)
done

lemma *spec2*: $\forall j\ i.\ P\ j\ i \Longrightarrow P\ j\ i$ **by** *blast*

lemma *singleton-matrix-le*[*simp*]: (*singleton-matrix j i a* $\leq$ *singleton-matrix j i b*)
= (*a* $\leq$ (*b*::-::*order*))
by (*auto simp*: *le-matrix-def*)

lemma *singleton-le-zero*[*simp*]: (*singleton-matrix j i x* $\leq$ *0*) = (*x* $\leq$ (*0*::'*a*::{*order*,*zero*}))
by (*metis singleton-matrix-le singleton-matrix-zero*)

lemma *singleton-ge-zero*[*simp*]: (*0* $\leq$ *singleton-matrix j i x*) = ((*0*::'*a*::{*order*,*zero*})
$\leq$ *x*)
by (*metis singleton-matrix-le singleton-matrix-zero*)

lemma *move-matrix-le-zero*[*simp*]:
fixes *A*:: '*a*::{*order*,*zero*} *matrix*
assumes *0* $\leq$ *j 0* $\leq$ *i*
shows (*move-matrix A j i* $\leq$ *0*) = (*A* $\leq$ *0*)
proof −
have *Rep-matrix A j' i'* $\leq$ *0*
if $\forall$ *n m*. ¬ *int n* < *j* $\wedge$ ¬ *int m* < *i* $\longrightarrow$ *Rep-matrix A* (*nat* (*int n* − *j*)) (*nat*
(*int m* − *i*)) $\leq$ *0*
for *j' i'*
using *that*[*rule-format*, *of j'* + *nat j i'* + *nat i*] **by** (*simp add*: *assms*)
then show *?thesis*
by (*auto simp*: *le-matrix-def*)
qed

lemma *move-matrix-zero-le*[*simp*]:
fixes *A*:: '*a*::{*order*,*zero*} *matrix*
assumes *0* $\leq$ *j 0* $\leq$ *i*
shows (*0* $\leq$ *move-matrix A j i*) = (*0* $\leq$ *A*)
proof −
have *0* $\leq$ *Rep-matrix A j' i'*
if $\forall$ *n m*. ¬ *int n* < *j* $\wedge$ ¬ *int m* < *i* $\longrightarrow$ *0* $\leq$ *Rep-matrix A* (*nat* (*int n* − *j*))
(*nat* (*int m* − *i*))
for *j' i'*
using *that*[*rule-format*, *of j'* + *nat j i'* + *nat i*] **by** (*simp add*: *assms*)
then show *?thesis*
by (*auto simp*: *le-matrix-def*)
qed

lemma *move-matrix-le-move-matrix-iff*[*simp*]:
fixes *A*:: '*a*::{*order*,*zero*} *matrix*
assumes *0* $\leq$ *j 0* $\leq$ *i*
shows (*move-matrix A j i* $\leq$ *move-matrix B j i*) = (*A* $\leq$ *B*)
proof −
have *Rep-matrix A j' i'* $\leq$ *Rep-matrix B j' i'*
if $\forall$ *n m*. ¬ *int n* < *j* $\wedge$ ¬ *int m* < *i* $\longrightarrow$ *Rep-matrix A* (*nat* (*int n* − *j*)) (*nat*

```
(int m − i)) ≤ Rep-matrix B (nat (int n − j)) (nat (int m − i))
    for j′ i′
    using that[rule-format, of j′ + nat j i′ + nat i] by (simp add: assms)
  then show ?thesis
    by (auto simp: le-matrix-def)
qed

instantiation matrix :: ({lattice, zero}) lattice
begin

definition inf = combine-matrix inf

definition sup = combine-matrix sup

instance
  by standard (auto simp: le-infI le-matrix-def inf-matrix-def sup-matrix-def)

end

instantiation matrix :: ({plus, zero}) plus
begin

definition
  plus-matrix-def: A + B = combine-matrix (+) A B

instance ..

end

instantiation matrix :: ({uminus, zero}) uminus
begin

definition
  minus-matrix-def: − A = apply-matrix uminus A

instance ..

end

instantiation matrix :: ({minus, zero}) minus
begin

definition
  diff-matrix-def: A − B = combine-matrix (−) A B

instance ..

end
```

instantiation *matrix* :: ({*plus*, *times*, *zero*}) *times*
begin

definition
times-matrix-def: $A * B = \mathit{mult\text{-}matrix}\ ((*))\ (+)\ A\ B$

instance ..

end

instantiation *matrix* :: ({*lattice*, *uminus*, *zero*}) *abs*
begin

definition
abs-matrix-def: $|A :: 'a\ \mathit{matrix}| = \mathit{sup}\ A\ (-\ A)$

instance ..

end

instance *matrix* :: (*monoid-add*) *monoid-add*
proof
fix $A\ B\ C :: 'a\ \mathit{matrix}$
show $A + B + C = A + (B + C)$
by (*simp add*: *add.assoc matrix-eqI plus-matrix-def*)
show $0 + A = A$
by (*simp add*: *matrix-eqI plus-matrix-def*)
show $A + 0 = A$
by (*simp add*: *matrix-eqI plus-matrix-def*)
qed

instance *matrix* :: (*comm-monoid-add*) *comm-monoid-add*
proof
fix $A\ B :: 'a\ \mathit{matrix}$
show $A + B = B + A$
by (*simp add*: *add.commute matrix-eqI plus-matrix-def*)
show $0 + A = A$
by (*simp add*: *plus-matrix-def matrix-eqI*)
qed

instance *matrix* :: (*group-add*) *group-add*
proof
fix $A\ B :: 'a\ \mathit{matrix}$
show $-\ A + A = 0$
by (*simp add*: *plus-matrix-def minus-matrix-def matrix-eqI*)
show $A + -\ B = A - B$
by (*simp add*: *plus-matrix-def diff-matrix-def minus-matrix-def matrix-eqI*)
qed

instance *matrix* :: (*ab-group-add*) *ab-group-add*
proof
fix *A B* :: *'a matrix*
show $-A + A = 0$
by (*simp add*: *plus-matrix-def minus-matrix-def matrix-eqI*)
show $A - B = A + - B$
by (*simp add*: *plus-matrix-def diff-matrix-def minus-matrix-def matrix-eqI*)
qed

instance *matrix* :: (*ordered-ab-group-add*) *ordered-ab-group-add*
proof
fix *A B C* :: *'a matrix*
assume $A \leq B$
then show $C + A \leq C + B$
by (*simp add*: *le-matrix-def plus-matrix-def*)
qed

instance *matrix* :: (*lattice-ab-group-add*) *semilattice-inf-ab-group-add* **..**
instance *matrix* :: (*lattice-ab-group-add*) *semilattice-sup-ab-group-add* **..**

instance *matrix* :: (*semiring-0*) *semiring-0*
proof
fix *A B C* :: *'a matrix*
show $A * B * C = A * (B * C)$
unfolding *times-matrix-def*
by (*smt* (*verit*, *best*) *add.assoc associative-def distrib-left distrib-right group-cancel.add2 mult.assoc mult-matrix-assoc mult-not-zero*)
show $(A + B) * C = A * C + B * C$
unfolding *times-matrix-def plus-matrix-def*
using *l-distributive-matrix*
by (*metis* (*full-types*) *add.assoc add.commute associative-def commutative-def distrib-right l-distributive-def mult-not-zero*)
show $A * (B + C) = A * B + A * C$
unfolding *times-matrix-def plus-matrix-def*
using *r-distributive-matrix*
by (*metis* (*no-types*, *lifting*) *add.assoc add.commute associative-def commutative-def distrib-left mult-zero-left mult-zero-right r-distributive-def*)
qed (*auto simp*: *times-matrix-def*)

instance *matrix* :: (*ring*) *ring* **..**

instance *matrix* :: (*ordered-ring*) *ordered-ring*
proof
fix *A B C* :: *'a matrix*
assume §: $A \leq B$ $0 \leq C$
from § **show** $C * A \leq C * B$
by (*simp add*: *times-matrix-def add-mono le-left-mult mult-left-mono*)
from § **show** $A * C \leq B * C$
by (*simp add*: *times-matrix-def add-mono le-right-mult mult-right-mono*)

qed

instance *matrix* :: (*lattice-ring*) *lattice-ring*
proof
fix *A B C* :: ('*a* :: *lattice-ring*) *matrix*
show |*A*| = *sup A* (−*A*)
by (*simp add*: *abs-matrix-def*)
qed

instance *matrix* :: (*lattice-ab-group-add-abs*) *lattice-ab-group-add-abs*
proof
show ⋀*a*:: '*a matrix*. |*a*| = *sup a* (− *a*)
by (*simp add*: *abs-matrix-def*)
qed

lemma *Rep-matrix-add*[*simp*]:
Rep-matrix ((*a*::('*a*::*monoid-add*)*matrix*)+*b*) *j i* = (*Rep-matrix a j i*) + (*Rep-matrix b j i*)
by (*simp add*: *plus-matrix-def*)

lemma *Rep-matrix-mult*: *Rep-matrix* ((*a*::('*a*::*semiring-0*) *matrix*) ∗ *b*) *j i* =
foldseq (+) (λ*k*. (*Rep-matrix a j k*) ∗ (*Rep-matrix b k i*)) (*max* (*ncols a*) (*nrows b*))
by (*simp add*: *times-matrix-def Rep-mult-matrix*)

lemma *apply-matrix-add*: ∀ *x y*. *f* (*x*+*y*) = (*f x*) + (*f y*) ⟹ *f* 0 = (0::'*a*)
⟹ *apply-matrix f* ((*a*::('*a*::*monoid-add*) *matrix*) + *b*) = (*apply-matrix f a*) + (*apply-matrix f b*)
by (*simp add*: *matrix-eqI*)

lemma *singleton-matrix-add*: *singleton-matrix j i* ((*a*::-::*monoid-add*)+*b*) = (*singleton-matrix j i a*) + (*singleton-matrix j i b*)
by (*simp add*: *matrix-eqI*)

lemma *nrows-mult*: *nrows* ((*A*::('*a*::*semiring-0*) *matrix*) ∗ *B*) ≤ *nrows A*
by (*simp add*: *times-matrix-def mult-nrows*)

lemma *ncols-mult*: *ncols* ((*A*::('*a*::*semiring-0*) *matrix*) ∗ *B*) ≤ *ncols B*
by (*simp add*: *times-matrix-def mult-ncols*)

definition
one-matrix :: *nat* ⇒ ('*a*::{*zero*,*one*}) *matrix* **where**
one-matrix n = *Abs-matrix* (λ*j i*. *if j* = *i* ∧ *j* < *n then 1 else 0*)

lemma *Rep-one-matrix*[*simp*]: *Rep-matrix* (*one-matrix n*) *j i* = (*if* (*j* = *i* ∧ *j* < *n*) *then 1 else 0*)
unfolding *one-matrix-def*
by (*smt* (*verit*, *del-insts*) *RepAbs-matrix not-le*)

lemma *nrows-one-matrix*[*simp*]: *nrows* ((*one-matrix n*) :: (*'a*::*zero-neq-one*)*matrix*)
= *n* (**is** *?r* = -)
proof −
have *?r* ≤ *n* **by** (*simp add*: *nrows-le*)
moreover have *n* ≤ *?r* **by** (*simp add*:*le-nrows*, *arith*)
ultimately show *?r* = *n* **by** *simp*
qed

lemma *ncols-one-matrix*[*simp*]: *ncols* ((*one-matrix n*) :: (*'a*::*zero-neq-one*)*matrix*)
= *n* (**is** *?r* = -)
proof −
have *?r* ≤ *n* **by** (*simp add*: *ncols-le*)
moreover have *n* ≤ *?r* **by** (*simp add*: *le-ncols*, *arith*)
ultimately show *?r* = *n* **by** *simp*
qed

lemma *one-matrix-mult-right*[*simp*]:
fixes *A* :: (*'a*::*semiring-1*) *matrix*
shows *ncols A* ≤ *n* ⟹ *A* ∗ (*one-matrix n*) = *A*
apply (*intro matrix-eqI*)
apply (*simp add*: *times-matrix-def Rep-mult-matrix*)
apply (*subst foldseq-almostzero*, *auto simp*: *ncols*)
done

lemma *one-matrix-mult-left*[*simp*]:
fixes *A* :: (*'a*::*semiring-1*) *matrix*
shows *nrows A* ≤ *n* ⟹ (*one-matrix n*) ∗ *A* = *A*
apply (*intro matrix-eqI*)
apply (*simp add*: *times-matrix-def Rep-mult-matrix*)
apply (*subst foldseq-almostzero*, *auto simp*: *nrows*)
done

lemma *transpose-matrix-mult*:
fixes *A* :: (*'a*::*comm-ring*) *matrix*
shows *transpose-matrix* (*A*∗*B*) = (*transpose-matrix B*) ∗ (*transpose-matrix A*)
by (*simp add*: *times-matrix-def transpose-mult-matrix mult.commute*)

lemma *transpose-matrix-add*:
fixes *A* :: (*'a*::*monoid-add*) *matrix*
shows *transpose-matrix* (*A*+*B*) = *transpose-matrix A* + *transpose-matrix B*
by (*simp add*: *plus-matrix-def transpose-combine-matrix*)

lemma *transpose-matrix-diff*:
fixes *A* :: (*'a*::*group-add*) *matrix*
shows *transpose-matrix* (*A*−*B*) = *transpose-matrix A* − *transpose-matrix B*
by (*simp add*: *diff-matrix-def transpose-combine-matrix*)

lemma *transpose-matrix-minus*:
fixes *A* :: (*'a*::*group-add*) *matrix*

shows *transpose-matrix* $(-A) = -$ *transpose-matrix* $(A::'a\ matrix)$
by (*simp add*: *minus-matrix-def transpose-apply-matrix*)

definition *right-inverse-matrix* :: $('a::\{ring\text{-}1\})$ *matrix* $\Rightarrow$ $'a$ *matrix* $\Rightarrow$ *bool* **where**
right-inverse-matrix A X == $(A * X =$ *one-matrix* $(max\ (nrows\ A)\ (ncols\ X)))$
$\wedge$ *nrows X* $\leq$ *ncols A*

definition *left-inverse-matrix* :: $('a::\{ring\text{-}1\})$ *matrix* $\Rightarrow$ $'a$ *matrix* $\Rightarrow$ *bool* **where**
left-inverse-matrix A X == $(X * A =$ *one-matrix* $(max(nrows\ X)\ (ncols\ A))) \wedge$
ncols X $\leq$ *nrows A*

definition *inverse-matrix* :: $('a::\{ring\text{-}1\})$ *matrix* $\Rightarrow$ $'a$ *matrix* $\Rightarrow$ *bool* **where**
inverse-matrix A X == (*right-inverse-matrix A X*) $\wedge$ (*left-inverse-matrix A X*)

lemma *right-inverse-matrix-dim*: *right-inverse-matrix A X* $\Longrightarrow$ *nrows A* = *ncols X*
using *ncols-mult*[*of A X*] *nrows-mult*[*of A X*]
by (*simp add*: *right-inverse-matrix-def*)

lemma *left-inverse-matrix-dim*: *left-inverse-matrix A Y* $\Longrightarrow$ *ncols A* = *nrows Y*
using *ncols-mult*[*of Y A*] *nrows-mult*[*of Y A*]
by (*simp add*: *left-inverse-matrix-def*)

lemma *left-right-inverse-matrix-unique*:
assumes *left-inverse-matrix A Y right-inverse-matrix A X*
shows *X* = *Y*
proof −
have *Y* = *Y* $*$ *one-matrix* (*nrows A*)
by (*metis assms*(*1*) *left-inverse-matrix-def one-matrix-mult-right*)
also have ... = *Y* $*$ (*A* $*$ *X*)
by (*metis assms*(*2*) *max.idem right-inverse-matrix-def right-inverse-matrix-dim*)

also have ... = (*Y* $*$ *A*) $*$ *X* **by** (*simp add*: *mult.assoc*)
also have ... = *X*
using *assms left-inverse-matrix-def right-inverse-matrix-def*
by (*metis left-inverse-matrix-dim max.idem one-matrix-mult-left*)
ultimately show *X* = *Y* **by** (*simp*)
qed

lemma *inverse-matrix-inject*: $[\![$ *inverse-matrix A X*; *inverse-matrix A Y* $]\!] \Longrightarrow$ *X* = *Y*
by (*auto simp*: *inverse-matrix-def left-right-inverse-matrix-unique*)

lemma *one-matrix-inverse*: *inverse-matrix* (*one-matrix n*) (*one-matrix n*)
by (*simp add*: *inverse-matrix-def left-inverse-matrix-def right-inverse-matrix-def*)

lemma *zero-imp-mult-zero*: $(a::'a::semiring\text{-}0) = 0 \mid b = 0 \Longrightarrow a * b = 0$
by *auto*

lemma *Rep-matrix-zero-imp-mult-zero*:
$\forall j\ i\ k.\ (Rep\text{-}matrix\ A\ j\ k = 0) \mid (Rep\text{-}matrix\ B\ k\ i) = 0 \implies A * B = (0::('a::lattice\text{-}ring)\ matrix)$
by (*simp add*: *matrix-eqI Rep-matrix-mult foldseq-zero zero-imp-mult-zero*)

lemma *add-nrows*: $nrows\ (A::('a::monoid\text{-}add)\ matrix) \leq u \implies nrows\ B \leq u \implies nrows\ (A + B) \leq u$
by (*simp add*: *nrows-le*)

lemma *move-matrix-row-mult*:
fixes $A :: ('a::semiring\text{-}0)\ matrix$
shows $move\text{-}matrix\ (A * B)\ j\ 0 = (move\text{-}matrix\ A\ j\ 0) * B$
proof −
have $\bigwedge m.\ \neg\ int\ m < j \implies ncols\ (move\text{-}matrix\ A\ j\ 0) \leq max\ (ncols\ A)\ (nrows\ B)$
by (*smt* (*verit*, *best*) *max1 nat-int ncols-move-matrix-le*)
then show *?thesis*
apply (*intro matrix-eqI*)
apply (*auto simp*: *Rep-matrix-mult foldseq-zero*)
apply (*rule-tac foldseq-zerotail*[*symmetric*])
apply (*auto simp*: *nrows zero-imp-mult-zero max2*)
done
qed

lemma *move-matrix-col-mult*:
fixes $A :: ('a::semiring\text{-}0)\ matrix$
shows $move\text{-}matrix\ (A * B)\ 0\ i = A * (move\text{-}matrix\ B\ 0\ i)$
proof −
have $\bigwedge n.\ \neg\ int\ n < i \implies nrows\ (move\text{-}matrix\ B\ 0\ i) \leq max\ (ncols\ A)\ (nrows\ B)$
by (*smt* (*verit*, *del-insts*) *max2 nat-int nrows-move-matrix-le*)
then show *?thesis*
apply (*intro matrix-eqI*)
apply (*auto simp*: *Rep-matrix-mult foldseq-zero*)
apply (*rule-tac foldseq-zerotail*[*symmetric*])
apply (*auto simp*: *ncols zero-imp-mult-zero max1*)
done
qed

lemma *move-matrix-add*: $((move\text{-}matrix\ (A + B)\ j\ i)::(('a::monoid\text{-}add)\ matrix)) = (move\text{-}matrix\ A\ j\ i) + (move\text{-}matrix\ B\ j\ i)$
by (*simp add*: *matrix-eqI*)

lemma *move-matrix-mult*: $move\text{-}matrix\ ((A::('a::semiring\text{-}0)\ matrix)*B)\ j\ i = (move\text{-}matrix\ A\ j\ 0) * (move\text{-}matrix\ B\ 0\ i)$
by (*simp add*: *move-matrix-ortho*[*of A*∗*B*] *move-matrix-col-mult move-matrix-row-mult*)

definition *scalar-mult* :: $('a::ring) \Rightarrow 'a\ matrix \Rightarrow 'a\ matrix$ **where**
$scalar\text{-}mult\ a\ m == apply\text{-}matrix\ ((*)\ a)\ m$

lemma *scalar-mult-zero*[*simp*]: *scalar-mult y 0 = 0*
by (*simp add*: *scalar-mult-def*)

lemma *scalar-mult-add*: *scalar-mult y* (*a*+*b*) = (*scalar-mult y a*) + (*scalar-mult y b*)
by (*simp add*: *scalar-mult-def apply-matrix-add algebra-simps*)

lemma *Rep-scalar-mult*[*simp*]: *Rep-matrix* (*scalar-mult y a*) *j i* = *y* ∗ (*Rep-matrix a j i*)
by (*simp add*: *scalar-mult-def*)

lemma *scalar-mult-singleton*[*simp*]: *scalar-mult y* (*singleton-matrix j i x*) = *singleton-matrix j i* (*y* ∗ *x*)
by (*simp add*: *scalar-mult-def*)

lemma *Rep-minus*[*simp*]: *Rep-matrix* (−(*A*::-::*group-add*)) *x y* = − (*Rep-matrix A x y*)
by (*simp add*: *minus-matrix-def*)

lemma *Rep-abs*[*simp*]: *Rep-matrix* |*A*::-::*lattice-ab-group-add*| *x y* = |*Rep-matrix A x y*|
by (*simp add*: *abs-lattice sup-matrix-def*)

end

theory *SparseMatrix*
imports *Matrix*
begin

type-synonym *'a spvec* = (*nat* ∗ *'a*) *list*
type-synonym *'a spmat* = *'a spvec spvec*

definition *sparse-row-vector* :: (*'a*::*ab-group-add*) *spvec* ⇒ *'a matrix*
where *sparse-row-vector arr* = *foldl* (% *m x*. *m* + (*singleton-matrix 0* (*fst x*) (*snd x*))) *0 arr*

definition *sparse-row-matrix* :: (*'a*::*ab-group-add*) *spmat* ⇒ *'a matrix*
where *sparse-row-matrix arr* = *foldl* (% *m r*. *m* + (*move-matrix* (*sparse-row-vector* (*snd r*)) (*int* (*fst r*)) *0*)) *0 arr*

code-datatype *sparse-row-vector sparse-row-matrix*

lemma *sparse-row-vector-empty* [*simp*]: *sparse-row-vector* [] = *0*
by (*simp add*: *sparse-row-vector-def*)

lemma *sparse-row-matrix-empty* [*simp*]: *sparse-row-matrix* [] = *0*
by (*simp add*: *sparse-row-matrix-def*)

lemma [*code*]:
‹*0* = *sparse-row-vector* []›
by *simp*

lemma *foldl-distrstart*: ∀ *a x y*. (*f* (*g x y*) *a* = *g x* (*f y a*)) ⟹ (*foldl f* (*g x y*) *l* = *g x* (*foldl f y l*))
by (*induct l arbitrary*: *x y*, *auto*)

lemma *sparse-row-vector-cons*[*simp*]:
sparse-row-vector (*a* # *arr*) = (*singleton-matrix 0* (*fst a*) (*snd a*)) + (*sparse-row-vector arr*)
by (*induct arr*) (*auto simp*: *foldl-distrstart sparse-row-vector-def*)

lemma *sparse-row-vector-append*[*simp*]:
sparse-row-vector (*a* @ *b*) = (*sparse-row-vector a*) + (*sparse-row-vector b*)
by (*induct a*) *auto*

lemma *nrows-spvec*[*simp*]: *nrows* (*sparse-row-vector x*) ≤ (*Suc 0*)
by (*induct x*) (*auto simp*: *add-nrows*)

lemma *sparse-row-matrix-cons*: *sparse-row-matrix* (*a*#*arr*) = ((*move-matrix* (*sparse-row-vector* (*snd a*)) (*int* (*fst a*)) *0*)) + *sparse-row-matrix arr*
by (*induct arr*) (*auto simp*: *foldl-distrstart sparse-row-matrix-def*)

lemma *sparse-row-matrix-append*: *sparse-row-matrix* (*arr*@*brr*) = (*sparse-row-matrix arr*) + (*sparse-row-matrix brr*)
by (*induct arr*) (*auto simp*: *sparse-row-matrix-cons*)

fun *sorted-spvec* :: *'a spvec* ⇒ *bool*
where
sorted-spvec [] = *True*
| *sorted-spvec-step1*: *sorted-spvec* [*a*] = *True*
| *sorted-spvec-step*: *sorted-spvec* ((*m*,*x*)#(*n*,*y*)#*bs*) = ((*m* < *n*) ∧ (*sorted-spvec* ((*n*,*y*)#*bs*)))

primrec *sorted-spmat* :: *'a spmat* ⇒ *bool*
where
sorted-spmat [] = *True*
| *sorted-spmat* (*a*#*as*) = ((*sorted-spvec* (*snd a*)) ∧ (*sorted-spmat as*))

declare *sorted-spvec.simps* [*simp del*]

lemma *sorted-spvec-empty*[*simp*]: *sorted-spvec* [] = *True*
by (*simp add*: *sorted-spvec.simps*)

lemma *sorted-spvec-cons1*: *sorted-spvec* (*a*#*as*) ⟹ *sorted-spvec as*
using *sorted-spvec.elims*(*2*) *sorted-spvec-empty* **by** *blast*

lemma *sorted-spvec-cons2*: *sorted-spvec* (*a*#*b*#*t*) ⟹ *sorted-spvec* (*a*#*t*)
by (*smt* (*verit*, *del-insts*) *sorted-spvec-step order.strict-trans list.inject sorted-spvec.elims*(*3*) *surj-pair*)

lemma *sorted-spvec-cons3*: *sorted-spvec*(*a*#*b*#*t*) ⟹ *fst a* < *fst b*
by (*metis sorted-spvec-step prod.collapse*)

lemma *sorted-sparse-row-vector-zero*:
assumes *m* ≤ *n*
shows *sorted-spvec* ((*n*,*a*)#*arr*) ⟹ *Rep-matrix* (*sparse-row-vector arr*) *j m* = *0*
proof (*induct arr*)
case *Nil*
then show *?case* **by** *auto*
next
case (*Cons a arr*)
with *assms* **show** *?case*
by (*auto dest*: *sorted-spvec-cons2 sorted-spvec-cons3*)
qed

lemma *sorted-sparse-row-matrix-zero*[*rule-format*]:
assumes *m* ≤ *n*
shows *sorted-spvec* ((*n*,*a*)#*arr*) ⟹ *Rep-matrix* (*sparse-row-matrix arr*) *m j* = *0*
proof (*induct arr*)
case *Nil*
then show *?case* **by** *auto*
next
case (*Cons a arr*)
with *assms* **show** *?case*
unfolding *sparse-row-matrix-cons*
by (*auto dest*: *sorted-spvec-cons2 sorted-spvec-cons3*)
qed

primrec *minus-spvec* :: ('*a*::*ab-group-add*) *spvec* ⇒ '*a spvec*
where
minus-spvec [] = []
| *minus-spvec* (*a*#*as*) = (*fst a*, −(*snd a*))#(*minus-spvec as*)

primrec *abs-spvec* :: ('*a*::*lattice-ab-group-add-abs*) *spvec* ⇒ '*a spvec*
where
abs-spvec [] = []
| *abs-spvec* (*a*#*as*) = (*fst a*, |*snd a*|)#(*abs-spvec as*)

lemma *sparse-row-vector-minus*:
sparse-row-vector (*minus-spvec v*) = − (*sparse-row-vector v*)
proof (*induct v*)
case *Nil*
then show *?case*

by *auto*
next
case (*Cons a v*)
then have *singleton-matrix 0* (*fst a*) (− *snd a*) = − *singleton-matrix 0* (*fst a*) (*snd a*)
by (*simp add*: *Rep-matrix-inject minus-matrix-def*)
then show *?case*
by (*simp add*: *local.Cons*)
qed

lemma *sparse-row-vector-abs*:
sorted-spvec (*v* :: *'a*::*lattice-ring spvec*) ⟹ *sparse-row-vector* (*abs-spvec v*) = |*sparse-row-vector v*|
proof (*induct v*)
case *Nil*
then show *?case*
by *simp*
next
case (*Cons ab v*)
then have *v*: *sorted-spvec v*
using *sorted-spvec-cons1* **by** *blast*
show *?case*
proof (*cases ab*)
case (*Pair a b*)
then have *0*: *Rep-matrix* (*sparse-row-vector v*) *0 a* = *0*
using *Cons.prems sorted-sparse-row-vector-zero* **by** *blast*
with *v Cons* **show** *?thesis*
by (*fastforce simp*: *Pair simp flip*: *Rep-matrix-inject*)
qed
qed

lemma *sorted-spvec-minus-spvec*:
sorted-spvec v ⟹ *sorted-spvec* (*minus-spvec v*)
by (*induct v rule*: *sorted-spvec.induct*) (*auto simp*: *sorted-spvec-step1 sorted-spvec-step*)

lemma *sorted-spvec-abs-spvec*:
sorted-spvec v ⟹ *sorted-spvec* (*abs-spvec v*)
by (*induct v rule*: *sorted-spvec.induct*) (*auto simp*: *sorted-spvec-step1 sorted-spvec-step*)

definition *smult-spvec y* = *map* (% *a*. (*fst a*, *y* ∗ *snd a*))

lemma *smult-spvec-empty*[*simp*]: *smult-spvec y* [] = []
by (*simp add*: *smult-spvec-def*)

lemma *smult-spvec-cons*: *smult-spvec y* (*a*#*arr*) = (*fst a*, *y* ∗ (*snd a*)) # (*smult-spvec y arr*)
by (*simp add*: *smult-spvec-def*)

fun *addmult-spvec* :: (*'a*::*ring*) ⇒ *'a spvec* ⇒ *'a spvec* ⇒ *'a spvec*

where
addmult-spvec y arr [] = arr
| *addmult-spvec y [] brr = smult-spvec y brr*
| *addmult-spvec y ((i,a)#arr) ((j,b)#brr) = (*
if i < j then ((i,a)#(addmult-spvec y arr ((j,b)#brr)))
*else (if (j < i) then ((j, y * b)#(addmult-spvec y ((i,a)#arr) brr))*
*else ((i, a + y*b)#(addmult-spvec y arr brr))))*

lemma *addmult-spvec-empty1*[*simp*]: *addmult-spvec y [] a = smult-spvec y a*
by (*induct a*) *auto*

lemma *addmult-spvec-empty2*[*simp*]: *addmult-spvec y a [] = a*
by *simp*

lemma *sparse-row-vector-map*: (∀ *x y*. *f* (*x*+*y*) = (*f x*) + (*f y*)) ⟹ (*f*::′*a*⇒(′*a*::*lattice-ring*))
0 = 0 ⟹
sparse-row-vector (*map* (% *x*. (*fst x*, *f* (*snd x*))) *a*) = *apply-matrix f* (*sparse-row-vector*
a)
by (*induct a*) (*simp-all add*: *apply-matrix-add*)

lemma *sparse-row-vector-smult*: *sparse-row-vector* (*smult-spvec y a*) = *scalar-mult*
y (*sparse-row-vector a*)
by (*induct a*) (*simp-all add*: *smult-spvec-cons scalar-mult-add*)

lemma *sparse-row-vector-addmult-spvec*: *sparse-row-vector* (*addmult-spvec* (*y*::′*a*::*lattice-ring*)
a b) =
(*sparse-row-vector a*) + (*scalar-mult y* (*sparse-row-vector b*))
by (*induct y a b rule*: *addmult-spvec.induct*)
(*simp-all add*: *scalar-mult-add smult-spvec-cons sparse-row-vector-smult single-*
ton-matrix-add)

lemma *sorted-smult-spvec*: *sorted-spvec a* ⟹ *sorted-spvec* (*smult-spvec y a*)
by (*induct a rule*: *sorted-spvec.induct*) (*auto simp*: *smult-spvec-def sorted-spvec-step1*
sorted-spvec-step)

lemma *sorted-spvec-addmult-spvec-helper*: ⟦*sorted-spvec* (*addmult-spvec y* ((*a*, *b*)
arr) *brr*); *aa* < *a*; *sorted-spvec* ((*a*, *b*) # *arr*);
sorted-spvec ((*aa*, *ba*) # *brr*)⟧ ⟹ *sorted-spvec* ((*aa*, *y* ∗ *ba*) # *addmult-spvec y*
((*a*, *b*) # *arr*) *brr*)
by (*induct brr*) (*auto simp*: *sorted-spvec.simps*)

lemma *sorted-spvec-addmult-spvec-helper2*:
⟦*sorted-spvec* (*addmult-spvec y arr* ((*aa*, *ba*) # *brr*)); *a* < *aa*; *sorted-spvec* ((*a*, *b*)
arr); *sorted-spvec* ((*aa*, *ba*) # *brr*)⟧
⟹ *sorted-spvec* ((*a*, *b*) # *addmult-spvec y arr* ((*aa*, *ba*) # *brr*))
by (*induct arr*) (*auto simp*: *smult-spvec-def sorted-spvec.simps*)

lemma *sorted-spvec-addmult-spvec-helper3*[*rule-format*]:

```
  sorted-spvec (addmult-spvec y arr brr) ⟹
   sorted-spvec ((aa, b) # arr) ⟹
  sorted-spvec ((aa, ba) # brr) ⟹
   sorted-spvec ((aa, b + y * ba) # (addmult-spvec y arr brr))
 by (smt (verit, ccfv-threshold) sorted-spvec-step addmult-spvec.simps(1) list.distinct(1)
list.sel(3) sorted-spvec.elims(1) sorted-spvec-addmult-spvec-helper2)

lemma sorted-addmult-spvec: sorted-spvec a ⟹ sorted-spvec b ⟹ sorted-spvec
(addmult-spvec y a b)
proof (induct y a b rule: addmult-spvec.induct)
  case (1 y arr)
  then show ?case
    by simp
next
  case (2 y v va)
  then show ?case
    by (simp add: sorted-smult-spvec)
next
  case (3 y i a arr j b brr)
  show ?case
  proof (cases i j rule: linorder-cases)
    case less
    with 3 show ?thesis
      by (simp add: sorted-spvec-addmult-spvec-helper2 sorted-spvec-cons1)
  next
    case equal
    with 3 show ?thesis
      by (simp add: sorted-spvec-addmult-spvec-helper3 sorted-spvec-cons1)
  next
    case greater
    with 3 show ?thesis
      by (simp add: sorted-spvec-addmult-spvec-helper sorted-spvec-cons1)
  qed
qed

fun mult-spvec-spmat :: ('a::lattice-ring) spvec ⇒ 'a spvec ⇒ 'a spmat ⇒ 'a spvec
where
  mult-spvec-spmat c [] brr = c
| mult-spvec-spmat c arr [] = c
| mult-spvec-spmat c ((i,a)#arr) ((j,b)#brr) = (
    if (i < j) then mult-spvec-spmat c arr ((j,b)#brr)
    else if (j < i) then mult-spvec-spmat c ((i,a)#arr) brr
    else mult-spvec-spmat (addmult-spvec a c b) arr brr)

lemma sparse-row-mult-spvec-spmat:
  assumes sorted-spvec (a::('a::lattice-ring) spvec) sorted-spvec B
   shows sparse-row-vector (mult-spvec-spmat c a B) = (sparse-row-vector c) +
(sparse-row-vector a) * (sparse-row-matrix B)
proof −
```

```
  have comp-1: !! a b. a < b ⟹ Suc 0 ≤ nat ((int b)−(int a)) by arith
  have not-iff: !! a b. a = b ⟹ (~ a) = (~ b) by simp
  {
    fix a
    fix v :: (nat × 'a) list
    assume a: a < nrows(sparse-row-vector v)
    have nrows(sparse-row-vector v) ≤ 1 by simp
    then have a = 0
      using a dual-order.strict-trans1 by blast
  }
  note nrows-helper = this
  show ?thesis
    using assms
  proof (induct c a B rule: mult-spvec-spmat.induct)
    case (1 c brr)
    then show ?case
      by simp
  next
    case (2 c v va)
    then show ?case
      by simp
  next
    case (3 c i a arr j b brr)
    then have abrr: sorted-spvec arr sorted-spvec brr
      using sorted-spvec-cons1 by blast+
    have ⋀m n. ⟦a ≠ 0; 0 < m⟧
          ⟹ a * Rep-matrix (sparse-row-vector b) m n = 0
      by (metis mult-zero-right neq0-conv nrows-helper nrows-notzero)
    then have †: scalar-mult a (sparse-row-vector b) =
           singleton-matrix 0 j a * move-matrix (sparse-row-vector b) (int j) 0
      apply (intro matrix-eqI)
      apply (simp)
      apply (subst Rep-matrix-mult)
      apply (subst foldseq-almostzero, auto)
      done
    show ?case
    proof (cases i j rule: linorder-cases)
      case less
      with 3 abrr † show ?thesis
     apply (simp add: algebra-simps sparse-row-matrix-cons Rep-matrix-zero-imp-mult-zero)
      by (metis Rep-matrix-zero-imp-mult-zero Rep-singleton-matrix less-imp-le-nat
sorted-sparse-row-matrix-zero)
    next
      case equal
      with 3 abrr † show ?thesis
     apply (simp add: sparse-row-matrix-cons algebra-simps sparse-row-vector-addmult-spvec)
       apply (subst Rep-matrix-zero-imp-mult-zero)
       using sorted-sparse-row-matrix-zero apply fastforce
       apply (subst Rep-matrix-zero-imp-mult-zero)
```

```
      apply (metis Rep-move-matrix comp-1 nrows-le nrows-spvec sorted-sparse-row-vector-zero
alethe-comp-simplify1(3))
       apply simp
       done
    next
      case greater
      have Rep-matrix (sparse-row-vector arr) j' k = 0 ∨
          Rep-matrix (move-matrix (sparse-row-vector b) (int j) 0) k
           i' = 0
       if sorted-spvec ((i, a) # arr) for j' i' k
      proof (cases k ≤ j)
       case True
       with greater that show ?thesis
         by (meson order.trans nat-less-le sorted-sparse-row-vector-zero)
      qed (use nrows-helper nrows-notzero in force)
      then have sparse-row-vector arr ∗ move-matrix (sparse-row-vector b) (int j)
0 = 0
       using greater 3
       by (simp add: Rep-matrix-zero-imp-mult-zero)
      with greater 3 abrr show ?thesis
       apply (simp add: algebra-simps sparse-row-matrix-cons)
      by (metis Rep-matrix-zero-imp-mult-zero Rep-move-matrix Rep-singleton-matrix
comp-1 nrows-le nrows-spvec)
    qed
  qed
qed

lemma sorted-mult-spvec-spmat:
  sorted-spvec (c::('a::lattice-ring) spvec) ⟹ sorted-spmat B ⟹ sorted-spvec (mult-spvec-spmat
c a B)
  by (induct c a B rule: mult-spvec-spmat.induct) (simp-all add: sorted-addmult-spvec)

primrec mult-spmat :: ('a::lattice-ring) spmat ⇒ 'a spmat ⇒ 'a spmat
where
  mult-spmat [] A = []
| mult-spmat (a#as) A = (fst a, mult-spvec-spmat [] (snd a) A)#(mult-spmat as
A)

lemma sparse-row-mult-spmat:
  sorted-spmat A ⟹ sorted-spvec B ⟹
  sparse-row-matrix (mult-spmat A B) = (sparse-row-matrix A) ∗ (sparse-row-matrix
B)
  by (induct A) (auto simp: sparse-row-matrix-cons sparse-row-mult-spvec-spmat
algebra-simps move-matrix-mult)

lemma sorted-spvec-mult-spmat:
  fixes A :: ('a::lattice-ring) spmat
  shows sorted-spvec A ⟹ sorted-spvec (mult-spmat A B)
by (induct A rule: sorted-spvec.induct) (auto simp: sorted-spvec.simps)
```

lemma *sorted-spmat-mult-spmat*:
sorted-spmat (*B*::('*a*::*lattice-ring*) *spmat*) ⟹ *sorted-spmat* (*mult-spmat A B*)
by (*induct A*) (*auto simp*: *sorted-mult-spvec-spmat*)

fun *add-spvec* :: ('*a*::*lattice-ab-group-add*) *spvec* ⇒ '*a spvec* ⇒ '*a spvec*
where

add-spvec arr [] = *arr*
| *add-spvec* [] *brr* = *brr*
| *add-spvec* ((*i*,*a*)#*arr*) ((*j*,*b*)#*brr*) = (
if i < *j then* (*i*,*a*)#(*add-spvec arr* ((*j*,*b*)#*brr*))
else if (*j* < *i*) *then* (*j*,*b*) # *add-spvec* ((*i*,*a*)#*arr*) *brr*
else (*i*, *a*+*b*) # *add-spvec arr brr*)

lemma *add-spvec-empty1*[*simp*]: *add-spvec* [] *a* = *a*
by (*cases a*, *auto*)

lemma *sparse-row-vector-add*: *sparse-row-vector* (*add-spvec a b*) = (*sparse-row-vector a*) + (*sparse-row-vector b*)
by (*induct a b rule*: *add-spvec.induct*) (*simp-all add*: *singleton-matrix-add*)

fun *add-spmat* :: ('*a*::*lattice-ab-group-add*) *spmat* ⇒ '*a spmat* ⇒ '*a spmat*
where

add-spmat [] *bs* = *bs*
| *add-spmat as* [] = *as*
| *add-spmat* ((*i*,*a*)#*as*) ((*j*,*b*)#*bs*) = (
if i < *j then*
(*i*,*a*) # *add-spmat as* ((*j*,*b*)#*bs*)
else if j < *i then*
(*j*,*b*) # *add-spmat* ((*i*,*a*)#*as*) *bs*
else
(*i*, *add-spvec a b*) # *add-spmat as bs*)

lemma *add-spmat-Nil2*[*simp*]: *add-spmat as* [] = *as*
by(*cases as*) *auto*

lemma *sparse-row-add-spmat*: *sparse-row-matrix* (*add-spmat A B*) = (*sparse-row-matrix A*) + (*sparse-row-matrix B*)
by (*induct A B rule*: *add-spmat.induct*) (*auto simp*: *sparse-row-matrix-cons sparse-row-vector-add move-matrix-add*)

lemma [*code*]:
‹*sparse-row-matrix A* + *sparse-row-matrix B* = *sparse-row-matrix* (*add-spmat A B*)›
‹*sparse-row-vector a* + *sparse-row-vector b* = *sparse-row-vector* (*add-spvec a b*)›
by (*simp-all add*: *sparse-row-add-spmat sparse-row-vector-add*)

lemma *sorted-add-spvec-helper1*[*rule-format*]: *add-spvec* ((*a*,*b*)#*arr*) *brr* = (*ab*, *bb*) # *list* ⟶ (*ab* = *a* | (*brr* ≠ [] & *ab* = *fst* (*hd brr*)))
proof −
have (∀ *x ab a*. *x* = (*a*,*b*)#*arr* ⟶ *add-spvec x brr* = (*ab*, *bb*) # *list* ⟶ (*ab* = *a* | (*ab* = *fst* (*hd brr*))))
by (*induct brr rule*: *add-spvec.induct*) (*auto split*:*if-splits*)
then show *?thesis*
by (*case-tac brr*, *auto*)
qed

lemma *sorted-add-spmat-helper1*[*rule-format*]:
add-spmat ((*a*,*b*)#*arr*) *brr* = (*ab*, *bb*) # *list* ⟹ (*ab* = *a* | (*brr* ≠ [] & *ab* = *fst* (*hd brr*)))
by (*smt* (*verit*) *add-spmat.elims fst-conv list.distinct*(*1*) *list.sel*(*1*))

lemma *sorted-add-spvec-helper*: *add-spvec arr brr* = (*ab*, *bb*) # *list* ⟹ ((*arr* ≠ [] & *ab* = *fst* (*hd arr*)) | (*brr* ≠ [] & *ab* = *fst* (*hd brr*)))
by (*induct arr brr rule*: *add-spvec.induct*) (*auto split*:*if-splits*)

lemma *sorted-add-spmat-helper*: *add-spmat arr brr* = (*ab*, *bb*) # *list* ⟹ ((*arr* ≠ [] & *ab* = *fst* (*hd arr*)) | (*brr* ≠ [] & *ab* = *fst* (*hd brr*)))
by (*induct arr brr rule*: *add-spmat.induct*) (*auto split*:*if-splits*)

lemma *add-spvec-commute*: *add-spvec a b* = *add-spvec b a*
by (*induct a b rule*: *add-spvec.induct*) *auto*

lemma *add-spmat-commute*: *add-spmat a b* = *add-spmat b a*
by (*induct a b rule*: *add-spmat.induct*) (*simp-all add*: *add-spvec-commute*)

lemma *sorted-add-spvec-helper2*: *add-spvec* ((*a*,*b*)#*arr*) *brr* = (*ab*, *bb*) # *list* ⟹ *aa* < *a* ⟹ *sorted-spvec* ((*aa*, *ba*) # *brr*) ⟹ *aa* < *ab*
by (*smt* (*verit*, *best*) *add-spvec.elims fst-conv list.sel*(*1*) *sorted-spvec-cons3*)

lemma *sorted-add-spmat-helper2*: *add-spmat* ((*a*,*b*)#*arr*) *brr* = (*ab*, *bb*) # *list* ⟹ *aa* < *a* ⟹ *sorted-spvec* ((*aa*, *ba*) # *brr*) ⟹ *aa* < *ab*
by (*metis* (*no-types*, *opaque-lifting*) *add-spmat.simps*(*1*) *list.sel*(*1*) *neq-Nil-conv sorted-add-spmat-helper sorted-spvec-cons3*)

lemma *sorted-spvec-add-spvec*: *sorted-spvec a* ⟹ *sorted-spvec b* ⟹ *sorted-spvec* (*add-spvec a b*)
proof (*induct a b rule*: *add-spvec.induct*)
case (*3 i a arr j b brr*)
then have *sorted-spvec arr sorted-spvec brr*
using *sorted-spvec-cons1* **by** *blast*+
with *3* **show** *?case*
apply *simp*
by (*smt* (*verit*, *ccfv-SIG*) *add-spvec.simps*(*2*) *list.sel*(*3*) *sorted-add-spvec-helper sorted-spvec.elims*(*1*))

qed *auto*

lemma *sorted-spvec-add-spmat*:
sorted-spvec A $\Longrightarrow$ *sorted-spvec B* $\Longrightarrow$ *sorted-spvec* (*add-spmat A B*)
proof (*induct A B rule*: *add-spmat.induct*)
case (*1 bs*)
then show *?case* **by** *auto*
next
case (*2 v va*)
then show *?case* **by** *auto*
next
case (*3 i a as j b bs*)
then have *sorted-spvec as sorted-spvec bs*
using *sorted-spvec-cons1* **by** *blast+*
with *3* **show** *?case*
apply *simp*
by (*smt* (*verit*) *Pair-inject add-spmat.elims list.discI list.inject sorted-spvec.elims*(*1*))
qed

lemma *sorted-spmat-add-spmat*[*rule-format*]: *sorted-spmat A* $\Longrightarrow$ *sorted-spmat B*
$\Longrightarrow$ *sorted-spmat* (*add-spmat A B*)
by (*induct A B rule*: *add-spmat.induct*) (*simp-all add*: *sorted-spvec-add-spvec*)

fun *le-spvec* :: ('*a*::*lattice-ab-group-add*) *spvec* $\Rightarrow$ '*a spvec* $\Rightarrow$ *bool*
where

le-spvec [] [] = *True*
| *le-spvec* ((-,*a*)#*as*) [] = (*a* $\leq$ *0* & *le-spvec as* [])
| *le-spvec* [] ((-,*b*)#*bs*) = (*0* $\leq$ *b* & *le-spvec* [] *bs*)
| *le-spvec* ((*i*,*a*)#*as*) ((*j*,*b*)#*bs*) = (
if (*i* < *j*) *then a* $\leq$ *0* & *le-spvec as* ((*j*,*b*)#*bs*)
else if (*j* < *i*) *then 0* $\leq$ *b* & *le-spvec* ((*i*,*a*)#*as*) *bs*
else a $\leq$ *b* & *le-spvec as bs*)

fun *le-spmat* :: ('*a*::*lattice-ab-group-add*) *spmat* $\Rightarrow$ '*a spmat* $\Rightarrow$ *bool*
where

le-spmat [] [] = *True*
| *le-spmat* ((*i*,*a*)#*as*) [] = (*le-spvec a* [] & *le-spmat as* [])
| *le-spmat* [] ((*j*,*b*)#*bs*) = (*le-spvec* [] *b* & *le-spmat* [] *bs*)
| *le-spmat* ((*i*,*a*)#*as*) ((*j*,*b*)#*bs*) = (
if i < *j then* (*le-spvec a* [] & *le-spmat as* ((*j*,*b*)#*bs*))
else if j < *i then* (*le-spvec* [] *b* & *le-spmat* ((*i*,*a*)#*as*) *bs*)
else (*le-spvec a b* & *le-spmat as bs*))

definition *disj-matrices* :: ('*a*::*zero*) *matrix* $\Rightarrow$ '*a matrix* $\Rightarrow$ *bool* **where**
disj-matrices A B $\longleftrightarrow$
(∀ *j i*. (*Rep-matrix A j i* $\neq$ *0*) $\longrightarrow$ (*Rep-matrix B j i* = *0*)) & (∀ *j i*. (*Rep-matrix*
B j i $\neq$ *0*) $\longrightarrow$ (*Rep-matrix A j i* = *0*))

lemma *disj-matrices-contr1*: *disj-matrices A B* $\Longrightarrow$ *Rep-matrix A j i* $\neq$ *0* $\Longrightarrow$ *Rep-matrix B j i = 0*
by (*simp add*: *disj-matrices-def*)

lemma *disj-matrices-contr2*: *disj-matrices A B* $\Longrightarrow$ *Rep-matrix B j i* $\neq$ *0* $\Longrightarrow$ *Rep-matrix A j i = 0*
by (*simp add*: *disj-matrices-def*)

lemma *disj-matrices-add*:
fixes *A* :: ('*a*::*lattice-ab-group-add*) *matrix*
shows *disj-matrices A B* $\Longrightarrow$ *disj-matrices C D* $\Longrightarrow$ *disj-matrices A D* $\Longrightarrow$ *disj-matrices B C* $\Longrightarrow$ (*A* + *B* $\leq$ *C* + *D*) = (*A* $\leq$ *C* $\wedge$ *B* $\leq$ *D*)
apply (*intro iffI conjI*)
unfolding *le-matrix-def disj-matrices-def*
apply (*metis Rep-matrix-add group-cancel.rule0 order-refl*)
apply (*metis* (*no-types*, *lifting*) *Rep-matrix-add add-cancel-right-left dual-order.refl*)
by (*meson add-mono le-matrix-def*)

lemma *disj-matrices-zero1*[*simp*]: *disj-matrices 0 B*
by (*simp add*: *disj-matrices-def*)

lemma *disj-matrices-zero2*[*simp*]: *disj-matrices A 0*
by (*simp add*: *disj-matrices-def*)

lemma *disj-matrices-commute*: *disj-matrices A B = disj-matrices B A*
by (*auto simp*: *disj-matrices-def*)

lemma *disj-matrices-add-le-zero*: *disj-matrices A B* $\Longrightarrow$
(*A* + *B* $\leq$ *0*) = (*A* $\leq$ *0* & (*B*::('*a*::*lattice-ab-group-add*) *matrix*) $\leq$ *0*)
by (*rule disj-matrices-add*[*of A B 0 0*, *simplified*])

lemma *disj-matrices-add-zero-le*: *disj-matrices A B* $\Longrightarrow$
(*0* $\leq$ *A* + *B*) = (*0* $\leq$ *A* & *0* $\leq$ (*B*::('*a*::*lattice-ab-group-add*) *matrix*))
by (*rule disj-matrices-add*[*of 0 0 A B*, *simplified*])

lemma *disj-matrices-add-x-le*: *disj-matrices A B* $\Longrightarrow$ *disj-matrices B C* $\Longrightarrow$
(*A* $\leq$ *B* + *C*) = (*A* $\leq$ *C* & *0* $\leq$ (*B*::('*a*::*lattice-ab-group-add*) *matrix*))
by (*auto simp*: *disj-matrices-add*[*of 0 A B C*, *simplified*])

lemma *disj-matrices-add-le-x*: *disj-matrices A B* $\Longrightarrow$ *disj-matrices B C* $\Longrightarrow$
(*B* + *A* $\leq$ *C*) = (*A* $\leq$ *C* & (*B*::('*a*::*lattice-ab-group-add*) *matrix*) $\leq$ *0*)
by (*auto simp*: *disj-matrices-add*[*of B A 0 C*,*simplified*] *disj-matrices-commute*)

lemma *disj-sparse-row-singleton*: *i* $\leq$ *j* $\Longrightarrow$ *sorted-spvec*((*j*,*y*)#*v*) $\Longrightarrow$ *disj-matrices* (*sparse-row-vector v*) (*singleton-matrix 0 i x*)
apply (*simp add*: *disj-matrices-def*)
using *sorted-sparse-row-vector-zero* **by** *blast*

lemma *disj-matrices-x-add*: *disj-matrices A B* $\Longrightarrow$ *disj-matrices A C* $\Longrightarrow$ *disj-matrices* (*A*::(*'a*::*lattice-ab-group-add*) *matrix*) (*B*+*C*)
by (*smt* (*verit*, *ccfv-SIG*) *Rep-matrix-add add-0 disj-matrices-def*)

lemma *disj-matrices-add-x*: *disj-matrices A B* $\Longrightarrow$ *disj-matrices A C* $\Longrightarrow$ *disj-matrices* (*B*+*C*) (*A*::(*'a*::*lattice-ab-group-add*) *matrix*)
by (*simp add*: *disj-matrices-x-add disj-matrices-commute*)

lemma *disj-singleton-matrices*[*simp*]: *disj-matrices* (*singleton-matrix j i x*) (*singleton-matrix u v y*) = (*j* $\neq$ *u* | *i* $\neq$ *v* | *x* = *0* | *y* = *0*)
by (*auto simp*: *disj-matrices-def*)

lemma *disj-move-sparse-vec-mat*:
assumes *j* $\leq$ *a* **and** *sorted-spvec* ((*a*, *c*) # *as*)
shows *disj-matrices* (*sparse-row-matrix as*) (*move-matrix* (*sparse-row-vector b*) (*int j*) *i*)
proof −
have *Rep-matrix* (*sparse-row-vector b*) (*n*−*j*) (*nat* (*int m* − *i*)) = *0*
if ¬ *n*<*j* **and** *nz*: *Rep-matrix* (*sparse-row-matrix as*) *n m* $\neq$ *0*
for *n m*
proof −
have *n* $\neq$ *j*
using *assms sorted-sparse-row-matrix-zero nz* **by** *blast*
with *that* **have** *j* < *n* **by** *auto*
then show *?thesis*
by (*metis One-nat-def Suc-diff-Suc nrows nrows-spvec plus-1-eq-Suc trans-le-add1*)
qed
then show *?thesis*
by (*auto simp*: *disj-matrices-def nat-minus-as-int*)
qed

lemma *disj-move-sparse-row-vector-twice*:
j $\neq$ *u* $\Longrightarrow$ *disj-matrices* (*move-matrix* (*sparse-row-vector a*) *j i*) (*move-matrix* (*sparse-row-vector b*) *u v*)
unfolding *disj-matrices-def*
by (*smt* (*verit*, *ccfv-SIG*) *One-nat-def Rep-move-matrix of-nat-1 le-nat-iff nrows nrows-spvec of-nat-le-iff*)

lemma *le-spvec-iff-sparse-row-le*:
sorted-spvec a $\Longrightarrow$ *sorted-spvec b* $\Longrightarrow$ (*le-spvec a b*) $\longleftrightarrow$ (*sparse-row-vector a* $\leq$ *sparse-row-vector b*)
proof (*induct a b rule*: *le-spvec.induct*)
case *1*
then show *?case*
by *auto*
next
case (*2 uu a as*)
then have *sorted-spvec as*

```
    by (metis sorted-spvec-cons1)
  with 2 show ?case
    apply (simp add: add.commute)
   by (metis disj-matrices-add-le-zero disj-sparse-row-singleton le-refl singleton-le-zero)
next
  case (3 uv b bs)
  then have sorted-spvec bs
    by (metis sorted-spvec-cons1)
  with 3 show ?case
    apply (simp add: add.commute)
   by (metis disj-matrices-add-zero-le disj-sparse-row-singleton le-refl singleton-ge-zero)
next
  case (4 i a as j b bs)
  then obtain §: sorted-spvec as sorted-spvec bs
    by (metis sorted-spvec-cons1)
  show ?case
  proof (cases i j rule: linorder-cases)
    case less
    with 4 § show ?thesis
      apply (simp add: )
       by (metis disj-matrices-add-le-x disj-matrices-add-x disj-matrices-commute
disj-singleton-matrices disj-sparse-row-singleton less-imp-le-nat singleton-le-zero not-le)
  next
    case equal
    with 4 § show ?thesis
      apply (simp add: )
       by (metis disj-matrices-add disj-matrices-commute disj-sparse-row-singleton
order-refl singleton-matrix-le)
  next
    case greater
    with 4 § show ?thesis
      apply (simp add: )
       by (metis disj-matrices-add-x disj-matrices-add-x-le disj-matrices-commute
disj-singleton-matrices disj-sparse-row-singleton le-refl order-less-le singleton-ge-zero)
  qed
qed

lemma le-spvec-empty2-sparse-row:
  sorted-spvec b ⟹ le-spvec b [] = (sparse-row-vector b ≤ 0)
  by (simp add: le-spvec-iff-sparse-row-le)

lemma le-spvec-empty1-sparse-row:
  (sorted-spvec b) ⟹ (le-spvec [] b = (0 ≤ sparse-row-vector b))
  by (simp add: le-spvec-iff-sparse-row-le)

lemma le-spmat-iff-sparse-row-le:
  ⟦sorted-spvec A; sorted-spmat A; sorted-spvec B; sorted-spmat B⟧ ⟹
  le-spmat A B = (sparse-row-matrix A ≤ sparse-row-matrix B)
proof (induct A B rule: le-spmat.induct)
```

```
  case (4 i a as j b bs)
  then obtain §: sorted-spvec as sorted-spvec bs
    by (metis sorted-spvec-cons1)
  show ?case
  proof (cases i j rule: linorder-cases)
    case less
    with 4 § show ?thesis
      apply (simp add: sparse-row-matrix-cons le-spvec-empty2-sparse-row)
        by (metis disj-matrices-add-le-x disj-matrices-add-x disj-matrices-commute
disj-move-sparse-row-vector-twice disj-move-sparse-vec-mat int-eq-iff less-not-refl move-matrix-le-zero
order-le-less)
  next
    case equal
    with 4 § show ?thesis
     by (simp add: sparse-row-matrix-cons le-spvec-iff-sparse-row-le disj-matrices-commute
disj-move-sparse-vec-mat[OF order-refl] disj-matrices-add)
  next
    case greater
    with 4 § show ?thesis
      apply (simp add: sparse-row-matrix-cons le-spvec-empty1-sparse-row)
        by (metis disj-matrices-add-x disj-matrices-add-x-le disj-matrices-commute
disj-move-sparse-row-vector-twice disj-move-sparse-vec-mat move-matrix-zero-le nat-int
nat-less-le of-nat-0-le-iff order-refl)
  qed
qed (auto simp add: sparse-row-matrix-cons disj-matrices-add-le-zero disj-matrices-add-zero-le
disj-move-sparse-vec-mat[OF order-refl]
   disj-matrices-commute sorted-spvec-cons1 le-spvec-empty2-sparse-row le-spvec-empty1-sparse-row)


primrec abs-spmat :: ('a::lattice-ring) spmat ⇒ 'a spmat
where
  abs-spmat [] = []
| abs-spmat (a#as) = (fst a, abs-spvec (snd a))#(abs-spmat as)

primrec minus-spmat :: ('a::lattice-ring) spmat ⇒ 'a spmat
where
  minus-spmat [] = []
| minus-spmat (a#as) = (fst a, minus-spvec (snd a))#(minus-spmat as)

lemma sparse-row-matrix-minus:
  sparse-row-matrix (minus-spmat A) = − (sparse-row-matrix A)
proof (induct A)
  case Nil
  then show ?case by auto
next
  case (Cons a A)
  then show ?case
    by (simp add: sparse-row-vector-minus sparse-row-matrix-cons matrix-eqI)
qed
```

lemma *Rep-sparse-row-vector-zero*:
assumes $x \neq 0$
shows *Rep-matrix* (*sparse-row-vector v*) *x y* = *0*
by (*metis Suc-leI assms le0 le-eq-less-or-eq nrows-le nrows-spvec*)

lemma *sparse-row-matrix-abs*:
sorted-spvec A ⟹ *sorted-spmat A* ⟹ *sparse-row-matrix* (*abs-spmat A*) = |*sparse-row-matrix A*|
proof (*induct A*)
case *Nil*
then show *?case* **by** *auto*
next
case (*Cons ab A*)
then have *A*: *sorted-spvec A*
using *sorted-spvec-cons1* **by** *blast*
show *?case*
proof (*cases ab*)
case (*Pair a b*)
show *?thesis*
unfolding *Pair*
proof (*intro matrix-eqI*)
fix *m n*
show *Rep-matrix* (*sparse-row-matrix* (*abs-spmat* ((*a*,*b*) # *A*))) *m n*
= *Rep-matrix* |*sparse-row-matrix* ((*a*,*b*) # *A*)| *m n*
using *Cons Pair A*
apply (*simp add*: *sparse-row-vector-abs sparse-row-matrix-cons*)
apply (*cases m*=*a*)
using *sorted-sparse-row-matrix-zero* **apply** *fastforce*
by (*simp add*: *Rep-sparse-row-vector-zero*)
qed
qed
qed

lemma *sorted-spvec-minus-spmat*: *sorted-spvec A* ⟹ *sorted-spvec* (*minus-spmat A*)
by (*induct A rule*: *sorted-spvec.induct*) (*auto simp*: *sorted-spvec.simps*)

lemma *sorted-spvec-abs-spmat*: *sorted-spvec A* ⟹ *sorted-spvec* (*abs-spmat A*)
by (*induct A rule*: *sorted-spvec.induct*) (*auto simp*: *sorted-spvec.simps*)

lemma *sorted-spmat-minus-spmat*: *sorted-spmat A* ⟹ *sorted-spmat* (*minus-spmat A*)
by (*induct A*) (*simp-all add*: *sorted-spvec-minus-spvec*)

lemma *sorted-spmat-abs-spmat*: *sorted-spmat A* ⟹ *sorted-spmat* (*abs-spmat A*)
by (*induct A*) (*simp-all add*: *sorted-spvec-abs-spvec*)

definition *diff-spmat* :: ('*a*::*lattice-ring*) *spmat* ⇒ '*a spmat* ⇒ '*a spmat*

where *diff-spmat A B = add-spmat A (minus-spmat B)*

lemma *sorted-spmat-diff-spmat*: *sorted-spmat A ⟹ sorted-spmat B ⟹ sorted-spmat (diff-spmat A B)*
by (*simp add*: *diff-spmat-def sorted-spmat-minus-spmat sorted-spmat-add-spmat*)

lemma *sorted-spvec-diff-spmat*: *sorted-spvec A ⟹ sorted-spvec B ⟹ sorted-spvec (diff-spmat A B)*
by (*simp add*: *diff-spmat-def sorted-spvec-minus-spmat sorted-spvec-add-spmat*)

lemma *sparse-row-diff-spmat*: *sparse-row-matrix (diff-spmat A B) = (sparse-row-matrix A) − (sparse-row-matrix B)*
by (*simp add*: *diff-spmat-def sparse-row-add-spmat sparse-row-matrix-minus*)

definition *sorted-sparse-matrix* :: *'a spmat ⇒ bool*
where *sorted-sparse-matrix A ⟷ sorted-spvec A & sorted-spmat A*

lemma *sorted-sparse-matrix-imp-spvec*: *sorted-sparse-matrix A ⟹ sorted-spvec A*
by (*simp add*: *sorted-sparse-matrix-def*)

lemma *sorted-sparse-matrix-imp-spmat*: *sorted-sparse-matrix A ⟹ sorted-spmat A*
by (*simp add*: *sorted-sparse-matrix-def*)

lemmas *sorted-sp-simps* =
sorted-spvec.simps
sorted-spmat.simps
sorted-sparse-matrix-def

lemma *bool1*: (¬ *True*) = *False* **by** *blast*
lemma *bool2*: (¬ *False*) = *True* **by** *blast*
lemma *bool3*: ((*P*::*bool*) ∧ *True*) = *P* **by** *blast*
lemma *bool4*: (*True* ∧ (*P*::*bool*)) = *P* **by** *blast*
lemma *bool5*: ((*P*::*bool*) ∧ *False*) = *False* **by** *blast*
lemma *bool6*: (*False* ∧ (*P*::*bool*)) = *False* **by** *blast*
lemma *bool7*: ((*P*::*bool*) ∨ *True*) = *True* **by** *blast*
lemma *bool8*: (*True* ∨ (*P*::*bool*)) = *True* **by** *blast*
lemma *bool9*: ((*P*::*bool*) ∨ *False*) = *P* **by** *blast*
lemma *bool10*: (*False* ∨ (*P*::*bool*)) = *P* **by** *blast*
lemmas *boolarith = bool1 bool2 bool3 bool4 bool5 bool6 bool7 bool8 bool9 bool10*

lemma *if-case-eq*: (*if b then x else y*) = (*case b of True => x | False => y*) **by** *simp*

primrec *pprt-spvec* :: (*'a*::{*lattice-ab-group-add*}) *spvec ⇒ 'a spvec*
where
pprt-spvec [] = []
| *pprt-spvec* (*a*#*as*) = (*fst a*, *pprt* (*snd a*)) # (*pprt-spvec as*)

primrec *nprt-spvec* :: ('*a*::{*lattice-ab-group-add*}) *spvec* ⇒ '*a spvec*
where
nprt-spvec [] = []
| *nprt-spvec* (*a*#*as*) = (*fst a*, *nprt* (*snd a*)) # (*nprt-spvec as*)

primrec *pprt-spmat* :: ('*a*::{*lattice-ab-group-add*}) *spmat* ⇒ '*a spmat*
where
pprt-spmat [] = []
| *pprt-spmat* (*a*#*as*) = (*fst a*, *pprt-spvec* (*snd a*))#(*pprt-spmat as*)

primrec *nprt-spmat* :: ('*a*::{*lattice-ab-group-add*}) *spmat* ⇒ '*a spmat*
where
nprt-spmat [] = []
| *nprt-spmat* (*a*#*as*) = (*fst a*, *nprt-spvec* (*snd a*))#(*nprt-spmat as*)

lemma *pprt-add*: *disj-matrices A* (*B*::(-::*lattice-ring*) *matrix*) ⟹ *pprt* (*A*+*B*) = *pprt A* + *pprt B*
apply (*simp add*: *pprt-def sup-matrix-def*)
apply (*intro matrix-eqI*)
by (*smt* (*verit*, *del-insts*) *Rep-combine-matrix Rep-zero-matrix-def add.commute comm-monoid-add-class.add-0 disj-matrices-def plus-matrix-def sup.idem*)

lemma *nprt-add*: *disj-matrices A* (*B*::(-::*lattice-ring*) *matrix*) ⟹ *nprt* (*A*+*B*) = *nprt A* + *nprt B*
unfolding *nprt-def inf-matrix-def*
apply (*intro matrix-eqI*)
by (*smt* (*verit*, *ccfv-threshold*) *Rep-combine-matrix Rep-matrix-add add.commute add-cancel-right-right add-eq-inf-sup disj-matrices-contr2 sup.idem*)

lemma *pprt-singleton*[*simp*]:
fixes *x*:: -::*lattice-ring*
shows *pprt* (*singleton-matrix j i x*) = *singleton-matrix j i* (*pprt x*)
unfolding *pprt-def sup-matrix-def*
by (*simp add*: *matrix-eqI*)

lemma *nprt-singleton*[*simp*]:
fixes *x*:: -::*lattice-ring*
shows *nprt* (*singleton-matrix j i x*) = *singleton-matrix j i* (*nprt x*)
by (*metis add-left-imp-eq pprt-singleton prts singleton-matrix-add*)

lemma *sparse-row-vector-pprt*:
fixes *v*:: -::*lattice-ring spvec*
shows *sorted-spvec v* ⟹ *sparse-row-vector* (*pprt-spvec v*) = *pprt* (*sparse-row-vector v*)
proof (*induct v rule*: *sorted-spvec.induct*)
case (*3 m x n y bs*)
then show *?case*
apply *simp*

apply (*subst pprt-add*)
apply (*metis disj-matrices-commute disj-sparse-row-singleton order.refl fst-conv prod.sel(2) sparse-row-vector-cons*)
by (*metis pprt-singleton sorted-spvec-cons1*)
qed *auto*

lemma *sparse-row-vector-nprt*:
fixes *v*:: -::*lattice-ring spvec*
shows *sorted-spvec v* ⟹ *sparse-row-vector* (*nprt-spvec v*) = *nprt* (*sparse-row-vector v*)
proof (*induct v rule*: *sorted-spvec.induct*)
case (*3 m x n y bs*)
then show *?case*
apply *simp*
apply (*subst nprt-add*)
apply (*metis disj-matrices-commute disj-sparse-row-singleton dual-order.refl fst-conv prod.sel(2) sparse-row-vector-cons*)
using *sorted-spvec-cons1* **by** *force*
qed *auto*

lemma *pprt-move-matrix*: *pprt* (*move-matrix* (*A*::('*a*::*lattice-ring*) *matrix*) *j i*) = *move-matrix* (*pprt A*) *j i*
by (*simp add*: *pprt-def sup-matrix-def matrix-eqI*)

lemma *nprt-move-matrix*: *nprt* (*move-matrix* (*A*::('*a*::*lattice-ring*) *matrix*) *j i*) = *move-matrix* (*nprt A*) *j i*
by (*simp add*: *nprt-def inf-matrix-def matrix-eqI*)

lemma *sparse-row-matrix-pprt*:
fixes *m*:: '*a*::*lattice-ring spmat*
shows *sorted-spvec m* ⟹ *sorted-spmat m* ⟹ *sparse-row-matrix* (*pprt-spmat m*) = *pprt* (*sparse-row-matrix m*)
proof (*induct m rule*: *sorted-spvec.induct*)
case (*2 a*)
then show *?case*
by (*simp add*: *pprt-move-matrix sparse-row-matrix-cons sparse-row-vector-pprt*)
next
case (*3 m x n y bs*)
then show *?case*
apply (*simp add*: *sparse-row-matrix-cons sparse-row-vector-pprt*)
apply (*subst pprt-add*)
apply (*subst disj-matrices-commute*)
apply (*metis disj-move-sparse-vec-mat eq-imp-le fst-conv prod.sel(2) sparse-row-matrix-cons*)
apply (*simp add*: *sorted-spvec.simps pprt-move-matrix*)
done
qed *auto*

lemma *sparse-row-matrix-nprt*:

fixes *m*:: *'a*::*lattice-ring spmat*
shows *sorted-spvec m* ⟹ *sorted-spmat m* ⟹ *sorted-spmat m* ⟹ *sparse-row-matrix* (*nprt-spmat m*) = *nprt* (*sparse-row-matrix m*)
proof (*induct m rule*: *sorted-spvec.induct*)
case (*2 a*)
then show *?case*
by (*simp add*: *nprt-move-matrix sparse-row-matrix-cons sparse-row-vector-nprt*)
next
case (*3 m x n y bs*)
then show *?case*
apply (*simp add*: *sparse-row-matrix-cons sparse-row-vector-nprt*)
apply (*subst nprt-add*)
apply (*subst disj-matrices-commute*)
apply (*metis disj-move-sparse-vec-mat fst-conv nle-le prod.sel*(*2*) *sparse-row-matrix-cons*)
apply (*simp add*: *sorted-spvec.simps nprt-move-matrix*)
done
qed *auto*

lemma *sorted-pprt-spvec*: *sorted-spvec v* ⟹ *sorted-spvec* (*pprt-spvec v*)
proof (*induct v rule*: *sorted-spvec.induct*)
case *1*
then show *?case* **by** *auto*
next
case (*2 a*)
then show *?case*
by (*simp add*: *sorted-spvec-step1*)
next
case (*3 m x n y bs*)
then show *?case*
by (*simp add*: *sorted-spvec-step*)
qed

lemma *sorted-nprt-spvec*: *sorted-spvec v* ⟹ *sorted-spvec* (*nprt-spvec v*)
by (*induct v rule*: *sorted-spvec.induct*) (*simp-all add*: *sorted-spvec.simps split*:*list.split-asm*)

lemma *sorted-spvec-pprt-spmat*: *sorted-spvec m* ⟹ *sorted-spvec* (*pprt-spmat m*)
by (*induct m rule*: *sorted-spvec.induct*) (*simp-all add*: *sorted-spvec.simps split*:*list.split-asm*)

lemma *sorted-spvec-nprt-spmat*: *sorted-spvec m* ⟹ *sorted-spvec* (*nprt-spmat m*)
by (*induct m rule*: *sorted-spvec.induct*) (*simp-all add*: *sorted-spvec.simps split*:*list.split-asm*)

lemma *sorted-spmat-pprt-spmat*: *sorted-spmat m* ⟹ *sorted-spmat* (*pprt-spmat m*)
by (*induct m*) (*simp-all add*: *sorted-pprt-spvec*)

lemma *sorted-spmat-nprt-spmat*: *sorted-spmat m* ⟹ *sorted-spmat* (*nprt-spmat m*)
by (*induct m*) (*simp-all add*: *sorted-nprt-spvec*)

definition *mult-est-spmat* :: ('*a*::*lattice-ring*) *spmat* ⇒ '*a spmat* ⇒ '*a spmat* ⇒ '*a spmat* ⇒ '*a spmat* **where**
mult-est-spmat r1 r2 s1 s2 =
add-spmat (*mult-spmat* (*pprt-spmat s2*) (*pprt-spmat r2*)) (*add-spmat* (*mult-spmat* (*pprt-spmat s1*) (*nprt-spmat r2*))
(*add-spmat* (*mult-spmat* (*nprt-spmat s2*) (*pprt-spmat r1*)) (*mult-spmat* (*nprt-spmat s1*) (*nprt-spmat r1*))))

lemmas *sparse-row-matrix-op-simps* =
sorted-sparse-matrix-imp-spmat sorted-sparse-matrix-imp-spvec
sparse-row-add-spmat sorted-spvec-add-spmat sorted-spmat-add-spmat
sparse-row-diff-spmat sorted-spvec-diff-spmat sorted-spmat-diff-spmat
sparse-row-matrix-minus sorted-spvec-minus-spmat sorted-spmat-minus-spmat
sparse-row-mult-spmat sorted-spvec-mult-spmat sorted-spmat-mult-spmat
sparse-row-matrix-abs sorted-spvec-abs-spmat sorted-spmat-abs-spmat
le-spmat-iff-sparse-row-le
sparse-row-matrix-pprt sorted-spvec-pprt-spmat sorted-spmat-pprt-spmat
sparse-row-matrix-nprt sorted-spvec-nprt-spmat sorted-spmat-nprt-spmat

lemmas *sparse-row-matrix-arith-simps* =
mult-spmat.simps mult-spvec-spmat.simps
addmult-spvec.simps
smult-spvec-empty smult-spvec-cons
add-spmat.simps add-spvec.simps
minus-spmat.simps minus-spvec.simps
abs-spmat.simps abs-spvec.simps
diff-spmat-def
le-spmat.simps le-spvec.simps
pprt-spmat.simps pprt-spvec.simps
nprt-spmat.simps nprt-spvec.simps
mult-est-spmat-def

end

theory *LP*
imports *Main HOL−Library.Lattice-Algebras*
begin

lemma *le-add-right-mono*:
assumes
a <= *b* + (*c*::'*a*::*ordered-ab-group-add*)
c <= *d*
shows *a* <= *b* + *d*
apply (*rule-tac order-trans*[**where** *y* = *b*+*c*])
apply (*simp-all add*: *assms*)

done

lemma *linprog-dual-estimate*:
assumes
$A * x \leq (b::'a::lattice\text{-}ring)$
$0 \leq y$
$|A - A'| \leq \delta\text{-}A$
$b \leq b'$
$|c - c'| \leq \delta\text{-}c$
$|x| \leq r$
shows
$c * x \leq y * b' + (y * \delta\text{-}A + |y * A' - c'| + \delta\text{-}c) * r$
proof −
from *assms* **have** *1*: $y * b <= y * b'$ **by** (*simp add*: *mult-left-mono*)
from *assms* **have** *2*: $y * (A * x) <= y * b$ **by** (*simp add*: *mult-left-mono*)
have *3*: $y * (A * x) = c * x + (y * (A - A') + (y * A' - c') + (c'-c)) * x$ **by** (*simp add*: *algebra-simps*)
from *1 2 3* **have** *4*: $c * x + (y * (A - A') + (y * A' - c') + (c'-c)) * x <= y * b'$ **by** *simp*
have *5*: $c * x <= y * b' + |(y * (A - A') + (y * A' - c') + (c'-c)) * x|$
by (*simp only*: *4 estimate-by-abs*)
have *6*: $|(y * (A - A') + (y * A' - c') + (c'-c)) * x| <= |y * (A - A') + (y * A' - c') + (c'-c)| * |x|$
by (*simp add*: *abs-le-mult*)
have *7*: $(|y * (A - A') + (y * A' - c') + (c'-c)|) * |x| <= (|y * (A-A') + (y*A'-c')| + |c' - c|) * |x|$
by(*rule abs-triangle-ineq* [*THEN mult-right-mono*]) *simp*
have *8*: $(|y * (A-A') + (y*A'-c')| + |c' - c|) * |x| <= (|y * (A-A')| + |y*A'-c'| + |c' - c|) * |x|$
by (*simp add*: *abs-triangle-ineq mult-right-mono*)
have *9*: $(|y * (A-A')| + |y*A'-c'| + |c'-c|) * |x| <= (|y| * |A-A'| + |y*A'-c'| + |c'-c|) * |x|$
by (*simp add*: *abs-le-mult mult-right-mono*)
have *10*: $c'-c = -(c-c')$ **by** (*simp add*: *algebra-simps*)
have *11*: $|c'-c| = |c-c'|$
by (*subst 10*, *subst abs-minus-cancel*, *simp*)
have *12*: $(|y| * |A-A'| + |y*A'-c'| + |c'-c|) * |x| <= (|y| * |A-A'| + |y*A'-c'| + \delta\text{-}c) * |x|$
by (*simp add*: *11 assms mult-right-mono*)
have *13*: $(|y| * |A-A'| + |y*A'-c'| + \delta\text{-}c) * |x| <= (|y| * \delta\text{-}A + |y*A'-c'| + \delta\text{-}c) * |x|$
by (*simp add*: *assms mult-right-mono mult-left-mono*)
have *r*: $(|y| * \delta\text{-}A + |y*A'-c'| + \delta\text{-}c) * |x| <= (|y| * \delta\text{-}A + |y*A'-c'| + \delta\text{-}c) * r$
apply (*rule mult-left-mono*)
apply (*simp add*: *assms*)
apply (*rule-tac add-mono*[*of 0::'a - 0*, *simplified*])+
apply (*rule mult-left-mono*[*of 0 δ-A*, *simplified*])
apply (*simp-all*)

```
    apply (rule order-trans[where y=|A−A'|], simp-all add: assms)
    apply (rule order-trans[where y=|c−c'|], simp-all add: assms)
    done
  from 6 7 8 9 12 13 r have 14: |(y * (A − A') + (y * A' − c') + (c'−c)) * x|
<= (|y| * δ-A + |y*A'−c'| + δ-c) * r
    by (simp)
  show ?thesis
    apply (rule le-add-right-mono[of - - |(y * (A − A') + (y * A' − c') + (c'−c))
* x|])
    apply (simp-all only: 5 14[simplified abs-of-nonneg[of y, simplified assms]])
    done
qed

lemma le-ge-imp-abs-diff-1:
  assumes
  A1 <= (A::'a::lattice-ring)
  A <= A2
  shows |A−A1| <= A2−A1
proof −
  have 0 <= A − A1
  proof −
    from assms add-right-mono [of A1 A − A1] show ?thesis by simp
  qed
  then have |A−A1| = A−A1 by (rule abs-of-nonneg)
  with assms show |A−A1| <= (A2−A1) by simp
qed

lemma mult-le-prts:
  assumes
  a1 <= (a::'a::lattice-ring)
  a <= a2
  b1 <= b
  b <= b2
  shows
  a * b <= pprt a2 * pprt b2 + pprt a1 * nprt b2 + nprt a2 * pprt b1 + nprt a1
* nprt b1
proof −
  have a * b = (pprt a + nprt a) * (pprt b + nprt b)
    apply (subst prts[symmetric])+
    apply simp
    done
  then have a * b = pprt a * pprt b + pprt a * nprt b + nprt a * pprt b + nprt
a * nprt b
    by (simp add: algebra-simps)
  moreover have pprt a * pprt b <= pprt a2 * pprt b2
    by (simp-all add: assms mult-mono)
  moreover have pprt a * nprt b <= pprt a1 * nprt b2
  proof −
    have pprt a * nprt b <= pprt a * nprt b2
```

```
    by (simp add: mult-left-mono assms)
   moreover have pprt a * nprt b2 <= pprt a1 * nprt b2
    by (simp add: mult-right-mono-neg assms)
   ultimately show ?thesis
    by simp
  qed
  moreover have nprt a * pprt b <= nprt a2 * pprt b1
  proof -
   have nprt a * pprt b <= nprt a2 * pprt b
    by (simp add: mult-right-mono assms)
   moreover have nprt a2 * pprt b <= nprt a2 * pprt b1
    by (simp add: mult-left-mono-neg assms)
   ultimately show ?thesis
    by simp
  qed
  moreover have nprt a * nprt b <= nprt a1 * nprt b1
  proof -
   have nprt a * nprt b <= nprt a * nprt b1
    by (simp add: mult-left-mono-neg assms)
   moreover have nprt a * nprt b1 <= nprt a1 * nprt b1
    by (simp add: mult-right-mono-neg assms)
   ultimately show ?thesis
    by simp
  qed
  ultimately show ?thesis
   by - (rule add-mono | simp)+
qed

lemma mult-le-dual-prts:
  assumes
  A * x ≤ (b::'a::lattice-ring)
  0 ≤ y
  A1 ≤ A
  A ≤ A2
  c1 ≤ c
  c ≤ c2
  r1 ≤ x
  x ≤ r2
  shows
  c * x ≤ y * b + (let s1 = c1 - y * A2; s2 = c2 - y * A1 in pprt s2 * pprt r2
+ pprt s1 * nprt r2 + nprt s2 * pprt r1 + nprt s1 * nprt r1)
  (is - <= - + ?C)
proof -
  from assms have y * (A * x) <= y * b by (simp add: mult-left-mono)
  moreover have y * (A * x) = c * x + (y * A - c) * x by (simp add: alge-
bra-simps)
  ultimately have c * x + (y * A - c) * x <= y * b by simp
  then have c * x <= y * b - (y * A - c) * x by (simp add: le-diff-eq)
  then have cx: c * x <= y * b + (c - y * A) * x by (simp add: algebra-simps)
```

have *s2*: $c - y * A <= c2 - y * A1$
by (*simp add*: *assms add-mono mult-left-mono algebra-simps*)
have *s1*: $c1 - y * A2 <= c - y * A$
by (*simp add*: *assms add-mono mult-left-mono algebra-simps*)
have *prts*: $(c - y * A) * x <= ?C$
apply (*simp add*: *Let-def*)
apply (*rule mult-le-prts*)
apply (*simp-all add*: *assms s1 s2*)
done
then have $y * b + (c - y * A) * x <= y * b + ?C$
by *simp*
with *cx* **show** *?thesis*
by(*simp only*:)
qed

end

1 Floating Point Representation of the Reals

theory *ComputeFloat*
imports *Complex-Main HOL−Library.Lattice-Algebras*
begin

ML-file ‹~~/*src*/*Tools*/*float.ML*›

definition *int-of-real* :: *real* ⇒ *int*
where *int-of-real x* = (*SOME y*. *real-of-int y* = *x*)

definition *real-is-int* :: *real* ⇒ *bool*
where *real-is-int x* = (∃(*u*::*int*). *x* = *real-of-int u*)

lemma *real-is-int-def2*: *real-is-int x* = (*x* = *real-of-int* (*int-of-real x*))
by (*auto simp add*: *real-is-int-def int-of-real-def*)

lemma *real-is-int-real*[*simp*]: *real-is-int* (*real-of-int* (*x*::*int*))
by (*auto simp add*: *real-is-int-def int-of-real-def*)

lemma *int-of-real-real*[*simp*]: *int-of-real* (*real-of-int x*) = *x*
by (*simp add*: *int-of-real-def*)

lemma *real-int-of-real*[*simp*]: *real-is-int x* ⟹ *real-of-int* (*int-of-real x*) = *x*
by (*auto simp add*: *int-of-real-def real-is-int-def*)

lemma *real-is-int-add-int-of-real*: *real-is-int a* ⟹ *real-is-int b* ⟹ (*int-of-real* (*a*+*b*)) = (*int-of-real a*) + (*int-of-real b*)
by (*auto simp add*: *int-of-real-def real-is-int-def*)

lemma *real-is-int-add*[*simp*]: *real-is-int a* $\Longrightarrow$ *real-is-int b* $\Longrightarrow$ *real-is-int* (*a*+*b*)
apply (*subst real-is-int-def2*)
apply (*simp add*: *real-is-int-add-int-of-real real-int-of-real*)
done

lemma *int-of-real-sub*: *real-is-int a* $\Longrightarrow$ *real-is-int b* $\Longrightarrow$ (*int-of-real* (*a*−*b*)) = (*int-of-real a*) − (*int-of-real b*)
by (*auto simp add*: *int-of-real-def real-is-int-def*)

lemma *real-is-int-sub*[*simp*]: *real-is-int a* $\Longrightarrow$ *real-is-int b* $\Longrightarrow$ *real-is-int* (*a*−*b*)
apply (*subst real-is-int-def2*)
apply (*simp add*: *int-of-real-sub real-int-of-real*)
done

lemma *real-is-int-rep*: *real-is-int x* $\Longrightarrow$ $\exists!$(*a*::*int*). *real-of-int a* = *x*
by (*auto simp add*: *real-is-int-def*)

lemma *int-of-real-mult*:
  assumes *real-is-int a real-is-int b*
  shows (*int-of-real* (*a*∗*b*)) = (*int-of-real a*) ∗ (*int-of-real b*)
  using *assms*
  by (*auto simp add*: *real-is-int-def of-int-mult*[*symmetric*]
        simp del: *of-int-mult*)

lemma *real-is-int-mult*[*simp*]: *real-is-int a* $\Longrightarrow$ *real-is-int b* $\Longrightarrow$ *real-is-int* (*a*∗*b*)
apply (*subst real-is-int-def2*)
apply (*simp add*: *int-of-real-mult*)
done

lemma *real-is-int-0*[*simp*]: *real-is-int* (*0*::*real*)
by (*simp add*: *real-is-int-def int-of-real-def*)

lemma *real-is-int-1*[*simp*]: *real-is-int* (*1*::*real*)
proof −
  have *real-is-int* (*1*::*real*) = *real-is-int*(*real-of-int* (*1*::*int*)) **by** *auto*
  also have ... = *True* **by** (*simp only*: *real-is-int-real*)
  ultimately show *?thesis* **by** *auto*
qed

lemma *real-is-int-n1*: *real-is-int* (−*1*::*real*)
proof −
  have *real-is-int* (−*1*::*real*) = *real-is-int*(*real-of-int* (−*1*::*int*)) **by** *auto*
  also have ... = *True* **by** (*simp only*: *real-is-int-real*)
  ultimately show *?thesis* **by** *auto*
qed

lemma *real-is-int-numeral*[*simp*]: *real-is-int* (*numeral x*)
  by (*auto simp*: *real-is-int-def intro*!: *exI*[*of - numeral x*])

lemma *real-is-int-neg-numeral*[*simp*]: *real-is-int* (− *numeral x*)
by (*auto simp*: *real-is-int-def intro*!: *exI*[*of* - − *numeral x*])

lemma *int-of-real-0*[*simp*]: *int-of-real* (*0*::*real*) = (*0*::*int*)
by (*simp add*: *int-of-real-def*)

lemma *int-of-real-1*[*simp*]: *int-of-real* (*1*::*real*) = (*1*::*int*)
proof −
have *1*: (*1*::*real*) = *real-of-int* (*1*::*int*) **by** *auto*
show *?thesis* **by** (*simp only*: *1 int-of-real-real*)
qed

lemma *int-of-real-numeral*[*simp*]: *int-of-real* (*numeral b*) = *numeral b*
unfolding *int-of-real-def* **by** *simp*

lemma *int-of-real-neg-numeral*[*simp*]: *int-of-real* (− *numeral b*) = − *numeral b*
unfolding *int-of-real-def*
by (*metis int-of-real-def int-of-real-real of-int-minus of-int-of-nat-eq of-nat-numeral*)

lemma *int-div-zdiv*: *int* (*a div b*) = (*int a*) *div* (*int b*)
by (*rule zdiv-int*)

lemma *int-mod-zmod*: *int* (*a mod b*) = (*int a*) *mod* (*int b*)
by (*rule zmod-int*)

lemma *abs-div-2-less*: *a* ≠ *0* ⟹ *a* ≠ −*1* ⟹ |(*a*::*int*) *div 2*| < |*a*|
by *arith*

lemma *norm-0-1*: (*1*::-::*numeral*) = *Numeral1*
by *auto*

lemma *add-left-zero*: *0* + *a* = (*a*::′*a*::*comm-monoid-add*)
by *simp*

lemma *add-right-zero*: *a* + *0* = (*a*::′*a*::*comm-monoid-add*)
by *simp*

lemma *mult-left-one*: *1* ∗ *a* = (*a*::′*a*::*semiring-1*)
by *simp*

lemma *mult-right-one*: *a* ∗ *1* = (*a*::′*a*::*semiring-1*)
by *simp*

lemma *int-pow-0*: (*a*::*int*)^*0* = *1*
by *simp*

lemma *int-pow-1*: (*a*::*int*)^(*Numeral1*) = *a*
by *simp*

lemma *one-eq-Numeral1-nring*: $(1::'a::numeral) = Numeral1$
by *simp*

lemma *one-eq-Numeral1-nat*: $(1::nat) = Numeral1$
by *simp*

lemma *zpower-Pls*: $(z::int)\hat{}0 = Numeral1$
by *simp*

lemma *fst-cong*: $a=a' \Longrightarrow fst\ (a,b) = fst\ (a',b)$
by *simp*

lemma *snd-cong*: $b=b' \Longrightarrow snd\ (a,b) = snd\ (a,b')$
by *simp*

lemma *lift-bool*: $x \Longrightarrow x=True$
by *simp*

lemma *nlift-bool*: $\sim x \Longrightarrow x=False$
by *simp*

lemma *not-false-eq-true*: $(\sim\ False) = True$ **by** *simp*

lemma *not-true-eq-false*: $(\sim\ True) = False$ **by** *simp*

lemmas *powerarith* = *nat-numeral power-numeral-even*
power-numeral-odd zpower-Pls

definition *float* :: $(int \times int) \Rightarrow real$ **where**
$float = (\lambda(a,\ b).\ real\text{-}of\text{-}int\ a * 2\ powr\ real\text{-}of\text{-}int\ b)$

lemma *float-add-l0*: $float\ (0,\ e) + x = x$
by (*simp add*: *float-def*)

lemma *float-add-r0*: $x + float\ (0,\ e) = x$
by (*simp add*: *float-def*)

lemma *float-add*:
$float\ (a1,\ e1) + float\ (a2,\ e2) =$
$(if\ e1<=e2\ then\ float\ (a1+a2*2\hat{}(nat(e2-e1)),\ e1)\ else\ float\ (a1*2\hat{}(nat\ (e1-e2))+a2,$
$e2))$
by (*simp add*: *float-def algebra-simps powr-realpow*[*symmetric*] *powr-diff*)

lemma *float-mult-l0*: $float\ (0,\ e) * x = float\ (0,\ 0)$
by (*simp add*: *float-def*)

lemma *float-mult-r0*: $x * float\ (0,\ e) = float\ (0,\ 0)$
by (*simp add*: *float-def*)

lemma *float-mult*:
float (*a1*, *e1*) * *float* (*a2*, *e2*) = (*float* (*a1* * *a2*, *e1* + *e2*))
by (*simp add*: *float-def powr-add*)

lemma *float-minus*:
− (*float* (*a*,*b*)) = *float* (−*a*, *b*)
by (*simp add*: *float-def*)

lemma *zero-le-float*:
(*0* <= *float* (*a*,*b*)) = (*0* <= *a*)
by (*simp add*: *float-def zero-le-mult-iff*)

lemma *float-le-zero*:
(*float* (*a*,*b*) <= *0*) = (*a* <= *0*)
by (*simp add*: *float-def mult-le-0-iff*)

lemma *float-abs*:
|*float* (*a*,*b*)| = (*if 0* <= *a then* (*float* (*a*,*b*)) *else* (*float* (−*a*,*b*)))
by (*simp add*: *float-def abs-if mult-less-0-iff not-less*)

lemma *float-zero*:
float (*0*, *b*) = *0*
by (*simp add*: *float-def*)

lemma *float-pprt*:
pprt (*float* (*a*, *b*)) = (*if 0* <= *a then* (*float* (*a*,*b*)) *else* (*float* (*0*, *b*)))
by (*auto simp add*: *zero-le-float float-le-zero float-zero*)

lemma *float-nprt*:
nprt (*float* (*a*, *b*)) = (*if 0* <= *a then* (*float* (*0*,*b*)) *else* (*float* (*a*, *b*)))
by (*auto simp add*: *zero-le-float float-le-zero float-zero*)

definition *lbound* :: *real* ⇒ *real*
where *lbound x* = *min 0 x*

definition *ubound* :: *real* ⇒ *real*
where *ubound x* = *max 0 x*

lemma *lbound*: *lbound x* ≤ *x*
by (*simp add*: *lbound-def*)

lemma *ubound*: *x* ≤ *ubound x*
by (*simp add*: *ubound-def*)

lemma *pprt-lbound*: *pprt* (*lbound x*) = *float* (*0*, *0*)
by (*auto simp*: *float-def lbound-def*)

lemma *nprt-ubound*: *nprt* (*ubound x*) = *float* (*0*, *0*)

by (*auto simp*: *float-def ubound-def*)

lemmas *floatarith*[*simplified norm-0-1*] = *float-add float-add-l0 float-add-r0 float-mult float-mult-l0 float-mult-r0*
float-minus float-abs zero-le-float float-pprt float-nprt pprt-lbound nprt-ubound

lemmas *arith* = *arith-simps rel-simps diff-nat-numeral nat-0*
nat-neg-numeral powerarith floatarith not-false-eq-true not-true-eq-false

ML-file ‹*float-arith.ML*›

end

theory *Compute-Oracle* **imports** *HOL.HOL*
begin

ML-file ‹*am.ML*›
ML-file ‹*am-compiler.ML*›
ML-file ‹*am-interpreter.ML*›
ML-file ‹*am-ghc.ML*›
ML-file ‹*am-sml.ML*›
ML-file ‹*report.ML*›
ML-file ‹*compute.ML*›
ML-file ‹*linker.ML*›

end
theory *ComputeHOL*
imports *Complex-Main Compute-Oracle*/*Compute-Oracle*
begin

lemma *Trueprop-eq-eq*: *Trueprop X* == (*X* == *True*) **by** (*simp add*: *atomize-eq*)
lemma *meta-eq-trivial*: *x* == *y* ⟹ *x* == *y* **by** *simp*
lemma *meta-eq-imp-eq*: *x* == *y* ⟹ *x* = *y* **by** *auto*
lemma *eq-trivial*: *x* = *y* ⟹ *x* = *y* **by** *auto*
lemma *bool-to-true*: *x* :: *bool* ⟹ *x* == *True* **by** *simp*
lemma *transmeta-1*: *x* = *y* ⟹ *y* == *z* ⟹ *x* = *z* **by** *simp*
lemma *transmeta-2*: *x* == *y* ⟹ *y* = *z* ⟹ *x* = *z* **by** *simp*
lemma *transmeta-3*: *x* == *y* ⟹ *y* == *z* ⟹ *x* = *z* **by** *simp*

lemma *If-True*: *If True* = (λ *x y*. *x*) **by** ((*rule ext*)+,*auto*)
lemma *If-False*: *If False* = (λ *x y*. *y*) **by** ((*rule ext*)+, *auto*)

lemmas *compute-if* = *If-True If-False*

lemma *bool1*: $(\neg\ True) = False$ **by** *blast*
lemma *bool2*: $(\neg\ False) = True$ **by** *blast*
lemma *bool3*: $(P \wedge True) = P$ **by** *blast*
lemma *bool4*: $(True \wedge P) = P$ **by** *blast*
lemma *bool5*: $(P \wedge False) = False$ **by** *blast*
lemma *bool6*: $(False \wedge P) = False$ **by** *blast*
lemma *bool7*: $(P \vee True) = True$ **by** *blast*
lemma *bool8*: $(True \vee P) = True$ **by** *blast*
lemma *bool9*: $(P \vee False) = P$ **by** *blast*
lemma *bool10*: $(False \vee P) = P$ **by** *blast*
lemma *bool11*: $(True \longrightarrow P) = P$ **by** *blast*
lemma *bool12*: $(P \longrightarrow True) = True$ **by** *blast*
lemma *bool13*: $(True \longrightarrow P) = P$ **by** *blast*
lemma *bool14*: $(P \longrightarrow False) = (\neg\ P)$ **by** *blast*
lemma *bool15*: $(False \longrightarrow P) = True$ **by** *blast*
lemma *bool16*: $(False = False) = True$ **by** *blast*
lemma *bool17*: $(True = True) = True$ **by** *blast*
lemma *bool18*: $(False = True) = False$ **by** *blast*
lemma *bool19*: $(True = False) = False$ **by** *blast*

lemmas *compute-bool* = *bool1 bool2 bool3 bool4 bool5 bool6 bool7 bool8 bool9 bool10 bool11 bool12 bool13 bool14 bool15 bool16 bool17 bool18 bool19*

lemma *compute-fst*: *fst* $(x,y) = x$ **by** *simp*
lemma *compute-snd*: *snd* $(x,y) = y$ **by** *simp*
lemma *compute-pair-eq*: $((a,\ b) = (c,\ d)) = (a = c \wedge b = d)$ **by** *auto*

lemma *case-prod-simp*: *case-prod f* $(x,y) = f\ x\ y$ **by** *simp*

lemmas *compute-pair* = *compute-fst compute-snd compute-pair-eq case-prod-simp*

lemma *compute-the*: *the* $(Some\ x) = x$ **by** *simp*
lemma *compute-None-Some-eq*: $(None = Some\ x) = False$ **by** *auto*
lemma *compute-Some-None-eq*: $(Some\ x = None) = False$ **by** *auto*
lemma *compute-None-None-eq*: $(None = None) = True$ **by** *auto*
lemma *compute-Some-Some-eq*: $(Some\ x = Some\ y) = (x = y)$ **by** *auto*

definition *case-option-compute* :: $'b\ option \Rightarrow 'a \Rightarrow ('b \Rightarrow 'a) \Rightarrow 'a$
where *case-option-compute opt a f* = *case-option a f opt*

lemma *case-option-compute*: *case-option* = $(\lambda\ a\ f\ opt.$ *case-option-compute opt a f*$)$

by (*simp add*: *case-option-compute-def*)

lemma *case-option-compute-None*: *case-option-compute None* = (λ *a f*. *a*)
apply (*rule ext*)+
apply (*simp add*: *case-option-compute-def*)
done

lemma *case-option-compute-Some*: *case-option-compute* (*Some x*) = (λ *a f*. *f x*)
apply (*rule ext*)+
apply (*simp add*: *case-option-compute-def*)
done

lemmas *compute-case-option* = *case-option-compute case-option-compute-None case-option-compute-Some*

lemmas *compute-option* = *compute-the compute-None-Some-eq compute-Some-None-eq compute-None-None-eq compute-Some-Some-eq compute-case-option*

lemma *length-cons*:*length* (*x*#*xs*) = *1* + (*length xs*)
by *simp*

lemma *length-nil*: *length* [] = *0*
by *simp*

lemmas *compute-list-length* = *length-nil length-cons*

definition *case-list-compute* :: *'b list* ⇒ *'a* ⇒ (*'b* ⇒ *'b list* ⇒ *'a*) ⇒ *'a*
where *case-list-compute l a f* = *case-list a f l*

lemma *case-list-compute*: *case-list* = (λ (*a*::*'a*) *f* (*l*::*'b list*). *case-list-compute l a f*)
apply (*rule ext*)+
apply (*simp add*: *case-list-compute-def*)
done

lemma *case-list-compute-empty*: *case-list-compute* ([]::*'b list*) = (λ (*a*::*'a*) *f*. *a*)
apply (*rule ext*)+
apply (*simp add*: *case-list-compute-def*)
done

lemma *case-list-compute-cons*: *case-list-compute* (*u*#*v*) = (λ (*a*::*'a*) *f*. (*f* (*u*::*'b*) *v*))
apply (*rule ext*)+
apply (*simp add*: *case-list-compute-def*)
done

lemmas *compute-case-list = case-list-compute case-list-compute-empty case-list-compute-cons*

lemma *compute-list-nth*: *((x#xs) ! n) = (if n = 0 then x else (xs ! (n − 1)))*
by (*cases n*, *auto*)

lemmas *compute-list = compute-case-list compute-list-length compute-list-nth*

lemmas *compute-let = Let-def*

lemmas *compute-hol = compute-if compute-bool compute-pair compute-option compute-list compute-let*

ML ‹
```
signature ComputeHOL =
sig
  val prep-thms : thm list -> thm list
  val to-meta-eq : thm -> thm
  val to-hol-eq : thm -> thm
  val symmetric : thm -> thm
  val trans : thm -> thm -> thm
end

structure ComputeHOL : ComputeHOL =
struct

local
fun lhs-of eq = fst (Thm.dest-equals (Thm.cprop-of eq));
in
fun rewrite-conv [] ct = raise CTERM (rewrite-conv, [ct])
  | rewrite-conv (eq :: eqs) ct =
      Thm.instantiate (Thm.match (lhs-of eq, ct)) eq
      handle Pattern.MATCH => rewrite-conv eqs ct;
end

val convert-conditions = Conv.fconv-rule (Conv.prems-conv ~1 (Conv.try-conv (rewrite-conv
[@{thm Trueprop-eq-eq}])))

val eq-th = @{thm HOL.eq-reflection}
```

val meta-eq-trivial = @{thm ComputeHOL.meta-eq-trivial}
val bool-to-true = @{thm ComputeHOL.bool-to-true}

fun to-meta-eq th = eq-th OF [th] handle THM - => meta-eq-trivial OF [th] handle THM - => bool-to-true OF [th]

fun to-hol-eq th = @{thm meta-eq-imp-eq} OF [th] handle THM - => @{thm eq-trivial} OF [th]

fun prep-thms ths = map (convert-conditions o to-meta-eq) ths

fun symmetric th = @{thm HOL.sym} OF [th] handle THM - => @{thm Pure.symmetric} OF [th]

local
  val trans-HOL = @{thm HOL.trans}
  val trans-HOL-1 = @{thm ComputeHOL.transmeta-1}
  val trans-HOL-2 = @{thm ComputeHOL.transmeta-2}
  val trans-HOL-3 = @{thm ComputeHOL.transmeta-3}
  fun tr [] th1 th2 = trans-HOL OF [th1, th2]
    | tr (t::ts) th1 th2 = (t OF [th1, th2] handle THM - => tr ts th1 th2)
in
 fun trans th1 th2 = tr [trans-HOL, trans-HOL-1, trans-HOL-2, trans-HOL-3] th1 th2
end

end
›

end
theory *ComputeNumeral*
imports *ComputeHOL ComputeFloat*
begin

lemmas *biteq = eq-num-simps*

lemmas *bitless = less-num-simps*

lemmas *bitle = le-num-simps*

lemmas *bitadd = add-num-simps*

lemmas *bitmul = mult-num-simps*

lemmas *bitarith* = *arith-simps*

lemmas *natnorm* = *one-eq-Numeral1-nat*

fun *natfac* :: *nat* ⇒ *nat*
  where *natfac n* = (*if n* = *0 then 1 else n* ∗ (*natfac* (*n* − *1*)))

lemmas *compute-natarith* =
  arith-simps rel-simps
  diff-nat-numeral nat-numeral nat-0 nat-neg-numeral
  numeral-One [*symmetric*]
  numeral-1-eq-Suc-0 [*symmetric*]
  Suc-numeral natfac.simps

lemmas *number-norm* = *numeral-One*[*symmetric*]

lemmas *compute-numberarith* =
  arith-simps rel-simps number-norm

lemmas *compute-num-conversions* =
  of-nat-numeral of-nat-0
  nat-numeral nat-0 nat-neg-numeral
  of-int-numeral of-int-neg-numeral of-int-0

lemmas *zpowerarith* = *power-numeral-even power-numeral-odd zpower-Pls int-pow-1*

lemmas *compute-div-mod* = *div-0 mod-0 div-by-0 mod-by-0 div-by-1 mod-by-1*
 one-div-numeral one-mod-numeral minus-one-div-numeral minus-one-mod-numeral
 one-div-minus-numeral one-mod-minus-numeral
 numeral-div-numeral numeral-mod-numeral minus-numeral-div-numeral minus-numeral-mod-numeral
 numeral-div-minus-numeral numeral-mod-minus-numeral
 div-minus-minus mod-minus-minus Parity.adjust-div-eq of-bool-eq one-neq-zero
 numeral-neq-zero neg-equal-0-iff-equal arith-simps arith-special divmod-trivial
 divmod-steps divmod-cancel divmod-step-def fst-conv snd-conv numeral-One
 case-prod-beta rel-simps Parity.adjust-mod-def div-minus1-right mod-minus1-right
 minus-minus numeral-times-numeral mult-zero-right mult-1-right

lemma *even-0-int*: *even* (*0*::*int*) = *True*
  by *simp*

lemma *even-One-int*: *even* (*numeral Num.One* :: *int*) = *False*
  by *simp*

lemma *even-Bit0-int*: *even* (*numeral* (*Num.Bit0 x*) :: *int*) = *True*
by (*simp only*: *even-numeral*)

lemma *even-Bit1-int*: *even* (*numeral* (*Num.Bit1 x*) :: *int*) = *False*
by (*simp only*: *odd-numeral*)

lemmas *compute-even* = *even-0-int even-One-int even-Bit0-int even-Bit1-int*

lemmas *compute-numeral* = *compute-if compute-let compute-pair compute-bool*
compute-natarith compute-numberarith max-def min-def
compute-num-conversions zpowerarith compute-div-mod compute-even

end

theory *Cplex*
imports *SparseMatrix LP ComputeFloat ComputeNumeral*
begin

ML-file ‹*Cplex-tools.ML*›
ML-file ‹*CplexMatrixConverter.ML*›
ML-file ‹*FloatSparseMatrixBuilder.ML*›
ML-file ‹*fspmlp.ML*›

lemma *spm-mult-le-dual-prts*:
assumes
sorted-sparse-matrix A1
sorted-sparse-matrix A2
sorted-sparse-matrix c1
sorted-sparse-matrix c2
sorted-sparse-matrix y
sorted-sparse-matrix r1
sorted-sparse-matrix r2
sorted-spvec b
le-spmat [] *y*
sparse-row-matrix A1 ≤ *A*
A ≤ *sparse-row-matrix A2*
sparse-row-matrix c1 ≤ *c*
c ≤ *sparse-row-matrix c2*
sparse-row-matrix r1 ≤ *x*
x ≤ *sparse-row-matrix r2*
A ∗ *x* ≤ *sparse-row-matrix* (*b*::('*a*::*lattice-ring*) *spmat*)
shows
c ∗ *x* ≤ *sparse-row-matrix* (*add-spmat* (*mult-spmat y b*)
(*let s1* = *diff-spmat c1* (*mult-spmat y A2*); *s2* = *diff-spmat c2* (*mult-spmat y A1*) *in*
add-spmat (*mult-spmat* (*pprt-spmat s2*) (*pprt-spmat r2*)) (*add-spmat* (*mult-spmat* (*pprt-spmat s1*) (*nprt-spmat r2*))
(*add-spmat* (*mult-spmat* (*nprt-spmat s2*) (*pprt-spmat r1*)) (*mult-spmat* (*nprt-spmat*

s1) (*nprt-spmat r1*))))))
apply (*simp add*: *Let-def*)
apply (*insert assms*)
apply (*simp add*: *sparse-row-matrix-op-simps algebra-simps*)
apply (*rule mult-le-dual-prts*[**where** *A*=*A*, *simplified Let-def algebra-simps*])
apply (*auto*)
done

lemma *spm-mult-le-dual-prts-no-let*:
assumes
sorted-sparse-matrix A1
sorted-sparse-matrix A2
sorted-sparse-matrix c1
sorted-sparse-matrix c2
sorted-sparse-matrix y
sorted-sparse-matrix r1
sorted-sparse-matrix r2
sorted-spvec b
le-spmat [] *y*
sparse-row-matrix A1 ≤ *A*
A ≤ *sparse-row-matrix A2*
sparse-row-matrix c1 ≤ *c*
c ≤ *sparse-row-matrix c2*
sparse-row-matrix r1 ≤ *x*
x ≤ *sparse-row-matrix r2*
A ∗ *x* ≤ *sparse-row-matrix* (*b*::('*a*::*lattice-ring*) *spmat*)
shows
c ∗ *x* ≤ *sparse-row-matrix* (*add-spmat* (*mult-spmat y b*)
(*mult-est-spmat r1 r2* (*diff-spmat c1* (*mult-spmat y A2*)) (*diff-spmat c2* (*mult-spmat y A1*))))
by (*simp add*: *assms mult-est-spmat-def spm-mult-le-dual-prts*[**where** *A*=*A*, *simplified Let-def*])

ML-file ‹*matrixlp.ML*›

end