Examples for program extraction in Higher-Order Logic

Stefan Berghofer

October 24, 2026

Contents

1 Auxiliary lemmas used in program extraction examples **1**

2 Quotient and remainder **2**

3 Greatest common divisor **2**

4 Warshall's algorithm **3**

5 Higman's lemma **5**
5.1 Extracting the program 8
5.2 Some examples 9

6 The pigeonhole principle **10**

7 Euclid's theorem **12**

1 Auxiliary lemmas used in program extraction examples

theory *Util*
imports *Main*
begin

Decidability of equality on natural numbers.

lemma *nat-eq-dec*: $\bigwedge n{::}nat.\ m = n \vee m \neq n$
⟨*proof*⟩

Well-founded induction on natural numbers, derived using the standard structural induction rule.

lemma *nat-wf-ind*:
assumes *R*: $\bigwedge x{::}nat.\ (\bigwedge y.\ y < x \Longrightarrow P\ y) \Longrightarrow P\ x$

shows $P\ z$
⟨*proof*⟩

Bounded search for a natural number satisfying a decidable predicate.

lemma *search*:
assumes *dec*: $\bigwedge x{::}nat.\ P\ x \vee \neg\ P\ x$
shows $(\exists\, x{<}y.\ P\ x) \vee \neg\ (\exists\, x{<}y.\ P\ x)$
⟨*proof*⟩

end

2 Quotient and remainder

theory *QuotRem*
imports *Util HOL−Library.Realizers*
begin

Derivation of quotient and remainder using program extraction.

theorem *division*: $\exists\, r\ q.\ a = Suc\ b * q + r \wedge r \leq b$
⟨*proof*⟩

extract *division*

The program extracted from the above proof looks as follows

```
division ≡
λx xa.
   nat-induct-P x (0, 0)
    (λa H. let (x, y) = H
           in case nat-eq-dec x xa of Left ⇒ (0, Suc y)
              | Right ⇒ (Suc x, y))
```

The corresponding correctness theorem is

$a = Suc\ b * snd\ (division\ a\ b) + fst\ (division\ a\ b) \wedge fst\ (division\ a\ b) \leq b$

lemma *division 9 2* $= (0, 3)$ ⟨*proof*⟩

end

3 Greatest common divisor

theory *Greatest-Common-Divisor*
imports *QuotRem*
begin

theorem *greatest-common-divisor*:
$\bigwedge n{::}nat.\ Suc\ m < n \Longrightarrow$

$\exists\, k\ n1\ m1.\ k * n1 = n \wedge k * m1 = Suc\ m \wedge$
$(\forall\, l\ l1\ l2.\ l * l1 = n \longrightarrow l * l2 = Suc\ m \longrightarrow l \leq k)$
⟨*proof*⟩

extract *greatest-common-divisor*

The extracted program for computing the greatest common divisor is

```
greatest-common-divisor ≡
λx. nat-wf-ind-P x
      (λx H2 xa.
          let (xa, y) = division xa x
          in nat-exhaust-P xa (Suc x, y, 1)
              (λnat. let (x, ya) = H2 nat (Suc x); (xa, ya) = ya
                     in (x, xa * y + ya, xa)))
```

instantiation *nat* :: *default*
begin

definition *default* = (*0*::*nat*)

instance ⟨*proof*⟩

end

instantiation *prod* :: (*default*, *default*) *default*
begin

definition *default* = (*default*, *default*)

instance ⟨*proof*⟩

end

instantiation *fun* :: (*type*, *default*) *default*
begin

definition *default* = (λ*x*. *default*)

instance ⟨*proof*⟩

end

lemma *greatest-common-divisor 7 12* = (*4*, *3*, *2*) ⟨*proof*⟩

end

4 Warshall's algorithm

theory *Warshall*

imports *HOL−Library.Realizers*
begin

Derivation of Warshall's algorithm using program extraction, based on Berger, Schwichtenberg and Seisenberger [1].

datatype $b = T \mid F$

primrec *is-path'* :: $('a \Rightarrow 'a \Rightarrow b) \Rightarrow 'a \Rightarrow 'a\ list \Rightarrow 'a \Rightarrow bool$
where
  is-path' $r\ x\ []\ z \longleftrightarrow r\ x\ z = T$
| *is-path'* $r\ x\ (y \# ys)\ z \longleftrightarrow r\ x\ y = T \wedge$ *is-path'* $r\ y\ ys\ z$

definition *is-path* :: $(nat \Rightarrow nat \Rightarrow b) \Rightarrow (nat * nat\ list * nat) \Rightarrow nat \Rightarrow nat \Rightarrow nat \Rightarrow bool$
  where *is-path* $r\ p\ i\ j\ k \longleftrightarrow$
    $fst\ p = j \wedge snd\ (snd\ p) = k \wedge$
    list-all $(\lambda x.\ x < i)\ (fst\ (snd\ p)) \wedge$
    is-path' $r\ (fst\ p)\ (fst\ (snd\ p))\ (snd\ (snd\ p))$

definition *conc* :: $'a \times 'a\ list \times 'a \Rightarrow 'a \times 'a\ list \times 'a \Rightarrow 'a \times 'a\ list * 'a$
  where *conc* $p\ q = (fst\ p, fst\ (snd\ p) @ fst\ q \# fst\ (snd\ q), snd\ (snd\ q))$

theorem *is-path'-snoc* [*simp*]: $\bigwedge x.$ *is-path'* $r\ x\ (ys @ [y])\ z =$ (*is-path'* $r\ x\ ys\ y \wedge r\ y\ z = T$)
  ⟨*proof*⟩

theorem *list-all-scoc* [*simp*]: *list-all* $P\ (xs @ [x]) \longleftrightarrow P\ x \wedge$ *list-all* $P\ xs$
  ⟨*proof*⟩

theorem *list-all-lemma*: *list-all* $P\ xs \Longrightarrow (\bigwedge x.\ P\ x \Longrightarrow Q\ x) \Longrightarrow$ *list-all* $Q\ xs$
⟨*proof*⟩

theorem *lemma1*: $\bigwedge p.$ *is-path* $r\ p\ i\ j\ k \Longrightarrow$ *is-path* $r\ p\ (Suc\ i)\ j\ k$
  ⟨*proof*⟩

theorem *lemma2*: $\bigwedge p.$ *is-path* $r\ p\ 0\ j\ k \Longrightarrow r\ j\ k = T$
  ⟨*proof*⟩

theorem *is-path'-conc*: *is-path'* $r\ j\ xs\ i \Longrightarrow$ *is-path'* $r\ i\ ys\ k \Longrightarrow$
  is-path' $r\ j\ (xs @ i \# ys)\ k$
⟨*proof*⟩

theorem *lemma3*:
  $\bigwedge p\ q.$ *is-path* $r\ p\ i\ j\ i \Longrightarrow$ *is-path* $r\ q\ i\ i\ k \Longrightarrow$
    is-path $r\ (conc\ p\ q)\ (Suc\ i)\ j\ k$
  ⟨*proof*⟩

theorem *lemma5*:
  $\bigwedge p.$ *is-path* $r\ p\ (Suc\ i)\ j\ k \Longrightarrow \neg$ *is-path* $r\ p\ i\ j\ k \Longrightarrow$

$(\exists\, q.\ \mathit{is\text{-}path}\ r\ q\ i\ j\ i) \wedge (\exists\, q'.\ \mathit{is\text{-}path}\ r\ q'\ i\ i\ k)$
⟨*proof*⟩

theorem *lemma5'*:
$\bigwedge p.\ \mathit{is\text{-}path}\ r\ p\ (\mathit{Suc}\ i)\ j\ k \Longrightarrow \neg\ \mathit{is\text{-}path}\ r\ p\ i\ j\ k \Longrightarrow$
$\neg\ (\forall\, q.\ \neg\ \mathit{is\text{-}path}\ r\ q\ i\ j\ i) \wedge \neg\ (\forall\, q'.\ \neg\ \mathit{is\text{-}path}\ r\ q'\ i\ i\ k)$
⟨*proof*⟩

theorem *warshall*: $\bigwedge j\ k.\ \neg\ (\exists\, p.\ \mathit{is\text{-}path}\ r\ p\ i\ j\ k) \vee (\exists\, p.\ \mathit{is\text{-}path}\ r\ p\ i\ j\ k)$
⟨*proof*⟩

extract *warshall*

The program extracted from the above proof looks as follows

```
warshall ≡
λx xa xb xc.
  nat-induct-P xa
   (λxa xb. case x xa xb of T ⇒ Some (xa, [], xb) | F ⇒ None)
   (λx H2 xa xb.
      case H2 xa xb of
      None ⇒
        case H2 xa x of None ⇒ None
        | Some q ⇒
            case H2 x xb of None ⇒ None | Some qa ⇒ Some (conc q qa)
      | Some q ⇒ Some q)
   xb xc
```

The corresponding correctness theorem is

$\mathit{case}\ \mathit{warshall}\ r\ i\ j\ k\ \mathit{of}\ \mathit{None} \Rightarrow \forall\, x.\ \neg\ \mathit{is\text{-}path}\ r\ x\ i\ j\ k$
$\mid \mathit{Some}\ q \Rightarrow \mathit{is\text{-}path}\ r\ q\ i\ j\ k$

⟨*ML*⟩

end

5 Higman's lemma

theory *Higman*
imports *Main*
begin

Formalization by Stefan Berghofer and Monika Seisenberger, based on Coquand and Fridlender [2].

datatype *letter* = *A* | *B*

inductive *emb* :: *letter list* ⇒ *letter list* ⇒ *bool*
where

```
  emb0 [Pure.intro]: emb [] bs
| emb1 [Pure.intro]: emb as bs ⟹ emb as (b # bs)
| emb2 [Pure.intro]: emb as bs ⟹ emb (a # as) (a # bs)

inductive L :: letter list ⇒ letter list list ⇒ bool
  for v :: letter list
where
  L0 [Pure.intro]: emb w v ⟹ L v (w # ws)
| L1 [Pure.intro]: L v ws ⟹ L v (w # ws)

inductive good :: letter list list ⇒ bool
where
  good0 [Pure.intro]: L w ws ⟹ good (w # ws)
| good1 [Pure.intro]: good ws ⟹ good (w # ws)

inductive R :: letter ⇒ letter list list ⇒ letter list list ⇒ bool
  for a :: letter
where
  R0 [Pure.intro]: R a [] []
| R1 [Pure.intro]: R a vs ws ⟹ R a (w # vs) ((a # w) # ws)

inductive T :: letter ⇒ letter list list ⇒ letter list list ⇒ bool
  for a :: letter
where
  T0 [Pure.intro]: a ≠ b ⟹ R b ws zs ⟹ T a (w # zs) ((a # w) # zs)
| T1 [Pure.intro]: T a ws zs ⟹ T a (w # ws) ((a # w) # zs)
| T2 [Pure.intro]: a ≠ b ⟹ T a ws zs ⟹ T a ws ((b # w) # zs)

inductive bar :: letter list list ⇒ bool
where
  bar1 [Pure.intro]: good ws ⟹ bar ws
| bar2 [Pure.intro]: (⋀w. bar (w # ws)) ⟹ bar ws

theorem prop1: bar ([] # ws)
  ⟨proof⟩

theorem lemma1: L as ws ⟹ L (a # as) ws
  ⟨proof⟩

lemma lemma2': R a vs ws ⟹ L as vs ⟹ L (a # as) ws
  ⟨proof⟩

lemma lemma2: R a vs ws ⟹ good vs ⟹ good ws
  ⟨proof⟩

lemma lemma3': T a vs ws ⟹ L as vs ⟹ L (a # as) ws
  ⟨proof⟩

lemma lemma3: T a ws zs ⟹ good ws ⟹ good zs
```

⟨*proof*⟩

lemma *lemma4*: $R\ a\ ws\ zs \Longrightarrow ws \neq [] \Longrightarrow T\ a\ ws\ zs$
⟨*proof*⟩

lemma *letter-neq*: $a \neq b \Longrightarrow c \neq a \Longrightarrow c = b$ **for** $a\ b\ c :: letter$
⟨*proof*⟩

lemma *letter-eq-dec*: $a = b \vee a \neq b$ **for** $a\ b :: letter$
⟨*proof*⟩

theorem *prop2*:
assumes *ab*: $a \neq b$ **and** *bar*: *bar xs*
shows $\bigwedge ys\ zs.\ bar\ ys \Longrightarrow T\ a\ xs\ zs \Longrightarrow T\ b\ ys\ zs \Longrightarrow bar\ zs$
⟨*proof*⟩

theorem *prop3*:
assumes *bar*: *bar xs*
shows $\bigwedge zs.\ xs \neq [] \Longrightarrow R\ a\ xs\ zs \Longrightarrow bar\ zs$
⟨*proof*⟩

theorem *higman*: *bar* []
⟨*proof*⟩

primrec *is-prefix* :: $'a\ list \Rightarrow (nat \Rightarrow 'a) \Rightarrow bool$
where
is-prefix [] f = *True*
| *is-prefix* $(x \#\ xs)\ f = (x = f\ (length\ xs) \wedge is\text{-}prefix\ xs\ f)$

theorem *L-idx*:
assumes *L*: *L w ws*
shows *is-prefix ws f* $\Longrightarrow \exists i.\ emb\ (f\ i)\ w \wedge i < length\ ws$
⟨*proof*⟩

theorem *good-idx*:
assumes *good*: *good ws*
shows *is-prefix ws f* $\Longrightarrow \exists i\ j.\ emb\ (f\ i)\ (f\ j) \wedge i < j$
⟨*proof*⟩

theorem *bar-idx*:
assumes *bar*: *bar ws*
shows *is-prefix ws f* $\Longrightarrow \exists i\ j.\ emb\ (f\ i)\ (f\ j) \wedge i < j$
⟨*proof*⟩

Strong version: yields indices of words that can be embedded into each other.

theorem *higman-idx*: $\exists (i::nat)\ j.\ emb\ (f\ i)\ (f\ j) \wedge i < j$
⟨*proof*⟩

Weak version: only yield sequence containing words that can be embedded

into each other.

theorem *good-prefix-lemma*:
assumes *bar*: *bar ws*
shows *is-prefix ws f* $\Longrightarrow \exists$ *vs. is-prefix vs f* $\wedge$ *good vs*
⟨*proof*⟩

theorem *good-prefix*: $\exists$ *vs. is-prefix vs f* $\wedge$ *good vs*
⟨*proof*⟩

end

5.1 Extracting the program

theory *Higman-Extraction*
imports *Higman HOL−Library.Realizers HOL−Library.Open-State-Syntax*
begin

declare *R.induct* [*ind-realizer*]
declare *T.induct* [*ind-realizer*]
declare *L.induct* [*ind-realizer*]
declare *good.induct* [*ind-realizer*]
declare *bar.induct* [*ind-realizer*]

extract *higman-idx*

Program extracted from the proof of *higman-idx*:

higman-idx $\equiv \lambda x.$ *bar-idx x higman*

Corresponding correctness theorem:

emb (*f* (*fst* (*higman-idx f*))) (*f* (*snd* (*higman-idx f*))) $\wedge$
fst (*higman-idx f*) $<$ *snd* (*higman-idx f*)

Program extracted from the proof of *higman*:

higman $\equiv$
bar2 [] (*rec-list* (*prop1* []) ($\lambda a\ w\ H.$ *prop3 a* [*a* # *w*] *H* (*R1* [] [] *w R0*)))

Program extracted from the proof of *prop1*:

prop1 $\equiv$
$\lambda x.$ *bar2* ([] # *x*) ($\lambda w.$ *bar1* (*w* # [] # *x*) (*good0 w* ([] # *x*) (*L0* [] *x*)))

Program extracted from the proof of *prop2*:

prop2 $\equiv$
$\lambda x\ xa\ xb\ xc\ H.$
compat-barT.rec-split-barT
($\lambda ws\ xa\ xb\ xba\ H\ Ha\ Haa.$ *bar1 xba* (*lemma3 x Ha xa*))

```
(λws xb r xba xbb H.
    compat-barT.rec-split-barT (λws x xb H Ha. bar1 xb (lemma3 xa Ha x))
     (λwsa xb ra xc H Ha.
         bar2 xc
          (λw. case w of [] ⇒ prop1 xc
                | a # list ⇒
                    case letter-eq-dec a x of
                    Left ⇒
                      r list wsa ((x # list) # xc) (bar2 wsa xb)
                       (T1 ws xc list H) (T2 x wsa xc list Ha)
                    | Right ⇒
                        ra list ((xa # list) # xc) (T2 xa ws xc list H)
                         (T1 wsa xc list Ha)))
      H xbb)
  H xb xc
```

Program extracted from the proof of *prop3*:

```
prop3 ≡
λx xa H.
  compat-barT.rec-split-barT (λws xa xb H. bar1 xb (lemma2 x H xa))
   (λws xa r xb H.
       bar2 xb
        (rec-list (prop1 xb)
          (λa w Ha.
              case letter-eq-dec a x of
              Left ⇒ r w ((x # w) # xb) (R1 ws xb w H)
              | Right ⇒
                  prop2 a x ws ((a # w) # xb) Ha (bar2 ws xa)
                   (T0 x ws xb w H) (T2 a ws xb w (lemma4 x H)))))
  H xa
```

5.2 Some examples

```
instantiation LT and TT :: default
begin

definition default = L0 [] []

definition default = T0 A [] [] [] R0

instance ⟨proof⟩

end

function mk-word-aux :: nat ⇒ Random.seed ⇒ letter list × Random.seed
where
  mk-word-aux k = exec {
    i ← Random.range 10;
```

```
    (if i > 7 ∧ k > 2 ∨ k > 1000 then Pair []
     else exec {
       let l = (if i mod 2 = 0 then A else B);
       ls ← mk-word-aux (Suc k);
       Pair (l # ls)
     })}
  ⟨proof⟩
termination
  ⟨proof⟩

definition mk-word :: Random.seed ⇒ letter list × Random.seed
  where mk-word = mk-word-aux 0

primrec mk-word-s :: nat ⇒ Random.seed ⇒ letter list × Random.seed
where
  mk-word-s 0 = mk-word
| mk-word-s (Suc n) = exec {
    - ← mk-word;
    mk-word-s n
  }

definition g1 :: nat ⇒ letter list
  where g1 s = fst (mk-word-s s (20000, 1))

definition g2 :: nat ⇒ letter list
  where g2 s = fst (mk-word-s s (50000, 1))

fun f1 :: nat ⇒ letter list
where
  f1 0 = [A, A]
| f1 (Suc 0) = [B]
| f1 (Suc (Suc 0)) = [A, B]
| f1 - = []

fun f2 :: nat ⇒ letter list
where
  f2 0 = [A, A]
| f2 (Suc 0) = [B]
| f2 (Suc (Suc 0)) = [B, A]
| f2 - = []

⟨ML⟩

end
```

6 The pigeonhole principle

```
theory Pigeonhole
imports Util HOL−Library.Realizers HOL−Library.Code-Target-Numeral
```

begin

We formalize two proofs of the pigeonhole principle, which lead to extracted programs of quite different complexity. The original formalization of these proofs in NUPRL is due to Aleksey Nogin [3].

This proof yields a polynomial program.

theorem *pigeonhole*:
$\bigwedge f.\ (\bigwedge i.\ i \le Suc\ n \Longrightarrow f\ i \le n) \Longrightarrow \exists\, i\ j.\ i \le Suc\ n \wedge j < i \wedge f\ i = f\ j$
⟨*proof*⟩

The following proof, although quite elegant from a mathematical point of view, leads to an exponential program:

theorem *pigeonhole-slow*:
$\bigwedge f.\ (\bigwedge i.\ i \le Suc\ n \Longrightarrow f\ i \le n) \Longrightarrow \exists\, i\ j.\ i \le Suc\ n \wedge j < i \wedge f\ i = f\ j$
⟨*proof*⟩

extract *pigeonhole pigeonhole-slow*

The programs extracted from the above proofs look as follows:

```
pigeonhole ≡
λx. nat-induct-P x (λx. (Suc 0, 0))
      (λx H2 xa.
          nat-induct-P (Suc (Suc x)) default
           (λx H2.
               case search (Suc x) (λxb. nat-eq-dec (xa (Suc x)) (xa xb)) of
               None ⇒ let (x, y) = H2 in (x, y) | Some p ⇒ (Suc x, p)))
```

```
pigeonhole-slow ≡
λx. nat-induct-P x (λx. (Suc 0, 0))
      (λx H2 xa.
          case search (Suc (Suc x))
                (λxb. nat-eq-dec (xa (Suc (Suc x))) (xa xb)) of
          None ⇒
            let (x, y) =
                  H2 (λi. if xa i = Suc x then xa (Suc (Suc x)) else xa i)
            in (x, y)
          | Some p ⇒ (Suc (Suc x), p))
```

The program for searching for an element in an array is

```
search ≡
λx H. nat-induct-P x None
        (λy Ha.
            case Ha of None ⇒ case H y of Left ⇒ Some y | Right ⇒ None
            | Some p ⇒ Some p)
```

The correctness statement for *pigeonhole* is

$(\bigwedge i.\ i \leq Suc\ n \Longrightarrow f\ i \leq n) \Longrightarrow$
$fst\ (pigeonhole\ n\ f) \leq Suc\ n \wedge$
$snd\ (pigeonhole\ n\ f) < fst\ (pigeonhole\ n\ f) \wedge$
$f\ (fst\ (pigeonhole\ n\ f)) = f\ (snd\ (pigeonhole\ n\ f))$

In order to analyze the speed of the above programs, we generate ML code from them.

instantiation *nat* :: *default*
begin

definition *default* = (*0*::*nat*)

instance ⟨*proof*⟩

end

instantiation *prod* :: (*default*, *default*) *default*
begin

definition *default* = (*default*, *default*)

instance ⟨*proof*⟩

end

definition *test n u* = *pigeonhole* (*nat-of-integer n*) (λ*m*. *m* − *1*)
definition *test′ n u* = *pigeonhole-slow* (*nat-of-integer n*) (λ*m*. *m* − *1*)
definition *test″ u* = *pigeonhole 8* (*List.nth* [*0*, *1*, *2*, *3*, *4*, *5*, *6*, *3*, *7*, *8*])

⟨*ML*⟩

end

7 Euclid's theorem

theory *Euclid*
imports
HOL−Computational-Algebra.Primes
Util
HOL−Library.Code-Target-Numeral
HOL−Library.Realizers
begin

A constructive version of the proof of Euclid's theorem by Markus Wenzel and Freek Wiedijk [4].

lemma *factor-greater-one1*: $n = m * k \Longrightarrow m < n \Longrightarrow k < n \Longrightarrow Suc\ 0 < m$
⟨*proof*⟩

lemma *factor-greater-one2*: $n = m * k \Longrightarrow m < n \Longrightarrow k < n \Longrightarrow Suc\ 0 < k$
⟨*proof*⟩

lemma *prod-mn-less-k*: $0 < n \Longrightarrow 0 < k \Longrightarrow Suc\ 0 < m \Longrightarrow m * n = k \Longrightarrow n < k$
⟨*proof*⟩

lemma *prime-eq*: $prime\ (p::nat) \longleftrightarrow 1 < p \wedge (\forall m.\ m\ dvd\ p \longrightarrow 1 < m \longrightarrow m = p)$
⟨*proof*⟩

lemma *prime-eq'*: $prime\ (p::nat) \longleftrightarrow 1 < p \wedge (\forall m\ k.\ p = m * k \longrightarrow 1 < m \longrightarrow m = p)$
⟨*proof*⟩

lemma *not-prime-ex-mk*:
assumes n: $Suc\ 0 < n$
shows $(\exists m\ k.\ Suc\ 0 < m \wedge Suc\ 0 < k \wedge m < n \wedge k < n \wedge n = m * k) \vee prime\ n$
⟨*proof*⟩

lemma *dvd-factorial*: $0 < m \Longrightarrow m \leq n \Longrightarrow m\ dvd\ fact\ n$
⟨*proof*⟩

lemma *dvd-prod* [*iff*]: $n\ dvd\ (\prod m::nat \in\# mset\ (n\ \#\ ns).\ m)$
⟨*proof*⟩

definition *all-prime* :: *nat list* ⇒ *bool*
where $all\text{-}prime\ ps \longleftrightarrow (\forall p \in set\ ps.\ prime\ p)$

lemma *all-prime-simps*:
all-prime []
$all\text{-}prime\ (p\ \#\ ps) \longleftrightarrow prime\ p \wedge all\text{-}prime\ ps$
⟨*proof*⟩

lemma *all-prime-append*: $all\text{-}prime\ (ps\ @\ qs) \longleftrightarrow all\text{-}prime\ ps \wedge all\text{-}prime\ qs$
⟨*proof*⟩

lemma *split-all-prime*:
assumes *all-prime ms* **and** *all-prime ns*
shows $\exists qs.\ all\text{-}prime\ qs \wedge$
$(\prod m::nat \in\# mset\ qs.\ m) = (\prod m::nat \in\# mset\ ms.\ m) * (\prod m::nat \in\# mset\ ns.\ m)$
(**is** $\exists qs.\ ?P\ qs \wedge ?Q\ qs$)
⟨*proof*⟩

lemma *all-prime-nempty-g-one*:
assumes *all-prime ps* **and** $ps \neq []$
shows $Suc\ 0 < (\prod m::nat \in\# mset\ ps.\ m)$

⟨*proof*⟩

lemma *factor-exists*: *Suc 0* < *n* ⟹ (∃ *ps*. *all-prime ps* ∧ (∏ *m*::*nat* ∈# *mset ps*. *m*) = *n*)
⟨*proof*⟩

lemma *prime-factor-exists*:
  assumes *N*: (*1*::*nat*) < *n*
  shows ∃ *p*. *prime p* ∧ *p dvd n*
⟨*proof*⟩

Euclid's theorem: there are infinitely many primes.

lemma *Euclid*: ∃ *p*::*nat*. *prime p* ∧ *n* < *p*
⟨*proof*⟩

extract *Euclid*

The program extracted from the proof of Euclid's theorem looks as follows.

Euclid ≡ λ*x*. *prime-factor-exists* (*fact x* + *1*)

The program corresponding to the proof of the factorization theorem is

```
factor-exists ≡
λx. nat-wf-ind-P x
      (λx H2.
          case not-prime-ex-mk x of None ⇒ [x]
          | Some p ⇒ let (x, y) = p in split-all-prime (H2 x) (H2 y))
```

instantiation *nat* :: *default*
begin

definition *default* = (*0*::*nat*)

instance ⟨*proof*⟩

end

instantiation *list* :: (*type*) *default*
begin

definition *default* = []

instance ⟨*proof*⟩

end

primrec *iterate* :: *nat* ⇒ ('*a* ⇒ '*a*) ⇒ '*a* ⇒ '*a list*
where

```
  iterate 0 f x = []
| iterate (Suc n) f x = (let y = f x in y # iterate n f y)

lemma factor-exists 1007 = [53, 19] ⟨proof⟩
lemma factor-exists 567 = [7, 3, 3, 3, 3] ⟨proof⟩
lemma factor-exists 345 = [23, 5, 3] ⟨proof⟩
lemma factor-exists 999 = [37, 3, 3, 3] ⟨proof⟩
lemma factor-exists 876 = [73, 3, 2, 2] ⟨proof⟩

lemma iterate 4 Euclid 0 = [2, 3, 7, 71] ⟨proof⟩

end
```

References

[1] U. Berger, H. Schwichtenberg, and M. Seisenberger. The Warshall algorithm and Dickson's lemma: Two examples of realistic program extraction. *Journal of Automated Reasoning*, 26:205–221, 2001.

[2] T. Coquand and D. Fridlender. A proof of Higman's lemma by structural induction. Technical report, Chalmers University, November 1993.

[3] A. Nogin. Writing constructive proofs yielding efficient extracted programs. In D. Galmiche, editor, *Proceedings of the Workshop on Type-Theoretic Languages: Proof Search and Semantics*, volume 37 of *Electronic Notes in Theoretical Computer Science*. Elsevier Science Publishers, 2000.

[4] M. Wenzel and F. Wiedijk. A comparison of the mathematical proof languages Mizar and Isar. *Journal of Automated Reasoning*, 29(3-4):389–411, 2002.