IMP in HOLCF

Tobias Nipkow and Robert Sandner

October 24, 2026

Contents

1 Denotational Semantics of Commands in HOLCF **1**
1.1 Definition 1
1.2 Equivalence of Denotational Semantics in HOLCF and Evaluation Semantics in HOL 1

2 Correctness of Hoare by Fixpoint Reasoning **2**

1 Denotational Semantics of Commands in HOLCF

theory *Denotational* **imports** *HOLCF "HOL-IMP.Big_Step"* **begin**

1.1 Definition

definition
```
  dlift :: "(('a::type) discr -> 'b::pcpo) => ('a lift -> 'b)" where
  "dlift f = (LAM x. case x of UU ⇒ UU | Def y ⇒ f·(Discr y))"
```

primrec *D :: "com ⇒ state discr → state lift"*
where
```
  "D(SKIP) = (LAM s. Def(undiscr s))"
| "D(X ::= a) = (LAM s. Def((undiscr s)(X := aval a (undiscr s))))"
| "D(c0 ;; c1) = (dlift(D c1) oo (D c0))"
| "D(IF b THEN c1 ELSE c2) =
       (LAM s. if bval b (undiscr s) then (D c1)·s else (D c2)·s)"
| "D(WHILE b DO c) =
       fix·(LAM w s. if bval b (undiscr s) then (dlift w)·((D c)·s)
                     else Def(undiscr s))"
```

1.2 Equivalence of Denotational Semantics in HOLCF and Evaluation Semantics in HOL

lemma *dlift_Def [simp]: "dlift f·(Def x) = f·(Discr x)"*
⟨*proof*⟩

lemma *cont_dlift [iff]: "cont (%f. dlift f)"*
⟨*proof*⟩

lemma *dlift_is_Def [simp]:*
"(dlift f·l = Def y) = (∃ x. l = Def x ∧ f·(Discr x) = Def y)"
⟨*proof*⟩

lemma *eval_implies_D: "(c,s) ⇒ t ⟹ D c·(Discr s) = (Def t)"*
⟨*proof*⟩

lemma *D_implies_eval: "∀ s t. D c·(Discr s) = (Def t) ⟶ (c,s) ⇒ t"*
⟨*proof*⟩

theorem *D_is_eval: "(D c·(Discr s) = (Def t)) = ((c,s) ⇒ t)"*
⟨*proof*⟩

end

2 Correctness of Hoare by Fixpoint Reasoning

theory *HoareEx* **imports** *Denotational* **begin**

An example from the HOLCF paper by Müller, Nipkow, Oheimb, Slotosch [1]. It demonstrates fixpoint reasoning by showing the correctness of the Hoare rule for while-loops.

type_synonym *assn = "state ⇒ bool"*

definition
hoare_valid :: "[assn, com, assn] ⇒ bool" (‹|= {(1_)}/ (_)/ {(1_)}› 50) **where**
"|= {P} c {Q} = (∀ s t. P s ∧ D c·(Discr s) = Def t ⟶ Q t)"

lemma *WHILE_rule_sound:*
"|= {A} c {A} ⟹ |= {A} WHILE b DO c {λs. A s ∧ ¬ bval b s}"
⟨*proof*⟩

end

References

[1] O. Müller, T. Nipkow, D. v. Oheimb, and O. Slotosch. HOLCF = HOL + LCF. *J. Functional Programming*, 9:191–223, 1999.