

Some aspects of Unix file-system security

Markus Wenzel
TU München

May 23, 2024

Abstract

Unix is a simple but powerful system where everything is either a process or a file. Access to system resources works mainly via the file-system, including special files and devices. Most Unix security issues are reflected directly within the file-system. We give a mathematical model of the main aspects of the Unix file-system including its security model, but ignoring processes. Within this formal model we discuss some aspects of Unix security, including a few odd effects caused by the general “worse-is-better” approach followed in Unix.

Our formal specifications will be given in simply-typed classical set-theory as provided by Isabelle/HOL. Formal proofs are expressed in a human-readable fashion using the structured proof language of Isabelle/Isar, which is a system intended to support intelligible semi-automated reasoning over a wide range of application domains. Thus the present development also demonstrates that Isabelle/Isar is sufficiently flexible to cover typical abstract verification tasks as well. So far this has been the classical domain of interactive theorem proving systems based on unstructured tactic languages.

Contents

1	Introduction	3
1.1	The Unix philosophy	3
1.2	Unix security	4
1.3	Odd effects	4
2	Unix file-systems	6
2.1	Names	6
2.2	Attributes	7
2.3	Files	7
2.4	Initial file-systems	9
2.5	Accessing file-systems	9

3	File-system transitions	10
3.1	Unix system calls	10
3.2	Basic properties of single transitions	13
3.3	Iterated transitions	14
4	Executable sequences	16
4.1	Possible transitions	16
4.2	Example executions	17
5	Odd effects — treated formally	20
5.1	The general procedure	20
5.2	The particular situation	21
5.3	Invariance lemmas	21
5.4	Putting it all together	26

1 Introduction

1.1 The Unix philosophy

Over the last 2 or 3 decades the Unix community has collected a certain amount of folklore wisdom on building systems that actually work, see [6] for further historical background information. Here is a recent account of the philosophical principles behind the Unix way of software and systems engineering.¹

The UNIX Philosophy (Score:2, Insightful)
by yebb on Saturday March 25, @11:06AM EST (#69)
(User Info)

The philosophy is a result of more than twenty years of software development and has grown from the UNIX community instead of being enforced upon it. It is a defacto-style of software development. The nine major tenets of the UNIX Philosophy are:

1. small is beautiful
2. make each program do one thing well
3. build a prototype as soon as possible
4. choose portability over efficiency
5. store numerical data in flat files
6. use software leverage to your advantage
7. use shell scripts to increase leverage and portability
8. avoid captive user interfaces
9. make every program a filter

The Ten Lesser Tenets

1. allow the user to tailor the environment
2. make operating system kernels small and lightweight
3. use lower case and keep it short
4. save trees
5. silence is golden
6. think parallel
7. the sum of the parts if greater than the whole
8. look for the ninety percent solution
9. worse is better
10. think hierarchically

The “worse-is-better” approach quoted above is particularly interesting. It basically means that *relevant* concepts have to be implemented in the right way, while *irrelevant* issues are simply ignored in order to avoid unnecessary complication of the design and implementation. Certainly, the overall

¹This has appeared on *Slashdot* on 25-March-2000, see <http://slashdot.com>.

quality of the resulting system heavily depends on the virtue of distinction between the two categories of “relevant” and “irrelevant”.

1.2 Unix security

The main entities of a Unix system are *files* and *processes* [4]. Files subsume any persistent “static” entity managed by the system — ranging from plain files and directories, to more special ones such device nodes, pipes etc. On the other hand, processes are “dynamic” entities that may perform certain operations while being run by the system.

The security model of classic Unix systems is centered around the file system. The operations permitted by a process that is run by a certain user are determined from information stored within the file system. This includes any kind of access control, such as read/write access to some plain file, or read-only access to a certain global device node etc. Thus proper arrangement of the main Unix file-system is very critical for overall security.²

Generally speaking, the Unix security model is a very simplistic one. The original designers did not have maximum security in mind, but wanted to get a decent system working for typical multi-user environments. Contemporary Unix implementations still follow the basic security model of the original versions from the early 1970’s [6]. Even back then there would have been better approaches available, albeit with more complexity involved both for implementers and users.

On the other hand, even in the 2000’s many computer systems are run with little or no file-system security at all, even though virtually any system is exposed to the net in one way or the other. Even “personal” computer systems have long left the comfortable home environment and entered the wilderness of the open net sphere.

This treatment of file-system security is a typical example of the “worse-is-better” principle introduced above. The simplistic security model of Unix got widely accepted within a large user community, while the more innovative (and cumbersome) ones are only used very reluctantly and even tend to be disabled by default in order to avoid confusion of beginners.

1.3 Odd effects

Simplistic systems usually work very well in typical situations, but tend to exhibit some odd features in non-typical ones. As far as Unix file-system security is concerned, there are many such features that are well-known to experts, but may surprise naive users.

²Incidentally, this is why the operation of mounting new volumes into the existing file space is usually restricted to the super-user.

Subsequently, we consider an example that is not so exotic after all. As may be easily experienced on a running Unix system, the following sequence of commands may put a user's file-system into an uncouth state. Below we assume that `user1` and `user2` are working within the same directory (e.g. somewhere within the home of `user1`).

```
user1> umask 000; mkdir foo; umask 022
user2> mkdir foo/bar
user2> touch foo/bar/baz
```

That is, `user1` creates a directory that is writable for everyone, and `user2` puts there a non-empty directory without write-access for others.

In this situation it has become impossible for `user1` to remove his very own directory `foo` without the cooperation of either `user2`, since `foo` contains another non-empty and non-writable directory, which cannot be removed.

```
user1> rmdir foo
rmdir: directory "foo": Directory not empty
user1> rmdir foo/bar
rmdir: directory "bar": Directory not empty
user1> rm foo/bar/baz
rm not removed: Permission denied
```

Only after `user2` has cleaned up his directory `bar`, is `user1` enabled to remove both `foo/bar` and `foo`. Alternatively `user2` could remove `foo/bar` as well. In the unfortunate case that `user2` does not cooperate or is presently unavailable, `user1` would have to find the super user (`root`) to clean up the situation. In Unix `root` may perform any file-system operation without any access control limitations.³

Is there really no other way out for `user1` in the above situation? Experiments can only show possible ways, but never demonstrate the absence of other means exhaustively. This is a typical situation where (formal) proof may help. Subsequently, we model the main aspects Unix file-system security within Isabelle/HOL [3] and prove that there is indeed no way for `user1` to get rid of his directory `foo` without help by others (see §5.4 for the main theorem stating this).

The formal techniques employed in this development are the typical ones for abstract “verification” tasks, namely induction and case analysis over the structure of file-systems and possible system transitions. Isabelle/HOL

³This is the typical Unix way of handling abnormal situations: while it is easy to run into odd cases due to simplistic policies it is as well quite easy to get out. There are other well-known systems that make it somewhat harder to get into a fix, but almost impossible to get out again!

[3] is particularly well-suited for this kind of application. By the present development we also demonstrate that the Isabelle/Isar environment [7, 8] for readable formal proofs is sufficiently flexible to cover non-trivial verification tasks as well. So far this has been the classical domain of “interactive” theorem proving systems based on unstructured tactic languages.

2 Unix file-systems

```

theory Unix
  imports
    Nested-Environment
    HOL-Library.Sublist
begin

```

We give a simple mathematical model of the basic structures underlying the Unix file-system, together with a few fundamental operations that could be imagined to be performed internally by the Unix kernel. This forms the basis for the set of Unix system-calls to be introduced later (see §3), which are the actual interface offered to processes running in user-space.

Basically, any Unix file is either a *plain file* or a *directory*, consisting of some *content* plus *attributes*. The content of a plain file is plain text. The content of a directory is a mapping from names to further files.⁴ Attributes include information to control various ways to access the file (read, write etc.).

Our model will be quite liberal in omitting excessive detail that is easily seen to be “irrelevant” for the aspects of Unix file-systems to be discussed here. First of all, we ignore character and block special files, pipes, sockets, hard links, symbolic links, and mount points.

2.1 Names

User ids and file name components shall be represented by natural numbers (without loss of generality). We do not bother about encoding of actual names (e.g. strings), nor a mapping between user names and user ids as would be present in a reality.

```

type-synonym uid = nat
type-synonym name = nat
type-synonym path = name list

```

⁴In fact, this is the only way that names get associated with files. In Unix files do *not* have a name in itself. Even more, any number of names may be associated with the very same file due to *hard links* (although this is excluded from our model).

2.2 Attributes

Unix file attributes mainly consist of *owner* information and a number of *permission* bits which control access for “user”, “group”, and “others” (see the Unix man pages *chmod(2)* and *stat(2)* for more details).

Our model of file permissions only considers the “others” part. The “user” field may be omitted without loss of overall generality, since the owner is usually able to change it anyway by performing *chmod*.⁵ We omit “group” permissions as a genuine simplification as we just do not intend to discuss a model of multiple groups and group membership, but pretend that everyone is member of a single global group.⁶

```
datatype perm =  
  Readable  
  | Writable  
  | Executable — (ignored)
```

```
type-synonym perms = perm set
```

```
record att =  
  owner :: uid  
  others :: perms
```

For plain files *Readable* and *Writable* specify read and write access to the actual content, i.e. the string of text stored here. For directories *Readable* determines if the set of entry names may be accessed, and *Writable* controls the ability to create or delete any entries (both plain files or sub-directories).

As another simplification, we ignore the *Executable* permission altogether. In reality it would indicate executable plain files (also known as “binaries”), or control actual lookup of directory entries (recall that mere directory browsing is controlled via *Readable*). Note that the latter means that in order to perform any file-system operation whatsoever, all directories encountered on the path would have to grant *Executable*. We ignore this detail and pretend that all directories give *Executable* permission to anybody.

2.3 Files

In order to model the general tree structure of a Unix file-system we use the arbitrarily branching datatype $(\prime a, \prime b, \prime c)$ *env* from the standard library of Isabelle/HOL [1]. This type provides constructors *Val* and *Env* as follows:

```
Val ::  $\prime a \Rightarrow (\prime a, \prime b, \prime c)$  env  
Env ::  $\prime b \Rightarrow (\prime c \Rightarrow (\prime a, \prime b, \prime c)$  env option)  $\Rightarrow (\prime a, \prime b, \prime c)$  env
```

⁵The inclined Unix expert may try to figure out some exotic arrangements of a real-world Unix file-system such that the owner of a file is unable to apply the *chmod* system call.

⁶A general HOL model of user group structures and related issues is given in [2].

Here the parameter $'a$ refers to plain values occurring at leaf positions, parameter $'b$ to information kept with inner branch nodes, and parameter $'c$ to the branching type of the tree structure. For our purpose we use the type instance with $att \times string$ (representing plain files), att (for attributes of directory nodes), and $name$ (for the index type of directory nodes).

type-synonym $file = (att \times string, att, name) env$

The HOL library also provides *lookup* and *update* operations for general tree structures with the subsequent primitive recursive characterizations.

$$\begin{aligned} lookup &:: ('a, 'b, 'c) env \Rightarrow 'c list \Rightarrow ('a, 'b, 'c) env option \\ update &:: 'c list \Rightarrow ('a, 'b, 'c) env option \Rightarrow ('a, 'b, 'c) env \Rightarrow ('a, 'b, 'c) env \end{aligned}$$

$$\begin{aligned} lookup\ env\ xs &= \\ (case\ xs\ of\ [] &\Rightarrow Some\ env \\ | x\ \#\ xs &\Rightarrow \\ &case\ env\ of\ Val\ a \Rightarrow None \\ &| Env\ b\ es \Rightarrow case\ es\ x\ of\ None \Rightarrow None\ |\ Some\ e \Rightarrow lookup\ e\ xs) \end{aligned}$$

$$\begin{aligned} update\ xs\ opt\ env &= \\ (case\ xs\ of\ [] &\Rightarrow case\ opt\ of\ None \Rightarrow env\ |\ Some\ e \Rightarrow e \\ | x\ \#\ xs &\Rightarrow \\ &case\ env\ of\ Val\ a \Rightarrow Val\ a \\ &| Env\ b\ es \Rightarrow \\ &case\ xs\ of\ [] \Rightarrow Env\ b\ (es(x := opt)) \\ &| y\ \#\ ys \Rightarrow \\ &Env\ b \\ &(es(x := case\ es\ x\ of\ None \Rightarrow None \\ &| Some\ e \Rightarrow Some\ (update\ (y\ \#\ ys)\ opt\ e)))) \end{aligned}$$

Several further properties of these operations are proven in [1]. These will be routinely used later on without further notice.

Apparently, the elements of type *file* contain an *att* component in either case. We now define a few auxiliary operations to manipulate this field uniformly, following the conventions for record types in Isabelle/HOL [3].

definition

$$\begin{aligned} attributes\ file &= \\ (case\ file\ of \\ &Val\ (att, text) \Rightarrow att \\ &| Env\ att\ dir \Rightarrow att) \end{aligned}$$

definition

$$\begin{aligned} map\ attributes\ f\ file &= \\ (case\ file\ of \\ &Val\ (att, text) \Rightarrow Val\ (f\ att, text) \\ &| Env\ att\ dir \Rightarrow Env\ (f\ att)\ dir) \end{aligned}$$

lemma [*simp*]: $attributes (Val (att, text)) = att$
by (*simp add: attributes-def*)

lemma [*simp*]: $attributes (Env att dir) = att$
by (*simp add: attributes-def*)

lemma [*simp*]: $attributes (map-attributes f file) = f (attributes file)$
by (*cases file*) (*simp-all add: attributes-def map-attributes-def split-tupled-all*)

lemma [*simp*]: $map-attributes f (Val (att, text)) = Val (f att, text)$
by (*simp add: map-attributes-def*)

lemma [*simp*]: $map-attributes f (Env att dir) = Env (f att) dir$
by (*simp add: map-attributes-def*)

2.4 Initial file-systems

Given a set of *known users* a file-system shall be initialized by providing an empty home directory for each user, with read-only access for everyone else. (Note that we may directly use the user id as home directory name, since both types have been identified.) Certainly, the very root directory is owned by the super user (who has user id 0).

definition

init users =
 $Env (\{owner = 0, others = \{Readable\}\})$
 $(\lambda u. \text{if } u \in \text{users then } Some (Env (\{owner = u, others = \{Readable\}\}))$
 $Map.empty$
 $\text{else } None)$

2.5 Accessing file-systems

The main internal file-system operation is access of a file by a user, requesting a certain set of permissions. The resulting *file option* indicates if a file had been present at the corresponding *path* and if access was granted according to the permissions recorded within the file-system.

Note that by the rules of Unix file-system security (e.g. [4]) both the super-user and owner may always access a file unconditionally (in our simplified model).

definition

access root path uid perms =
 $(\text{case lookup root path of}$
 $None \Rightarrow None$
 $| Some file \Rightarrow$
 $\text{if } uid = 0$
 $\vee uid = owner (attributes file)$

$\vee perms \subseteq others$ (*attributes file*)
 then *Some file*
 else *None*)

Successful access to a certain file is the main prerequisite for system-calls to be applicable (cf. §3). Any modification of the file-system is then performed using the basic *update* operation.

We see that *access* is just a wrapper for the basic *lookup* function, with additional checking of attributes. Subsequently we establish a few auxiliary facts that stem from the primitive *lookup* used within *access*.

lemma *access-empty-lookup*: $access\ root\ path\ uid\ \{\} = lookup\ root\ path$
 by (*simp add: access-def split: option.splits*)

lemma *access-some-lookup*:
 $access\ root\ path\ uid\ perms = Some\ file \implies$
 $lookup\ root\ path = Some\ file$
 by (*simp add: access-def split: option.splits if-splits*)

lemma *access-update-other*:
assumes *parallel*: $path' \parallel path$
shows $access\ (update\ path'\ opt\ root)\ path\ uid\ perms = access\ root\ path\ uid\ perms$
proof –
from *parallel* **obtain** $y\ z\ xs\ ys\ zs$ **where**
 $y \neq z$ **and** $path' = xs @ y \# ys$ **and** $path = xs @ z \# zs$
by (*blast dest: parallel-decomp*)
then have $lookup\ (update\ path'\ opt\ root)\ path = lookup\ root\ path$
by (*blast intro: lookup-update-other*)
then show *?thesis* **by** (*simp only: access-def*)
qed

3 File-system transitions

3.1 Unix system calls

According to established operating system design (cf. [4]) user space processes may only initiate system operations by a fixed set of *system-calls*. This enables the kernel to enforce certain security policies in the first place.⁷

In our model of Unix we give a fixed datatype *operation* for the syntax of system-calls, together with an inductive definition of file-system state transitions of the form $root -x \rightarrow root'$ for the operational semantics.

datatype *operation* =

⁷Incidentally, this is the very same principle employed by any “LCF-style” theorem proving system according to Milner’s principle of “correctness by construction”, such as Isabelle/HOL itself.

```

    Read uid string path
  | Write uid string path
  | Chmod uid perms path
  | Creat uid perms path
  | Unlink uid path
  | Mkdir uid perms path
  | Rmdir uid path
  | Readdir uid name set path

```

The *uid* field of an operation corresponds to the *effective user id* of the underlying process, although our model never mentions processes explicitly. The other parameters are provided as arguments by the caller; the *path* one is common to all kinds of system-calls.

primrec *uid-of* :: operation ⇒ uid

where

```

    uid-of (Read uid text path) = uid
  | uid-of (Write uid text path) = uid
  | uid-of (Chmod uid perms path) = uid
  | uid-of (Creat uid perms path) = uid
  | uid-of (Unlink uid path) = uid
  | uid-of (Mkdir uid path perms) = uid
  | uid-of (Rmdir uid path) = uid
  | uid-of (Readdir uid names path) = uid

```

primrec *path-of* :: operation ⇒ path

where

```

    path-of (Read uid text path) = path
  | path-of (Write uid text path) = path
  | path-of (Chmod uid perms path) = path
  | path-of (Creat uid perms path) = path
  | path-of (Unlink uid path) = path
  | path-of (Mkdir uid perms path) = path
  | path-of (Rmdir uid path) = path
  | path-of (Readdir uid names path) = path

```

Note that we have omitted explicit *Open* and *Close* operations, pretending that *Read* and *Write* would already take care of this behind the scenes. Thus we have basically treated actual sequences of real system-calls *open-read/write-close* as atomic.

In principle, this could make big a difference in a model with explicit concurrent processes. On the other hand, even on a real Unix system the exact scheduling of concurrent *open* and *close* operations does *not* directly affect the success of corresponding *read* or *write*. Unix allows several processes to have files opened at the same time, even for writing! Certainly, the result from reading the contents later may be hard to predict, but the system-calls involved here will succeed in any case.

The operational semantics of system calls is now specified via transitions of the file-system configuration. This is expressed as an inductive relation (although there is no actual recursion involved here).

```

inductive transition :: file ⇒ operation ⇒ file ⇒ bool
  (- ----> - [90, 1000, 90] 100)
where
  read:
    root -(Read uid text path)→ root
    if access root path uid {Readable} = Some (Val (att, text))
  | write:
    root -(Write uid text path)→ update path (Some (Val (att, text))) root
    if access root path uid {Writable} = Some (Val (att, text'))
  | chmod:
    root -(Chmod uid perms path)→
      update path (Some (map-attributes (others-update (λ-. perms)) file)) root
    if access root path uid {} = Some file and uid = 0 ∨ uid = owner (attributes
file)
  | creat:
    root -(Creat uid perms path)→
      update path (Some (Val (owner = uid, others = perms), [])) root
    if path = parent-path @ [name]
    and access root parent-path uid {Writable} = Some (Env att parent)
    and access root path uid {} = None
  | unlink:
    root -(Unlink uid path)→ update path None root
    if path = parent-path @ [name]
    and access root parent-path uid {Writable} = Some (Env att parent)
    and access root path uid {} = Some (Val plain)
  | mkdir:
    root -(Mkdir uid perms path)→
      update path (Some (Env (owner = uid, others = perms) Map.empty)) root
    if path = parent-path @ [name]
    and access root parent-path uid {Writable} = Some (Env att parent)
    and access root path uid {} = None
  | rmdir:
    root -(Rmdir uid path)→ update path None root
    if path = parent-path @ [name]
    and access root parent-path uid {Writable} = Some (Env att parent)
    and access root path uid {} = Some (Env att' Map.empty)
  | readdir:
    root -(Readdir uid names path)→ root
    if access root path uid {Readable} = Some (Env att dir)
    and names = dom dir

```

Certainly, the above specification is central to the whole formal development. Any of the results to be established later on are only meaningful to the outside world if this transition system provides an adequate model of real Unix systems. This kind of “reality-check” of a formal model is the well-

known problem of *validation*.

If in doubt, one may consider to compare our definition with the informal specifications given the corresponding Unix man pages, or even peek at an actual implementation such as [5]. Another common way to gain confidence into the formal model is to run simple simulations (see §4.2), and check the results with that of experiments performed on a real Unix system.

3.2 Basic properties of single transitions

The transition system $root -x \rightarrow root'$ defined above determines a unique result $root'$ from given $root$ and x (this holds rather trivially, since there is even only one clause for each operation). This uniqueness statement will simplify our subsequent development to some extent, since we only have to reason about a partial function rather than a general relation.

theorem *transition-uniq*:

```
  assumes  $root'$ :  $root -x \rightarrow root'$ 
    and  $root''$ :  $root -x \rightarrow root''$ 
  shows  $root' = root''$ 
  using  $root''$ 
proof cases
  case read
    with  $root'$  show ?thesis by cases auto
  next
    case write
      with  $root'$  show ?thesis by cases auto
  next
    case chmod
      with  $root'$  show ?thesis by cases auto
  next
    case creat
      with  $root'$  show ?thesis by cases auto
  next
    case unlink
      with  $root'$  show ?thesis by cases auto
  next
    case mkdir
      with  $root'$  show ?thesis by cases auto
  next
    case rmdir
      with  $root'$  show ?thesis by cases auto
  next
    case readdir
      with  $root'$  show ?thesis by cases blast+
qed
```

Apparently, file-system transitions are *type-safe* in the sense that the result of transforming an actual directory yields again a directory.

```

theorem transition-type-safe:
  assumes tr:  $root -x \rightarrow root'$ 
    and inv:  $\exists att\ dir. root = Env\ att\ dir$ 
  shows  $\exists att\ dir. root' = Env\ att\ dir$ 
proof (cases path-of x)
  case Nil
    with tr inv show ?thesis
    by cases (auto simp add: access-def split: if-splits)
next
  case Cons
    from tr obtain opt where
       $root' = root \vee root' = update\ (path-of\ x)\ opt\ root$ 
    by cases auto
    with inv Cons show ?thesis
    by (auto simp add: update-eq split: list.splits)
qed

```

The previous result may be seen as the most basic invariant on the file-system state that is enforced by any proper kernel implementation. So user processes — being bound to the system-call interface — may never mess up a file-system such that the root becomes a plain file instead of a directory, which would be a strange situation indeed.

3.3 Iterated transitions

Iterated system transitions via finite sequences of system operations are modeled inductively as follows. In a sense, this relation describes the cumulative effect of the sequence of system-calls issued by a number of running processes over a finite amount of time.

```

inductive transitions :: file  $\Rightarrow$  operation list  $\Rightarrow$  file  $\Rightarrow$  bool ( $- \Rightarrow - [90, 1000, 90] 100$ )
  where
    nil:  $root = [] \Rightarrow root$ 
    | cons:  $root = (x \# xs) \Rightarrow root''$  if  $root -x \rightarrow root'$  and  $root' = xs \Rightarrow root''$ 

```

We establish a few basic facts relating iterated transitions with single ones, according to the recursive structure of lists.

```

lemma transitions-nil-eq:  $root = [] \Rightarrow root' \longleftrightarrow root = root'$ 
proof
  assume  $root = [] \Rightarrow root'$ 
  then show  $root = root'$  by cases simp-all
next
  assume  $root = root'$ 
  then show  $root = [] \Rightarrow root'$  by (simp only: transitions.nil)
qed

```

```

lemma transitions-cons-eq:

```

$root = (x \# xs) \Rightarrow root'' \iff (\exists root'. root -x \rightarrow root' \wedge root' = xs \Rightarrow root'')$
proof
assume $root = (x \# xs) \Rightarrow root''$
then show $\exists root'. root -x \rightarrow root' \wedge root' = xs \Rightarrow root''$
by *cases auto*
next
assume $\exists root'. root -x \rightarrow root' \wedge root' = xs \Rightarrow root''$
then show $root = (x \# xs) \Rightarrow root''$
by (*blast intro: transitions.cons*)
qed

The next two rules show how to “destruct” known transition sequences. Note that the second one actually relies on the uniqueness property of the basic transition system (see §3.2).

lemma *transitions-nilD*: $root = [] \Rightarrow root' \Longrightarrow root' = root$
by (*simp add: transitions-nil-eq*)

lemma *transitions-consD*:

assumes *list*: $root = (x \# xs) \Rightarrow root''$
and *hd*: $root -x \rightarrow root'$
shows $root' = xs \Rightarrow root''$
proof –
from *list* **obtain** r' **where** $r': root -x \rightarrow r'$ **and** $root'': r' = xs \Rightarrow root''$
by *cases simp-all*
from r' *hd* **have** $r' = root'$ **by** (*rule transition-uniq*)
with $root''$ **show** $root' = xs \Rightarrow root''$ **by** *simp*
qed

The following fact shows how an invariant Q of single transitions with property P may be transferred to iterated transitions. The proof is rather obvious by rule induction over the definition of $root = xs \Rightarrow root'$.

lemma *transitions-invariant*:

assumes $r: \bigwedge r x r'. r -x \rightarrow r' \Longrightarrow Q r \Longrightarrow P x \Longrightarrow Q r'$
and *trans*: $root = xs \Rightarrow root'$
shows $Q root \Longrightarrow \forall x \in set\ xs. P x \Longrightarrow Q root'$
using *trans*
proof *induct*
case *nil*
show *?case* **by** (*rule nil.prem*)
next
case (*cons root x root' xs root''*)
note $P = \langle \forall x \in set\ (x \# xs). P x \rangle$
then have $P x$ **by** *simp*
with $\langle root -x \rightarrow root' \rangle$ **and** $\langle Q root \rangle$ **have** Q' : $Q root'$ **by** (*rule r*)
from P **have** $\forall x \in set\ xs. P x$ **by** *simp*
with Q' **show** $Q root''$ **by** (*rule cons.hyps*)
qed

As an example of applying the previous result, we transfer the basic type-safety property (see §3.2) from single transitions to iterated ones, which is a rather obvious result indeed.

theorem *transitions-type-safe*:
assumes $root = xs \Rightarrow root'$
and $\exists att\ dir. root = Env\ att\ dir$
shows $\exists att\ dir. root' = Env\ att\ dir$
using *transition-type-safe* **and** *assms*
proof (*rule transitions-invariant*)
show $\forall x \in set\ xs. True$ **by** *blast*
qed

4 Executable sequences

An inductively defined relation such as the one of $root -x \rightarrow root'$ (see §3.1) has two main aspects. First of all, the resulting system admits a certain set of transition rules (introductions) as given in the specification. Furthermore, there is an explicit least-fixed-point construction involved, which results in induction (and case-analysis) rules to eliminate known transitions in an exhaustive manner.

Subsequently, we explore our transition system in an experimental style, mainly using the introduction rules with basic algebraic properties of the underlying structures. The technique closely resembles that of Prolog combined with functional evaluation in a very simple manner.

Just as the “closed-world assumption” is left implicit in Prolog, we do not refer to induction over the whole transition system here. So this is still purely positive reasoning about possible executions; exhaustive reasoning will be employed only later on (see §5), when we shall demonstrate that certain behavior is *not* possible.

4.1 Possible transitions

Rather obviously, a list of system operations can be executed within a certain state if there is a result state reached by an iterated transition.

definition *can-exec* $root\ xs \longleftrightarrow (\exists root'. root = xs \Rightarrow root')$

lemma *can-exec-nil*: *can-exec* $root\ []$
unfolding *can-exec-def* **by** (*blast intro: transitions.intros*)

lemma *can-exec-cons*:
 $root -x \rightarrow root' \Longrightarrow can-exec\ root'\ xs \Longrightarrow can-exec\ root\ (x \# xs)$
unfolding *can-exec-def* **by** (*blast intro: transitions.intros*)

In case that we already know that a certain sequence can be executed we may destruct it backwardly into individual transitions.

lemma *can-exec-snocD*: *can-exec root (xs @ [y])*
 $\implies \exists \text{root}' \text{root}''. \text{root} = \text{xs} \Rightarrow \text{root}' \wedge \text{root}' - y \rightarrow \text{root}''$
proof (*induct xs arbitrary: root*)
case Nil
then show *?case*
by (*simp add: can-exec-def transitions-nil-eq transitions-cons-eq*)
next
case (Cons x xs)
from $\langle \text{can-exec root } ((x \# \text{xs}) @ [y]) \rangle$ **obtain** *r root''* **where**
x: root -x → r **and**
xs-y: r = (xs @ [y]) ⇒ root''
by (*auto simp add: can-exec-def transitions-nil-eq transitions-cons-eq*)
from *xs-y Cons.hyps* **obtain** *root' r'*
where *xs: r = xs ⇒ root'* **and** *y: root' -y → r'*
unfolding *can-exec-def* **by** *blast*
from *x xs* **have** *root = (x # xs) ⇒ root'*
by (*rule transitions.cons*)
with *y* **show** *?case* **by** *blast*
qed

4.2 Example executions

We are now ready to perform a few experiments within our formal model of Unix system-calls. The common technique is to alternate introduction rules of the transition system (see §3), and steps to solve any emerging side conditions using algebraic properties of the underlying file-system structures (see §2).

lemmas *eval = access-def init-def*

theorem $u \in \text{users} \implies \text{can-exec } (\text{init } \text{users})$

[*Mkdir u perms [u, name]*]

apply (*rule can-exec-cons*)

— *back-chain can-exec* (of *Cons*)

apply (*rule mkdir*)

— *back-chain Mkdir*

apply (*force simp add: eval*)⁺

— *solve preconditions of Mkdir*

apply (*simp add: eval*)

— *peek at resulting dir* (optional)

1. $u \in \text{users} \implies$

can-exec

(*Env* ($\downarrow \text{owner} = 0$, *others* = {*Readable*}))

($\lambda u. \text{if } u \in \text{users}$

then Some (*Env* ($\downarrow \text{owner} = u$, *others* = {*Readable*})) ($\lambda x. \text{None}$))

```

      else None)
    (u ↦
      Env (owner = u, others = {Readable})
      [name ↦ Env (owner = u, others = perms) (λx. None)]))
  []

```

```

apply (rule can-exec-nil)
  — back-chain can-exec (of Nil)
done

```

By inspecting the result shown just before the final step above, we may gain confidence that our specification of Unix system-calls actually makes sense. Further common errors are usually exhibited when preconditions of transition rules fail unexpectedly.

Here are a few further experiments, using the same techniques as before.

theorem $u \in users \implies can-exec (init users)$

```

  [Creat u perms [u, name],
   Unlink u [u, name]]
apply (rule can-exec-cons)
apply (rule creat)
apply (force simp add: eval)+
apply (simp add: eval)
apply (rule can-exec-cons)
apply (rule unlink)
apply (force simp add: eval)+
apply (simp add: eval)

```

peek at result:

```

1.  $u \in users \implies$ 
   can-exec
   (Env (owner = 0, others = {Readable})
    ((λu. if u ∈ users
      then Some (Env (owner = u, others = {Readable}) (λx. None))
      else None)
    (u ↦ Env (owner = u, others = {Readable}) (λx. None))))
  []

```

```

apply (rule can-exec-nil)
done

```

theorem $u \in users \implies Writable \in perms_1 \implies$

```

  Readable ∈ perms2  $\implies name_3 \neq name_4 \implies$ 
  can-exec (init users)
  [Mkdir u perms1 [u, name1],
   Mkdir u' perms2 [u, name1, name2],
   Creat u' perms3 [u, name1, name2, name3],
   Creat u' perms3 [u, name1, name2, name4],

```

$\text{Readdir } u \{name_3, name_4\} [u, name_1, name_2]$
apply (*rule can-exec-cons*, *rule transition.intros*,
(force simp add: eval)+, *(simp add: eval)?*)+

peek at result:

1. $u \in users \implies$
 $Writable \in perms_1 \implies$
 $Readable \in perms_2 \implies$
 $name_3 \neq name_4 \implies$
can-exec
 $(Env \{owner = 0, others = \{Readable\}\})$
 $((\lambda u. \text{if } u \in users$
 $\quad \text{then } Some (Env \{owner = u, others = \{Readable\}\}) (\lambda x. None)$
 $\quad \text{else } None)$
 $(u \mapsto$
 $\quad Env \{owner = u, others = \{Readable\}\})$
 $\quad [name_1 \mapsto$
 $\quad \quad Env \{owner = u, others = perms_1\})$
 $\quad [name_2 \mapsto$
 $\quad \quad \quad Env \{owner = u', others = perms_2\})$
 $\quad \quad [name_3 \mapsto Val (\{owner = u', others = perms_3\}, [])], name_4 \mapsto$
 $\quad \quad \quad Val (\{owner = u', others = perms_3\}, [])]]))$
 \square

apply (*rule can-exec-nil*)
done

theorem $u \in users \implies Writable \in perms_1 \implies Readable \in perms_3 \implies$
can-exec (init users)
 $[Mkdir u perms_1 [u, name_1],$
 $\quad Mkdir u' perms_2 [u, name_1, name_2],$
 $\quad Creat u' perms_3 [u, name_1, name_2, name_3],$
 $\quad Write u' "foo" [u, name_1, name_2, name_3],$
 $\quad Read u "foo" [u, name_1, name_2, name_3]]$
apply (*rule can-exec-cons*, *rule transition.intros*,
(force simp add: eval)+, *(simp add: eval)?*)+

peek at result:

1. $u \in users \implies$
 $Writable \in perms_1 \implies$
 $Readable \in perms_3 \implies$
can-exec
 $(Env \{owner = 0, others = \{Readable\}\})$
 $((\lambda u. \text{if } u \in users$
 $\quad \text{then } Some (Env \{owner = u, others = \{Readable\}\}) (\lambda x. None)$
 $\quad \text{else } None)$
 $(u \mapsto$
 $\quad Env \{owner = u, others = \{Readable\}\})$

```

      [name1 ↦
      Env (owner = u, others = perms1)
      [name2 ↦
      Env (owner = u', others = perms2)
      [name3 ↦ Val ((owner = u', others = perms3), "foo")]]]]))
□

```

```

apply (rule can-exec-nil)
done

```

5 Odd effects — treated formally

We are now ready to give a completely formal treatment of the slightly odd situation discussed in the introduction (see §1): the file-system can easily reach a state where a user is unable to remove his very own directory, because it is still populated by items placed there by another user in an uncouth manner.

5.1 The general procedure

The following theorem expresses the general procedure we are following to achieve the main result.

theorem *general-procedure*:

assumes *cannot-y*: $\bigwedge r r'. Q r \implies r -y \rightarrow r' \implies \text{False}$

and *init-inv*: $\bigwedge \text{root}. \text{init users} = \text{bs} \implies \text{root} \implies Q \text{root}$

and *preserve-inv*: $\bigwedge r x r'. r -x \rightarrow r' \implies Q r \implies P x \implies Q r'$

and *init-result*: $\text{init users} = \text{bs} \implies \text{root}$

shows $\neg (\exists xs. (\forall x \in \text{set } xs. P x) \wedge \text{can-exec root } (xs @ [y]))$

proof –

{

fix *xs*

assume *Ps*: $\forall x \in \text{set } xs. P x$

assume *can-exec*: $\text{can-exec root } (xs @ [y])$

then obtain *root' root''* **where** *xs*: $\text{root} = \text{xs} \implies \text{root}'$ **and** *y*: $\text{root}' -y \rightarrow \text{root}''$

by (*blast dest: can-exec-snocD*)

from *init-result* **have** $Q \text{root}$ **by** (*rule init-inv*)

from *preserve-inv xs this Ps* **have** $Q \text{root}'$

by (*rule transitions-invariant*)

from *this y* **have** False **by** (*rule cannot-y*)

}

then show *?thesis* **by** *blast*

qed

Here $P x$ refers to the restriction on file-system operations that are admitted after having reached the critical configuration; according to the problem specification this will become *uid-of* $x = \text{user}_1$ later on. Furthermore, y

refers to the operations we claim to be impossible to perform afterwards, we will take *Rmdir* later. Moreover Q is a suitable (auxiliary) invariant over the file-system; choosing Q adequately is very important to make the proof work (see §5.3).

5.2 The particular situation

We introduce a few global declarations and axioms to describe our particular situation considered here. Thus we avoid excessive use of local parameters in the subsequent development.

context

```

fixes users :: uid set
  and user1 :: uid
  and user2 :: uid
  and name1 :: name
  and name2 :: name
  and name3 :: name
  and perms1 :: perms
  and perms2 :: perms
assumes user1-known: user1 ∈ users
  and user1-not-root: user1 ≠ 0
  and users-neq: user1 ≠ user2
  and perms1-writable: Writable ∈ perms1
  and perms2-not-writable: Writable ∉ perms2
notes facts = user1-known user1-not-root users-neq
  perms1-writable perms2-not-writable

```

begin

definition

```

bogus =
  [Mkdir user1 perms1 [user1, name1],
   Mkdir user2 perms2 [user1, name1, name2],
   Creat user2 perms2 [user1, name1, name2, name3]]

```

definition *bogus-path* = [*user*₁, *name*₁, *name*₂]

The *local.bogus* operations are the ones that lead into the uncouth situation; *local.bogus-path* is the key position within the file-system where things go awry.

5.3 Invariance lemmas

The following invariant over the root file-system describes the bogus situation in an abstract manner: located at a certain *path* within the file-system is a non-empty directory that is neither owned nor writable by *user*₁.

definition

invariant root path \longleftrightarrow
 $(\exists \text{ att dir.}$
 $\text{access root path user}_1 \{ \} = \text{Some (Env att dir)} \wedge \text{dir} \neq \text{Map.empty} \wedge$
 $\text{user}_1 \neq \text{owner att} \wedge$
 $\text{access root path user}_1 \{ \text{Writable} \} = \text{None})$

Following the general procedure (see §5.1) we will now establish the three key lemmas required to yield the final result.

1. The invariant is sufficiently strong to entail the pathological case that user_1 is unable to remove the (owned) directory at $[\text{user}_1, \text{name}_1]$.
2. The invariant does hold after having executed the *local.bogus* list of operations (starting with an initial file-system configuration).
3. The invariant is preserved by any file-system operation performed by user_1 alone, without any help by other users.

As the invariant appears both as assumptions and conclusions in the course of proof, its formulation is rather critical for the whole development to work out properly. In particular, the third step is very sensitive to the invariant being either too strong or too weak. Moreover the invariant has to be sufficiently abstract, lest the proof become cluttered by confusing detail.

The first two lemmas are technically straight forward — we just have to inspect rather special cases.

lemma *cannot-rmdir*:

assumes *inv*: *invariant root bogus-path*
and *rmdir*: $\text{root} \text{---} (\text{Rmdir user}_1 [\text{user}_1, \text{name}_1]) \rightarrow \text{root}'$
shows *False*

proof —

from *inv* **obtain** *file* **where** $\text{access root bogus-path user}_1 \{ \} = \text{Some file}$
unfolding *invariant-def* **by** *blast*

moreover

from *rmdir* **obtain** *att* **where** $\text{access root } [\text{user}_1, \text{name}_1] \text{ user}_1 \{ \} = \text{Some (Env att Map.empty)}$

by *cases auto*

then have $\text{access root } ([\text{user}_1, \text{name}_1] @ [\text{name}_2]) \text{ user}_1 \{ \} = \text{Map.empty name}_2$

by (*simp only: access-empty-lookup lookup-append-some*) *simp*

ultimately show *False* **by** (*simp add: bogus-path-def*)

qed

lemma

assumes *init*: $\text{init users} = \text{bogus} \Rightarrow \text{root}$

shows *init-invariant*: *invariant root bogus-path*

supply *eval* = *facts access-def init-def*

using *init*

apply (*unfold bogus-def bogus-path-def*)

apply (*drule transitions-consD*, *rule transition.intros*,
 (*force simp add: eval*)+, (*simp add: eval*)?)+
 — evaluate all operations
apply (*drule transitions-nilD*)
 — reach final result
apply (*simp add: invariant-def eval*)
 — check the invariant
done

At last we are left with the main effort to show that the “bogosity” invariant is preserved by any file-system operation performed by $user_1$ alone. Note that this holds for any $path$ given, the particular $local.bogus-path$ is not required here.

lemma *preserve-invariant*:

assumes $tr: root -x \rightarrow root'$
and $inv: invariant\ root\ path$
and $uid: uid\ of\ x = user_1$
shows $invariant\ root'\ path$

proof —

from inv **obtain** $att\ dir$ **where**
 $inv1: access\ root\ path\ user_1\ \{\} = Some\ (Env\ att\ dir)$ **and**
 $inv2: dir \neq Map.empty$ **and**
 $inv3: user_1 \neq owner\ att$ **and**
 $inv4: access\ root\ path\ user_1\ \{Writable\} = None$
by (*auto simp add: invariant-def*)

from $inv1$ **have** $lookup: lookup\ root\ path = Some\ (Env\ att\ dir)$
by (*simp only: access-empty-lookup*)

from $inv1\ inv3\ inv4$ **and** $user_1-not-root$
have $not-writable: Writable \notin others\ att$
by (*auto simp add: access-def split: option.splits*)

show *?thesis*

proof *cases*

assume $root' = root$
with inv **show** $invariant\ root'\ path$ **by** (*simp only:*)

next

assume $changed: root' \neq root$
with tr **obtain** opt **where** $root': root' = update\ (path-of\ x)\ opt\ root$
by *cases auto*

show *?thesis*

proof (*rule prefix-cases*)

assume $path-of\ x \parallel path$

with $inv\ root'$

have $\bigwedge perms. access\ root'\ path\ user_1\ perms = access\ root\ path\ user_1\ perms$
by (*simp only: access-update-other*)

with inv **show** $invariant\ root'\ path$

by (*simp only: invariant-def*)

```

next
  assume prefix (path-of x) path
  then obtain ys where path: path = path-of x @ ys ..

show ?thesis
proof (cases ys)
  assume ys = []
  with tr uid inv2 inv3 lookup changed path and user1-not-root
  have False
  by cases (auto simp add: access-empty-lookup dest: access-some-lookup)
  then show ?thesis ..
next
  fix z zs assume ys: ys = z # zs
  have lookup root' path = lookup root path
  proof -
    from inv2 lookup path ys
    have look: lookup root (path-of x @ z # zs) = Some (Env att dir)
      by (simp only:)
    then obtain att' dir' file' where
      look': lookup root (path-of x) = Some (Env att' dir') and
      dir': dir' z = Some file' and
      file': lookup file' zs = Some (Env att dir)
      by (blast dest: lookup-some-upper)

    from tr uid changed look' dir' obtain att'' where
      look'': lookup root' (path-of x) = Some (Env att'' dir')
      by cases (auto simp add: access-empty-lookup lookup-update-some
        dest: access-some-lookup)
    with dir' file' have lookup root' (path-of x @ z # zs) =
      Some (Env att dir)
      by (simp add: lookup-append-some)
    with look path ys show ?thesis
      by simp
  qed
  with inv show invariant root' path
    by (simp only: invariant-def access-def)
  qed
next
  assume strict-prefix path (path-of x)
  then obtain y ys where path: path = path-of x @ y # ys ..

  obtain dir' where
    lookup': lookup root' path = Some (Env att dir') and
    inv2': dir' ≠ Map.empty
  proof (cases ys)
    assume ys = []
    with path have parent: path = path @ [y] by simp
    with tr uid inv4 changed obtain file where
      root' = update (path-of x) (Some file) root

```



```

    by cases auto
  with lookup parent have lookup root' path = Some (Env att (dir(y→file)))
    by (simp only: update-append-some update-cons-nil-env)
  moreover have dir(y→file) ≠ Map.empty by simp
  ultimately show ?thesis ..
next
fix z zs assume ys: ys = z # zs
with lookup root' path
have lookup root' path = Some (update (y # ys) opt (Env att dir))
  by (simp only: update-append-some)
also obtain file' where
  update (y # ys) opt (Env att dir) = Env att (dir(y→file'))
proof -
  have dir y ≠ None
  proof -
    have dir y = lookup (Env att dir) [y]
      by (simp split: option.splits)
    also from lookup have ... = lookup root (path @ [y])
      by (simp only: lookup-append-some)
    also have ... ≠ None
    proof -
      from ys obtain us u where rev-ys: ys = us @ [u]
        by (cases ys rule: rev-cases) simp
      with tr path
      have lookup root ((path @ [y]) @ (us @ [u])) ≠ None ∨
        lookup root ((path @ [y]) @ us) ≠ None
        by cases (auto dest: access-some-lookup)
      then show ?thesis
        by (fastforce dest!: lookup-some-append)
    qed
  finally show ?thesis .
qed
with ys show ?thesis using that by auto
qed
also have dir(y→file') ≠ Map.empty by simp
ultimately show ?thesis ..
qed

from lookup' have inv1': access root' path user1 {} = Some (Env att dir')
  by (simp only: access-empty-lookup)

from inv3 lookup' and not-writable user1-not-root
have access root' path user1 {Writable} = None
  by (simp add: access-def)
with inv1' inv2' inv3 show ?thesis unfolding invariant-def by blast
qed
qed
qed

```

5.4 Putting it all together

The main result is now imminent, just by composing the three invariance lemmas (see §5.3) according to the overall procedure (see §5.1).

corollary

assumes *bogus: init users = bogus* \Rightarrow *root*

shows $\neg (\exists xs. (\forall x \in \text{set } xs. \text{uid-of } x = \text{user}_1) \wedge$
can-exec root (xs @ [Rmdir user₁ [user₁, name₁]]))

proof –

from *cannot-rmdir init-invariant preserve-invariant*
and *bogus show ?thesis* **by** (*rule general-procedure*)

qed

end

end

References

- [1] G. Bauer, T. Nipkow, D. v. Oheimb, L. C. Paulson, T. M. Rasmussen, C. Tabacnyj, and M. Wenzel. The supplemental Isabelle/HOL library. <https://isabelle.in.tum.de/library/HOL/Library/document.pdf>, 2002.
- [2] W. Naraschewski. *Teams as Types — A Formal Treatment of Authorization in Groupware*. PhD thesis, TU München, 2001. Submitted.
- [3] T. Nipkow, L. C. Paulson, and M. Wenzel. *Isabelle’s Logics: HOL*, 2000. <https://isabelle.in.tum.de/doc/logics-HOL.pdf>.
- [4] A. S. Tanenbaum. *Modern Operating Systems*. Prentice-Hall, 1992.
- [5] L. Torvalds et al. The Linux kernel archives. <http://www.kernel.org>.
- [6] The Unix heritage society. <http://minnie.cs.adfa.edu.au/TUHS/>.
- [7] M. Wenzel. Isar — a generic interpretative approach to readable formal proof documents. In Y. Bertot, G. Dowek, A. Hirschowitz, C. Paulin, and L. Theiry, editors, *Theorem Proving in Higher Order Logics: TPHOLs ’99*, volume 1690 of *LNCS*, 1999.
- [8] M. Wenzel. *The Isabelle/Isar Reference Manual*, 2002. <https://isabelle.in.tum.de/doc/isar-ref.pdf>.